

CONTRACT SPECIFICATIONS FOR

DISTRICT OF LAKELAND NO. 521

MCPHEE LAKE LANDFILL DECOMMISSIONING PROJECT

September 11th, 2026

Prepared by PINTER & Associates Ltd.

These Contract Documents are for the sole use of the Engineer, and of the Owner, Contractor, Subcontractors, and Suppliers having a contract for the execution of the Works covered in the Contract Documents in whole or in part. The Contract Documents contain proprietary and confidential information that shall not be reproduced in any manner or disclosed to or discussed with any other parties without the express written permission of the Engineer. Information in these documents is to be considered the intellectual property of the Engineer in accordance with Canadian copyright law.

DIVISION 00 – BIDDING AND CONTRACT REQUIREMENTS

Section Number	Section Title	No. of Pages
00 01 01	Project Title Page	(x)
00 01 05	Certifications Page	1
00 01 10	Table of Contents	2
00 01 15	List of Drawings	1
00 11 16	Invitation to Bid	1
00 21 13	Instructions to Bidders	7
00 30 00	Information Available to Bidders	1
00 41 00	Bid Form	5
00 43 36	Subcontract List	1
00 43 43	Force Account Rates	1
00 43 44	Equipment Supplier List	1
00 43 83	Construction Schedule	1
00 45 13	Bidders' Qualifications	1
00 61 00	Bid Bond	3
00 61 13	Labour and Material Payment Bond	4
00 61 13.13	Performance Bond	3
00 62 16	Certificate of Insurance	3
00 73 16	General Insurance	3
00 91 13	Addenda	1

DIVISION 01 – GENERAL INSTRUCTIONS

Section Number	Section Title	No. of Pages
01 00 00	General Requirements	10
01 11 00	Summary of Work	5
01 22 00	Measurement and Payment	5
01 28 00	Management and Co-ordination	2
01 29 00	Payment Procedures	3
01 31 20	Contract Meetings	4
01 33 00	Submittal Procedures	5
01 34 00	Shop Drawings, Product Data and Samples	3
01 35 00.06	Special Procedures for Traffic Control	2
01 35 29.06	Health and Safety Requirements	4
01 35 43	Environmental Procedures	5
01 41 00	Regulatory Requirements	2
01 42 19	Reference Standards	3
01 45 00	Quality Control	3
01 51 00	Existing and Temporary Utilities	2
01 52 00	Construction Facilities	5
01 55 20	Existing and Temporary Roads	2
01 61 00	Common Product Requirements	4
01 71 23	Field Engineering	2
01 74 11	Cleaning	2
01 77 00	Closeout Procedures	2

DIVISION 02 – SITE CONDITIONS

Section Number	Section Title	No. of Pages
02 01 40	Care of Water	2

DIVISION 31 – EARTHWORKS

Section Number	Section Title	No. of Pages
31 11 00	Clearing and Grubbing	5
31 14 13	Soil Stripping and Stockpiling	3
31 21 00	General Excavation	5
31 22 13	Rough Grading	3
31 22 50	Compacted Earth Fill	4
31 23 20	Earthwork and Granular Material Testing	1
31 23 33.01	Excavating, Trenching, & Backfilling	7
31 27 00	Subgrade Preparation	2
31 27 20	Compacted Clay Liner (CCL)	2
31 29 00	Grass Seeding	2
31 95 10	Restoration of Sitework	2

A-NMS000115++

District of Lakeland No. 521
Landfill Decommissioning
Project Specification

LIST OF DRAWINGS

Section 00 01 15
Page 1 of 1
2026-09-10

Engineering Drawings

<u>Drawing Number</u>	<u>Drawing Title</u>
FIG. 1	Site Location
FIG. 2	Site Layout
FIG. 3	Sections

Electronic submissions containing Bids clearly marked for the **“District of Lakeland No. 521, SK Landfill Decommissioning”** and addressed to **Jessica Georget** must be sent to **public.works@lakeland521.ca** before **3:00 pm CST on the 28th day of September 2026**. Bids submitted after the Bid closing time will not be accepted and will be returned to the Bidder unopened. The time as indicated by the declining time clock on the Online Bidding System shall be the official time for closing.

The work involves the construction of the final cover at the District of Lakeland No. 521 McPhee Lake Landfill.

Contract Documents will be available on or after September 14th, 2026 free of charge. Bidders are required to check for any updated information and addenda issued before the closing date and time.

Any changes to the Bid Documentation will be issued by means of written addenda and will form part of the Bid. No amendment of any kind to the tender is effective unless it is posted in a formal written addendum. Upon submitting to this Bid, Bidders will be deemed to have received notice of all addenda and deemed to have considered the information for inclusion in the tender submitted.

Bids must be accompanied by the specified Bid Bond and Consent of Surety Company payable to the District of Lakeland No. 521. Failure to provide Bid Bond and Consent of Surety Company will be a factor taken into account when awarding the contract.

The lowest or any bid will not necessarily be accepted.

The work is expected to be completed in 2026.

Owner's Name and Address:

District of Lakeland No. 521
Box 27,
Christopher Lake, SK S0J 0N0

Attention: Jessica Georget
Telephone: (306) 982-2010
Email: public.works@lakeland521.ca

PART 1 – GENERAL1.1 DEFINITIONS

.1

Definitions

- .1 “Bid Closing Time” means the time and date stipulated for receipt of bids in Article 1.3.1.1 of this Sections as may be amended by addendum.
- .2 “Bid Documents” mean the bid documents obtained in accordance with Article 1.3.1.1 of these Instructions to Bidders and comprising all of the documents and drawings listed in the Table of Contents thereof and any addenda that may be issued thereto.
- .3 “Bid Form” means Section 00 41 00 of the Bid Documents and the supplements thereto.
- .4 “Bidder” means any holder of Bid Documents.
- .5 “Total Bid” means the amount entered by the Bidder into the Bid Form on the line “TOTAL BID: (excluding GST & PST). The Total Bid will be only one of the criteria for the evaluation of bids. Bids will be evaluated in accordance with the evaluation criteria identified in Section 1.11.
- .6 “Bid Price” means the monetary sum identified in Bid Form as an offer to perform the work.

.2

Additional Definitions

- .1 The definitions set out in CCDC 4 are incorporated into and form part of this Section 00 21 13 – Instructions to Bidders.

1.2 LIMITATION OF
LIABILITY

.1

The Bidder agrees that the Owner’s sole Obligation, in return for the Bidder’s preparation and submission of its bid, is to give consideration to the bid in accordance with the Contract Documents. The Bidder hereby waives any claim for damages or costs of any nature against the Owner and the Engineer (including, without limitation, the cost of preparing and submitting the Tender and any anticipated profits and contributions to overhead) arising out of the Owner’s use of its discretion under the Contract Documents and the Engineer’s advice to the Owner.

1.3 INVITATION

.1

Invitational Tender:

- .1 Ensure offers are signed under seal, executed, and dated, and are received by email at public.works@lakeland521.ca before 3:00 pm CST on the 28th day of September 2026-
- .2 Offers submitted after above time will be returned to Bidder unopened.
- .3 Offers will be opened privately immediately after time for receipt of Bids.
- .4 Amendments to submitted offer will be permitted if received in writing through email prior to Bid closing and if endorsed by same party or parties who signed and sealed the original offer.

1.4 INTENT

- .1 Intent of this Invitational Tender is to obtain an offer to perform Work to complete the construction of a Landfill Cell Closure, for a Unit Price contract, in accordance with Contract Documents. Refer to Section 01 00 00 – General Requirements.
- .2 Perform Work within time in Section 01 11 00 – Summary of Work.
- .3 Initiate Work within timeline stated within Section 01 11 00 – Summary of Work.

1.5 CONTRACT/BID DOCUMENTS

- .1 Availability:
 - .1 Electronic versions of Bid Documents will be provided to Invited firms at the commencement of the bid period.
 - .2 Bid Documents are made available only for purpose of obtaining offers for this project. Their use does not confer license or grant for other purposes.
 - .3 Bid documents irregularly obtained from sources other than those provided for in Article 1.5.1.1 (“unofficial bid documents”) are used entirely at the risk of the Person who holds them. Neither Engineer nor Owner undertakes to provide information or addenda to Persons holding unofficial bid documents. Any use which a Person makes of unofficial bid documents or any reliance on or decisions to be made based on them, are the responsibility of such Persons. Engineer and Owner accept no responsibility for damages, if any, suffered by any Person as a result of decisions made or actions based on unofficial bid documents. Bids received from Persons holding unofficial bid documents may be declared informal at the sole and unfettered discretion of the Owner and if so declared will be rejected.
- .2 Examination:
 - .1 Upon receipt of Bid Documents verify that documents are complete. Notify Engineer should the document be incomplete.
 - .2 Immediately notify the contact person upon finding discrepancies or omissions in Bid Documents.
- .3 The Owner reserves the right to either cancel the invitation to tender, not award any contract, negotiate a tender and awarded contract, or add or remove scope from the accepted tender and awarded contract.
- .4 Queries/Addenda:
 - .1 Direct questions to public.works@lakeland521.ca in writing.
 - .2 All question responses will be provided in writing through email.
 - .3 Addenda will be in written form and may be issued the bidding period. Addenda will become part of Contract Documents. Include costs in Bid Price.
 - .4 The deadline for questions requested by Bidders must be in writing by the 21st day of September 2026-
 - .5 If required an addendum may follow the reply to bidders.

.5 Product/System Options:

- .1 Where Bid Documents stipulate a particular product, substitutions will be considered by the owner only after formal award of the project. Do not include contractor-initiated options within the bid submission.

1.6 SITE EXAMINATIONS

.1 Site Examination:

- .1 The Bidder is fully responsible for obtaining all information required for the preparation of his Bid and, prior to submitting a Bid, the Bidder shall have visited and carefully examined the Place of the Work and the surrounding area in a reasonable and prudent manner and satisfied itself as to the scope and character of the Work and all conditions and information affecting the Work and how the Work is to be completed, including, without limitation, the nature and location of the Work, working areas, storage areas, local features including private property and utilities, access to and at the Place of the Work, weather conditions and any other factors which may influence the performance of the Work and/or the pricing of the Work.
- .2 Bidders must notify the Owner at least one business day prior to visiting the place of the work.

1.7 QUALIFICATIONS

.1 Bidders' Qualifications:

- .1 Submit complete Document 00 45 13 - Bidders' Qualification form with the Bid Form.
- .2 Indicate the OHS Act Certificate of Registration number. Refer to Supplementary Conditions.

.2 Subcontractors:

- .1 Owner reserves right to reject proposed subcontractor for reasonable cause.

1.8 CONSTRUCTION
SCHEDULE

.1 Required Construction Completion Date:

- .1 Construction will be completed no later than the 30th day of November

1.9 LIQUIDATED DAMAGES

.1 Liquidated Damages:

- .1 Failure to meet the above construction completion date will result in liquidated damages fees to accrue at a rate of \$4,000/day each calendar day. Fees will accrue starting the day after required construction completion date and continue until Substantial Completion of the project.

1.10 BID SUBMISSION

.1 Bid Ineligibility:

- .1 Bids that are unsigned, improperly signed or sealed, conditional, illegible, obscure, contain arithmetical errors, erasures, alterations, or irregularities of any kind, may be declared informal at Owner's discretion.

- .2 Bids with Bid Forms and enclosures which are improperly prepared may be declared informal at Owner's discretion.
- .3 Bids that fail to include security deposit, bonding or insurance requirements will be declared informal.
- .2 Submissions:
 - .1 Bidders are solely responsible for delivery of their Bids in manner and time prescribed.
 - .2 Submit a copy of executed offer on Bid Forms provided, signed and with corporate seal together with required security by email, clearly identified with Bidder's name, project name, and Owner's name on outside.
 - .3 An abstract of submitted Bids will be made available to Bidders following Bid opening.
- .3 Bid Modifications:
 - .1 Written amendments to the submitted bids shall be permitted if received by email to public.works@lakeland521.ca at the office where bids are being opened prior to Bid Closing Time, provided that bid amendments are endorsed by the same party or parties who signed and sealed the offer.
 - .2 The onus is on Bidder to ensure timely receipt of bid modifications. Owner makes no assurances regarding availability of communication lines or equipment. To be considered, bid modifications must be received prior to Bid Closing Time.
 - .3 An amendment that expressly or by inference discloses Bidder's Total Bid or other material element of the bid, such that in the opinion of Owner the confidentiality of the bid is breached, shall be valid cause for Owner, at their sole discretion to reject the bid.
- .4 Bid Withdrawal:
 - .1 Bidder shall be permitted to withdraw bid without prejudice, provided a request, in writing, signed by the same person or persons who signed the Bid Form is received at the email address designated in the Bid Documents before Bid Closing Time. Error on the part of Bidder in preparing the bid confers no right to the withdrawal of the bid after it has been opened.

1.11 BID ENCLOSURES/ REQUIREMENTS

- .1 Security Deposit:
 - .1 Bids are to be accompanied by security deposit as follows: Bid Bond or certified cheque in an amount not less than 10 percent of Bid price.
 - .2 Endorse Bid Bond or certified cheque in name of Owner as obligee, signed and sealed by principal (Contractor) and surety.
 - .3 Use most current edition CCDC approved bond forms.
 - .4 Security deposit will be returned after delivery to Owner of required Performance and Labour and Materials Payment Bond(s) by accepted Bidder.
 - .5 If no contract is awarded, security deposits will be returned.
 - .6 If accepted Bidder fails for any reason to execute Contract Agreement or to provide the surety bonds stipulated in Section

00 73 16 – Insurance within the time agreed to in the Bid Form, and such extension of time as may be granted by Owner, the accepted by Bidders' surety shall pay to the Owner the amount of the difference in money between the Total Bid and the amount for which Owner may legally contract with another party to perform the work, if the latter amount be in excess of the former.

- .2 Consent of Surety:
 - .1 Submit with Bid Form and Bid Bond, Consent of Surety, stating that surety providing Bid Bond is willing to supply Performance and Labour and Materials Payment Bond specified.
 - .2 Include cost of bonds in Bid Price.
- .3 Performance Assurance:
 - .1 Accepted Bidder must provide Performance and Labour and Materials Payment Bond as described in Section 00 61 13.
 - .2 Include cost of bonds in Bid Price.
- .4 Insurance:
 - .1 Provide signed "Undertaking of Insurance" on standard form provided by insurance company stating intention to provide insurance to Bidder in accordance with insurance requirements of Contract Documents.
- .5 Bid Form Requirements:
 - .1 Bidder, in submitting an offer, accepts time period stated in Contract documents for performing Work. Completion date in Agreement is completion time added to commencement date.
- .6 Fees for Changes in Work:
 - .1 Include in Bid Form, percentage markup for overhead and profit applicable for changes in Work, whether additions to or deductions from Work on which Bid price is based.
 - .2 Include in Bid Form, fees proposed for subcontract work for changes (both additions and deductions) in Work. Contractor may apply markup as noted, to subcontractor's gross (net plus markup) costs on additional work.
- .7 Bid Signing:
 - .1 Bid Form to be signed under seal by Bidder.
 - .2 Sole Proprietorship: signature of sole proprietor in presence of witness who shall also sign. Insert words "Sole Proprietor" under signature. Affix seal if applicable.
 - .3 Partnership: signature of all partners in presence of witness who shall also sign. Insert word 'Partner' under each signature. Affix seal to each signature.
 - .4 Limited Company: signature of duly authorized signing officer(s) in normal signatures. Insert officer's capacity in which signing officer acts, under each signature. Affix corporate seal. If Bid is signed by officials other than President and Secretary of company, or President-Secretary-Treasurer of company, copy of by-law

resolution of Board of Directors authorizing them to do so must also be submitted within Bid envelope.

.5 Incorporated Company: signature of duly authorized signing officer(s) in normal signatures. Insert officer's capacity in which signing officer acts, under each signature. Affix corporate seal. If Bid is signed by officials other than President and Secretary of company, or President-Secretary-Treasurer of company, copy of by-law resolution of Board of Directors authorizing them to do so must also be submitted within Bid envelope.

.6 Joint Venture: each party of joint venture must execute Bid under respective seals in manner appropriate to such party as described above, similar to requirements of Partnership.

.8 Supplements to Bid Form to be submitted with bid:

.1 Document 00 61 00 – Bid Bond.

.2 Document 00 43 36 – Subcontract List. List the names of all subcontractors. Identify portion(s) of the work to be performed by each subcontractor.

.3 Document 00 43 83 – Construction Schedule. Provide the requested schedule information to demonstrate ability to plan work and respond to critical deadlines.

.4 Document 00 45 13 – Bidders' Qualifications. Complete in all details and submit with the Bid Form.

.5 Document 00 43 43 – Force Account Rates. List all personnel and equipment hourly rates likely to be used on the project. These rates will form the basis for payment for force account work carried out in accordance with CCDC 4.

.6 Document 00 61 13 13 – Performance Bond. A Consent of Surety Letter that is required for submission.

.7 Document 00 62 16 – Certificate of Insurance.

.8 Document 00 61 13 – Labour and Material Payment Bond. A Consent of Surety Letter that is required for submission

1.12 OFFER ACCEPTANCE/ REJECTION

.1 Duration of Offer:

.1 Bids to remain open to acceptance, and irrevocable for 30 days after Bid closing date.

.2 Acceptance of Offer:

.1 Owner reserves right to accept or reject any or all offers.

.2 After acceptance by Owner, a written Bid acceptance will be issued to the successful Bidder.

.3 Unsuccessful bidders will be notified promptly of the process outcome.

.4 After Bid has been accepted, unsuccessful Bids will be returned to respective Bidders with submitted Bid securities and other requested enclosures.

1.13 PROJECT FUNDING

.1

This project is funded in part by the Government of Saskatchewan and the Client:

1.14 BID EVALUATION

.1

Bids will be evaluated via a points system with the following points distribution:

.1 Price – 70 points

.a Points for price will be allotted according to a mathematical formula in which the lowest bidder receives full points and all other bidders receive points in proportion to their price as compared to the lowest bid.

.2 Experience – 20 points

.a Points for experience will be awarded according to the bidder's or their subcontractor's demonstrated experience in the last 5 years. The project examples must be similar in size, scope and nature to the Project including a history of its on-schedule and on-budget performance of such projects. The exact allotment of these points is necessarily subjective and will be at the sole discretion of the evaluator(s).

.3 Schedule – 5 points

.a Points for Schedule will be allotted according to a mathematical formula in which the bidder with the shortest schedule will be awarded full points and all other bidders receive points in proportion to the length of their schedule as compared to the shortest schedule.

.4 Local Content – 5 points

.a Points for local content and experience will be awarded according to the bidder's proximity to the job and/or commitment to include local labourers on the job. The exact allotment of these points is necessarily subjective and will be at the sole discretion of the evaluator(s).

.2 Only qualified Bids will be considered by the Owner.

.3 Bids will be evaluated based on the Stipulated Price (Base Bid Price) (as well as the Alternative Prices and Unit Prices included in the Appendices to the Bid Form).

.4 The Owner may, in its sole discretion, request clarification from a Bidder during the evaluation process. In responding to a request for clarification, the Bidder shall not revise, amend, or otherwise modify their submission alter its Bid.

.5 In assessing Bids, the Owner expects to select the Bidder that will provide the overall best value to the Owner, as determined by the Owner in its sole discretion

PART 2 – PRODUCTS2.1 NOT USED

.1

Not Used.

PART 3 – EXECUTION

3.1 NOT USED .1 Not Used.

END OF SECTION

PART 1 – GENERAL

1.1 REPORT .1 Not Used.

PART 2 – PRODUCTS

2.1 NOT USED .1 Not used.

PART 3 – EXECUTION

3.1 NOT USED .1 Not used.

END OF SECTION

TO: District of Lakeland No. 521
Box 27
Christopher Lake, SK S0J 0N0

The undersigned Bidder, having carefully examined the Contract Documents and locality of the proposed work, and having full knowledge of the work required and the materials to be furnished and used, hereby agrees to provide all necessary materials, supervision, labour, and equipment and perform and complete all work, and fulfill everything as set forth and in strict accordance with the Contract Documents and Addenda numbered ¹ _____ for the prices stated in the Schedule of Quantities and Prices.

¹ Bidder to fill each Addendum No. received, e.g., 1,2,3, etc. as applicable.

The undersigned also agrees:

- 1 That Owner is in no way obligated to accept this bid;
- 2 that Owner may, at Owner's discretion, award to other than the low Bidder;
- 3 that, if the Bid Form is improperly completed or incomplete, Owner shall have the right to disqualify and/or reject this bid;
- 4 that this bid is made without knowledge of the bid prices to be submitted for this work by any other company, firm, or person;
- 5 that this bid is made without any connection or arrangement with any other company, firm, or person submitting a bid for this work;
- 6 that this bid is made without any undisclosed connection or arrangement with any other company, firm, or person submitting a bid for this work;
- 7 that this bid is irrevocable for sixty (60) days after the closing date for receipt of bids and that the Owner may, at any time within such period, accept this bid whether any other bid has previously been accepted or not and whether Notice of Award of a contract has been given or not;
- 8 to deposit with Owner a Performance Bond and Labour and Material Payment Bond on the forms provided in these documents and for the amount specified in the CCDC and the specified insurance endorsement certificates and execute the Contract Agreement in accordance with the time periods specified in the CCDC, such time periods being extended only on the written approval of Owner;
- 9 to commence and proceed actively with the work promptly following receipt of the Notice to Proceed, and to complete all work under the Contract within a period of * _____ calendar days from Notice of Award, subject to the provisions of the CCDC for extension of Contract Time;
- 10 to compensate Owner in accordance with the Contract Documents if the work is not completed with the Contract Time;
- 11 to do all extra work not reasonably interfere from the specifications or drawings, but called for in writing by Engineer and to accept as full compensation therefore payment in accordance with the provisions of the CCDC;
- 12 that estimates of quantities shown in the Bid Form serve only to provide a bases for comparing bids and that no representations have been made by either Owner or Engineer that the actual quantities will even approximately correspond therewith, and further, that Owner has the right to increase or decrease the quantities in any or all items and to eliminate items entirely from the work;
- 13 that payment for the work done will be made on the basis of the quantities measured by Engineer and at the prices shown the Bid Form which shall be compensation in full for the work done under the terms of the Contract, exclusive of GST payable by Owner; and
- 14 that payment for the work done will be made at the bid price(s) which shall be compensation in full for the work done under the terms of the Contract, exclusive of GST payable by Owner.

* Contractor to complete

SCHEDULE OF QUANTITIES AND PRICES

Item	Description	Unit	Quantity	Unit Price	Extension
1.0	Miscellaneous Items				
1.1	Mobilization and Demobilization	L.S.	1	\$ _____	\$ _____
1.2	Bonding and Insurance	L.S.	1	\$ _____	\$ _____
1.3	Supervision	L.S.	1	\$ _____	\$ _____
1.4	Live Out Allowance	L.S.	1	\$ _____	\$ _____
				Subtotal	\$ _____
2.0	Site Work				
2.1	Site Grading, includes levelling slope	m ²	2,500	\$ _____	\$ _____
2.2	Loading, Hauling and Installing Clay for Clay Liner in 150 mm Lifts	m ³	1,000	\$ _____	\$ _____
2.3	Loading, Hauling and Installing Subsoil	m ³	740	\$ _____	\$ _____
2.4	Installing Topsoil	m ³	500	\$ _____	\$ _____
2.5	Seeding and Fertilizing	m ²	2,500	\$ _____	\$ _____
				Subtotal	\$ _____

BID SUMMARY

TOTAL BID (excluding GST)	\$ _____
Goods and Services Tax	\$ _____

Total – Value of Materials	\$ _____
Total – Value of Saskatchewan Provincial Sales Tax at 6.00 %	\$ _____

SUPPLEMENTS TO BID FORM

The following Supplements to Bid Form are included with and form a part of the Bid. We understand that the information provided on these forms will be used by the Owner during Bid analysis.

- 00 43 36 - Subcontract List
- 00 43 83 - Construction Schedule
- 00 45 13 - Bidders Qualifications
- 00 61 00 - Bid Bond
- 00 61 13 - Labour and Material Payment Bond
- 00 61 13.13 - Performance Bond
- 00 62 16 - Certificate of Insurance
- 00 43 43 - Force Account Rates

In addition to the documents above, a copy of the emergency plan (including equipment on site, number of workers on site, hazardous materials on site (fuel), if applicable) will be provided to the client.

A-NMS004100++

District of Lakeland No. 521
Landfill Decommissioning
Project Specification

BID FORM

Section 00 41 00
Page 5 of 5
2026-09-10

This bid is executed under seal at _____ this _____ day of _____, 20__.

Name of firm

Address

For Individual or Partnership:

SIGNED, SEALED AND DELIVERED by:

Bidder (please print)

Signature

in the presence of:

Title

Name

Address

City/Province/PC

Seal

Occupation

For Individual or Partnership:

The Corporate Seal of:

Bidder (please print)

was hereunto affixed in the presence of:

Authorized Signing Office

Title

Seal

Authorized Signing Office

Title

END OF SECTION

Supplement to Bid Form

It is our intention that the following work will, subject to Engineer’s approval be subcontracted to the firms indicated below. All other work will be performed by our own forces, except as authorized in writing by Engineer.

Trade	Name and Address of Subcontractor

END OF SECTION

Supplement to Bid Forms
SCHEDULE OF FORCE ACCOUNT RATES

The following personnel and equipment rates will form the basis of payment for force account work carried out in accordance with the General Conditions. The rates shown are all inclusive. Contractor overhead and profit and, where applicable, subcontractor overhead and profit, are included in the rates. (Add additional pages, if necessary).

PERSONNEL

List by Occupation	Hourly Rate	Overtime Rate

EQUIPMENT
(Complete with Operator)

Description	Hourly Rate	Model and Size

END OF SECTION

Supplement to Bid Form

The following is a list of suppliers from whom we intend to purchase various items of material indicated, together with the product brand name or the name of the manufacturer of each. We will alter neither products nor suppliers from those listed below without the written authorization of the Engineer.

Item	Supplier

END OF SECTION

Supplement to Bid Form

We provide the following information relative to the Construction Schedule in order that Owner may assess our ability to plan the work and respond to critical deadlines.

Item	Schedule						

END OF SECTION

Supplement to Bid Form

We provide the following information in order that Owner may judge our ability to fulfill the Contract requirements.

1. The average number of persons we will employ and maintain on the project is _____.
2. The name of the superintendent we propose to place on the project and his previous experience on this type of construction is as follows:

Superintendent Name:			
Project Name and Value (\$)	Owner	Contact Name	Phone Number

3. The project, owner, and contact for similar work:

Project Name and Value (\$)	Owner	Contact Name	Phone Number

END OF SECTION

A-NMS006100++

District of Lakeland No. 521

BID BOND

Section 00 61 00

Landfill Decommissioning

Page 1 of 3

Project Specification

2026-09-10

Use CCDC standard form 220, an example of which follows.

No.....
\$.....

KNOW ALL MEN BY THESE PRESENTS THAT

.....
.....as Principal

hereinafter called the Principal, and
.....

a corporation created and existing under the laws of
.....

and duly authorized to transact the business of Suretyship in.....

as Surety, hereinafter called the Surety, are held and firmly bond unto.....

.....
.....as Obligee

hereinafter called the Obligee, in the amount of
.....

.....
.....Dollars (\$)

lawful money of Canada, for the payment of which sum, well and truly to be made, the Principal and the Surety bind themselves, their heirs, executors, administrators, successors and assigns, jointly and severally, firmly by these presents.

WHEREAS, the Principal has submitted a written tender to the Obligee, dated
the..... day of
.....,20..... for
.....
.....
.....
.....
.....
.....

NOW, THEREFORE, THE CONDITIONS OF THIS OBLIGATION is such that if the aforesaid Principal shall have the tender accepted within sixty (60) days from the closing date of tender and the said Principal will, within the time required, enter into a formal contract and give the specified security to secure the performance of the terms and conditions of the Contract, then this obligation shall be null and void. Otherwise the Principal and the Surety will pay unto the Obligee the difference in money between the amount of the bid of the said Principal and the amount for which the Obligee legally contracts with another party to perform the work if the latter amount be in excess of the former.

The Principal and the Surety shall not be liable for a greater sum than the specified penalty of this bond,
Any suit under this bond must be instituted before the expiration of six months from the date of this Bond.

IN WITNESS WHEREOF, the Principal and the Surety and Signed and Sealed this Bond this
..... day of
.....,
20.....

SIGNED AND SEALED

In the presence of

(
(
(
(.....)(Seal)
Principal

(
(
(
(.....)(Seal)
Surety

END OF SECTION

A-NMS00611316

District of Lakeland No. 521
Landfill Decommissioning
Project Specification

LABOUR AND MATERIAL
PAYMENT BOND

Section 00 61 13
Page 1 of 4
2026-09-10

Use CCDC standard form 222, an example of which follows.

No.....

\$.....

Note: This Bond is issued simultaneously with another Bond in favour of the Obligee conditioned for the full and faithful performance of the Contract.

KNOW ALL MEN BY THESE PRESENTS THAT

.....

.....as Principal

hereinafter called the Principal, and

.....

a corporation created and existing under the laws of

.....

and duly authorized to transact the business of Suretyship in.....

as Surety, hereinafter called the Surety, subject to the conditions hereinafter contained, held and firmly bound unto.....

.....as Trustee

hereinafter called the Obligee, for the use and benefit of the Claimants, their and each of their heirs, executors, administrators, successors and assigns in the amount

of.....

.....

.....Dollars (\$

)

lawful money of Canada, for the payment of which sum, well and truly to be made the Principal and the Surety bind themselves, their heirs, executors, administrators, successors and assigns, jointly and severally, firmly by these presents.

WHEREAS, the Principal has submitted a written tender to the Obligee, dated the..... day of

.....,20..... For

.....

.....

.....

.....

.....

.....

which Contract Documents are by reference made a part hereof, and are hereinafter referred to as the Contract.

NOW, THEREFORE, THE CONDITIONS OF THIS OBLIGATION is such that if the Principal shall make payments to all Claimants for all labour and material used or reasonably required for use in the performance of the Contract, then this obligation shall be null and void; otherwise it shall remain in full force and affect, subject however to the following conditions:

1. A Claimant for the purpose of this Bond is defined as one having a direct contract with the Principal for labour, material, or both, used or reasonable required for use in the performance of the Contract, labour and material being construed that part water, gas, power, light, heat, oil, gasoline, telephone service or rental equipment directly applicable to the Contract provided that a person firm or corporation who rents equipment to the Principal to be used in the performance of the Contract under a contract which provides that all or any part of the rent is to be applied towards the purchase price thereof, shall only be a Claimant to the extent of the prevailing industrial rental value of such equipment for the period during which the equipment was used in the performance of the Contract. The prevailing industrial rental value of equipment shall be determined, insofar as it is practical to do so, in accordance with and in the manner provided for in the latest revised edition of the publication of the Canadian Construction Associated titled "Rental Rates on Construction Equipment" published prior to the period during which the equipment was used in the performance of the Contract.
2. The Principal and the Surety hereby jointly and severally agree with the Oblige as Trustee that every Claimant who has not been paid as provided for under the terms of his contract with the Principal, before the expiration of a period of ninety (90) days after the date on which the last of such Claimant's work or labour was done or performed or materials were furnished by such Claimant, may as beneficiary of the trust herein provided for, sue on this Bond, prosecute to final judgment for such sum or sums as may be justly due to such claimant under the terms of a contract with the Principal and have execution thereon. Provided that the Oblige is not obliged to do or take any act, action or proceeding against the Surety on behalf of the Claimants, or any of them, to enforce the provisions of this Bond. If any act, action or proceeding is taken either in the name of the Oblige or by joining the Oblige as a party to such proceeding, then such act, action or proceeding shall be taken on the understanding and bases that the Claimants or any of them, who take such act, action or proceeding, shall indemnify and save harmless the Oblige against all costs, charges and expenses or liabilities incurred thereon and any loss or damage resulting to the Oblige by reason thereof. Provided still further that, subject to the foregoing terms and conditions, and Claimants, or any of them, may use the name of the Oblige to sue or enforce the provisions of this Bond.
3. No suit or action shall be commenced hereunder by any Claimant:
 - (a) unless such Claimant shall have given written notice within the time limits hereinafter set forth to each of the Principal, the Surety and the Oblige, stating with substantial accuracy the amount claimed. Such notice shall be served by mailing the same by registered mail to the Principal, the Surety and the Oblige, at any place where any office is regularly maintained for the transaction of business by such persons or served in any manner in which legal process may be served in the Province or other part of Canada in which the subject matter of the Contract is located. Such notice shall be given:
 - (1) in respect of any claim for the amount or any portion thereof, required to be held back from the Claimant by the Principal under either the terms of the Claimant's contract with the Principal, or under the Builders' (Mechanics') Liens Legislation applicable to the Claimant's contract with the Principal, whichever is the greater, within one hundred and twenty (120) days after such Claimant should have been paid in full under the Claimant's contract with the Principal;
 - (2) in respect of any claim other than the holdback, or portion thereof, referred to above, within one hundred and twenty (120) days after the date upon which such Claimant did, or performed, the last of the work or labour or furnished the last of the materials for which such claim is made under the Claimant's contract with the Principal;
 - (b) after the expiration of one (1) year following the date on which the Principal ceased work on the Contract, including work performed under the guarantees provided in the Contract;
 - (c) other than in a Court of competent jurisdiction in the Province or District of Canada in which the subject matter of the Contract, or any part thereof, is situated and not elsewhere, and the parties hereto agree to submit the jurisdiction of the Court.
4. The Surety agrees not to take advantage of Article 1959 of the Civil Code of the Province of Quebec in the event that, by an act or an omission of the Claimant, the Surety can no longer be subrogated in the rights, hypothecs and privileges of said Claimant.
5. Any material change in the contract between the Principal and Oblige shall not prejudice the rights or interest of any Claimant under this Bond, who is not instrumental in bringing about or has not caused such change.
6. The amount of this Bond shall be reduced by, and to the extent of any payment or payments made in good faith, and in accordance with the provisions hereof, inclusive of the payment by the Surety of Builders' (Mechanics') Liens

which may be filed of record against the subject matter of the Contract, whether or not claim for such lien be presented under and against this Bond.

7. The Surety shall not be liable for a greater sum than the specified penalty of this bond.

IN WITNESS WHEREOF, the Principal and the Surety have Signed and Sealed this Bond this
..... day of,
20.....

SIGNED and SEALED
in the presence of

(
(
(
(.....)(Seal)
Principal

(
(
(
(.....)(Seal)
Surety

END OF SECTION

A-NMS00611313

District of Lakeland No. 521
Landfill Decommissioning
Project Specification

PERFORMANCE BOND

Sect 00 61 13.13
Page 1 of 3
2026-09-10

Use CCDC standard form 221, an example of which follows.

No.....
\$.....

KNOW ALL MEN BY THESE PRESENTS THAT

.....
.....as Principal

hereinafter called the Principal, and
.....

a corporation created and existing under the laws of
.....

and duly authorized to transact the business of Suretyship in.....

as Surety, hereinafter called the Surety, are held and firmly bond unto.....

.....as Obligee

hereinafter called the Obligee, in the amount
of.....

.....Dollars (\$)

lawful money of Canada, for the payment of which sum, well and truly to be made, the Principal and the Surety bind themselves, their heirs, executors, administrators, successors and assigns, jointly and severally, firmly by these presents.

WHEREAS, the Principal has submitted a written tender to the Obligee, dated
the..... day of,
20..... for
.....
.....
.....
.....
.....
.....
.....

in accordance with the Contract Documents submitted therefore which are by reference made part hereof and are hereinafter referred to as the Contract.

NOW, THEREFORE, THE CONDITIONS OF THIS OBLIGATION is such that if the shall promptly and faithfully perform the Contract then this obligation shall be null and void; otherwise it shall remain in full force and affect.

Whenever the Principal shall be, and declared by the Obligee to be, in default under the Contract, the Obligee having performed the Obligee's obligations thereunder, the Surety shall promptly remedy the default or shall promptly:

- (1) complete the Contract in accordance with its terms and conditions, or
- (2) obtain a bid of bids for submission to Obligee for completing the Contract in accordance with its terms and conditions, and upon determination by the Obligee and the Surety of the lowest responsible bidder, arrange for a contract between such bidder and the Obligee and make available as work progresses (even though there should be a default, or a succession of defaults, under the contract or contracts of completion, arranged under this paragraph) sufficient funds to pay the cost of completion less the balance of the Contract price; but not

exceeding, including other costs and damages for which the Surety may be liable hereunder, the amount payable by the Obligee to the Principal under the Contract, less the amount properly paid by the Obligee to the Principal.

Any suit under this Bond must be instituted before the expiration of two (2) years from the date which the final payment under the Contract falls due.

The Surety shall not be liable for a greater sum than the specified penalty of the Bond.

No right of action shall accrue on this Bond, to or for the use of, any person or corporation other than the Obligee named herein, or the heirs, executors, administrators or successors of the Obligee.

IN WITNESS WHEREOF, the Principal and the Surety have Signed and Sealed this Bond this
..... day of, 20.....

SIGNED and SEALED
in the presence of

(
(
(
(.....)(Seal)
Principal

(
(
(
(.....)(Seal)
Surety

END OF SECTION

A-NMS006216++

District of Lakeland No. 521
Landfill Decommissioning
Project Specification

CERTIFICATE OF INSURANCE

Section 00 62 16
Page 1 of 3
2026-09-10

Use standard two-sided form, which follows.

Issued to:

Project: Description:

Location:

This is to certify that insurances as described herein, have been arranged through this office for the insured named below on whose behalf this Certificate is executed and we hereby certify that such insurances are in full force and effect as of this date, but only with respect to the type(s) of insurance for which a policy number, policy period, and limits of liability or amount is shown.

SCHEDULE OF INSURANCE			
TYPE OF INSURANCE	COMPANY AND POLICY NUMBER	EFFECTIVE & EXPIRY DATES OF POLICY	LIMIT OF LIABILITY/AMOUNT
COMPREHENSIVE GENERAL LIABILITY	_____	EFFECTIVE _____ EXPIRY _____	BODILY INJURY \$ _____ EACH PERSON \$ _____ EACH ACCIDENT \$ _____ AGGREGATE PRODUCTS
			PROPERTY DAMAGE \$ _____ EACH ACCIDENT \$ _____ AGGREGATE PRODUCTS
			BODILY INJURY & PROPERTY DAMAGE \$ _____ INCLUSIVE \$ _____ AGGREGATE PRODUCTS
		WRAP UP ☐	
EMPLOYERS LIABILITY	_____	EFFECTIVE _____ EXPIRY _____	\$ _____ EACH PERSON \$ _____ EACH ACCIDENT
AUTOMOBILE LIABILITY (OWNED/LEASED VEHICLES)	_____	EFFECTIVE _____ EXPIRY _____	BODILY INJURY \$ _____ EACH PERSON \$ _____ EACH ACCIDENT
			PROPERTY DAMAGE \$ _____ EACH ACCIDENT
			BODILY INJURY & PROPERTY DAMAGE \$ _____ INCLUSIVE
AUTOMOBILE LIABILITY NON- OWNED VEHICLES	_____	EFFECTIVE _____ EXPIRY _____ WRAP UP ☐	BODILY INJURY \$ _____ EACH PERSON \$ _____ EACH ACCIDENT
			PROPERTY DAMAGE \$ _____ EACH ACCIDENT
			BODILY INJURY & PROPERTY DAMAGE \$ _____ INCLUSIVE
UMBRELLA LIABILITY	_____	EFFECTIVE _____ EXPIRY _____	\$ _____ LIMITS EXCESS OF \$ _____
BUILDERS RISK/ INSTALLATION FLOATER	_____	EFFECTIVE _____ EXPIRY _____ WRAP UP ☐	\$ _____ SITE \$ _____ OTHER LOCATION \$ _____ TRANSIT
CONTRACTORS EQUIPMENT	_____	EFFECTIVE _____ EXPIRY _____	\$ _____
WORKER'S COMPENSATION	_____	EFFECTIVE _____ EXPIRY _____	AS REQUIRED BY THE ORDINANCE(S) OF THE
OTHER			

PARTICULARS OF INSURANCE	
GENERAL LIABILITY ☐ Premises Property and Operations ☐ Products and Completed Operations ☐ Blanket Contractual (all written agreements) ☐ Tenants Fire Legal Liability ☐ Owners and Contractors Protective ☐ Occurrence Bodily Injury and Property Damage ☐ Broad Form Property Damage ☐ Contingent Employers Liability ☐ Personal Injury ☐ Employees as Additional Insured ☐ Severability of Interest or Cross Liability ☐ Exclusions pertaining to Blasting, Collapse, Underpinning, deleted as follows: ☐ Owner as Additional Named Insured ☐ Provides Coverage for Claims arising from Use of Machinery and Equipment attached to licensed construction machinery on Project Site ☐ Waiver of Subrogation against Named Insured ☐ 30 Days Notice of Cancellation or Material Change ☐ ☐ ☐	BUILDERS RISK/INSTALLATION FLOATER ☐ All Risk Form ☐ Fire, Extended Coverages, Riot, Vandalism or Malicious Acts ☐ Difference in Conditions ☐ Flood Included ☐ Earthquake Included ☐ Excluded Faulty Workmanship, Faulty Construction or Faulty Design but not loss resulting therefrom ☐ Covers Transit by Land ☐ Covers Boiler Explosion during Installation, Temporary Operation and Testing ☐ Covers Owner as Additional Named Insured ☐ Grants Permission for Occupancy prior to completion ☐ Waiver of Subrogation Against Named Insureds ☐ 30 Days Notice of Cancellation or Material Change ☐ ☐ ☐ ☐
CONTINGENT EMPLOYERS LIABILITY ☐ 30 Days Notice of Cancellation or Material Change ☐	CONTRACTORS EQUIPMENT ☐ Subrogation Waived Against Owner ☐ Subrogation Waived Against Owner, Construction or Project Manager, Architects and Engineers ☐ 30 Days Notice of Cancellation or Material Change ☐ ☐
AUTOMOBILE ☐ 15 Days Notice of Cancellation or Material Change ☐	NON-OWNED AUTOMOBILE ☐ 15 Days Notice of Cancellation or Material Change ☐
MARINE/AIRCRAFT ☐ 30 Days Notice of Cancellation ☐	OTHERS ☐ ☐ ☐ ☐ ☐
MARINE/AIRCRAFT/CARGO ☐ 30 Days Notice of Cancellation or Material Change ☐	
☒ INDICATES THAT THE COVERAGE/ENDOREMENT INDICATED IS INCLUDED	
REMARKS (STATE DEDUCTIBLE IF ANY)	
TERMS AND CONDITIONS This Certificate is issued for convenience only. All of the terms and conditions of the Policies referred to are contained in the original document which are not modified or amended by this Certificate. In the event of cancellation or material change of the Policies referred to herein, the Insurer and/or the undersigned will provide written notice as indicated above.	

DATED _____

Authorized to sign on behalf of Insurers

END OF SECTION

PART 1 – GENERAL1.1 DEFINITIONS

.1

Not used.

1.2 LIMITATION OF
LIABILITY

.1

Without limiting any of Contractor's obligations or liabilities under the Contract Documents, Contractor shall, and shall cause its Subcontractors to, obtain and continuously carry, while Work is being performed and, unless otherwise specified in this Section, while any remedial or warranty work is being undertaken, at Contractor's own expense and cost, the following insurance coverage with minimum limits not less than those stated.

1.3 COMMERCIAL GENERAL
LIABILITY INSURANCE

.1

Commercial General Liability Insurance, in a form acceptable to Owner, with limits of not less than \$5,000,000.00 inclusive per occurrence for bodily injury, death and damage to property, including loss of use thereof

Commercial General Liability Policy shall include the following:

- .1 Additional Insured: Owner and Engineer are added as additional insured, but only with respect to liability arising out of the Contractor's performance of the Contract.
- .2 Bodily Injury and Property Damage to third parties arising out of the operations of the Contractor.
- .3 Products and Completed Operations: Coverage for bodily injury or property damage arising out of goods or products manufactured, sold, handled, or distributed by the Contractor and/or arising out of operations that have been completed by the Contractor.
- .4 Personal Injury: While not limited to, the coverage must include Violation of Privacy, Libel and Slander, False Arrest, Detention or Imprisonment and Defamation of Character.
- .5 Cross Liability/Separation of Insureds: Without increasing the limit of liability, the policy must protect all insured parties to the full extent of coverage provided. Further, the policy must apply to each Insured in the same manner and to the same extent as if a separate policy had been issued to each.
- .6 Blanket Contractual Liability: The policy must, on a blanket basis or by specific reference to the Contract, extend to assumed liabilities with respect to contractual provisions.
- .7 Employees must be included as Additional Insured.
- .8 Employers' Liability (or confirmation that all employees are covered by Worker's compensation (WSIB) or similar program)
- .9 Broad Form Property Damage including Completed Operations: Expands the Property Damage coverage to include certain losses that would otherwise be excluded by the standard care, custody or control exclusion found in a standard policy.
- .10 Notice of Cancellation: The Insurer will provide the Owner thirty (30) days written notice of policy cancellation.
- .11 Owners' or Contractors' Protective Liability: Covers the damages that the Contractor becomes legally obligated to pay arising out of the operations of a subcontractor.
- .12 Non-Owned Automobile Liability - Coverage for suits against the Contractor resulting from the use of hired or non-owned vehicles.

		.13	All Risks Tenants Legal Liability - to protect the Contractor for liabilities arising out of its occupancy of leased premises.
		.14	Sudden and Accidental Pollution Liability (minimum 120 hours): To protect the Contractor for liabilities arising from damages caused by accidental pollution incidents.
<u>1.4 AUTOMOBILE INSURANCE (OWNED AND NON-OWNED)</u>	.1		Automobile Liability Insurance in an amount usual for a contract of this nature, but for not less than \$2,000,000 per accident or occurrence., covering death and damage to property, effective for all licensed vehicles owned, leased, rented or used by Contractor. The policy shall include the following: .1 Third Party Liability - \$2,000,000 Minimum Limit per Accident or Occurrence .2 Accident Benefits - all jurisdictional statutes .3 Uninsured Motorist Protection .4 Notice of Cancellation: The Insurer will endeavour to provide the Contracting Authority thirty (30) days written notice of cancellation
<u>1.5 CONTRACTORS' EQUIPMENT INSURANCE</u>	.1		"All-Risk" Contractors' Equipment Insurance to the full insurable value of construction machinery and equipment used by Contractor in the performance of Work, including boiler insurance for temporary boilers and pressure vessels as applicable.
<u>1.6 BUILDERS' RISK INSURANCE</u>	.1		"All-Risks" Course of Construction Insurance in the joint names of Contractor, Owner, and Engineer, with the subcontractors as unnamed insureds, insuring not less than one hundred and ten percent (110%) of the sum of the amount of the Contract Price and the full value of materials provided by the Owner for incorporation into Work, with a deductible not exceeding \$5000.00. Such coverage to contain sublimits for materials in transit and materials stored at unnamed locations. Builders Risk Insurance shall be obtained and carried until Total Performance of the Work.
<u>1.7 UNMANNED AERIAL VEHICLE LIABILITY INSURANCE</u>	.1		Unmanned aerial vehicle liability insurance with respect to owned or non-owned aircraft (if used directly or indirectly in the performance of the Work), shall have limits of not less than \$5,000,000 per occurrence or accident for bodily injury, death and damage to property or such amounts as required by applicable laws or regulations.
	.2		All policies of insurance shall be in a form acceptable to Owner and shall not allow subrogation claims by the insurer against Owner or Engineer.
	.3		All policies of insurance that Contractor is required to obtain will be considered as primary insurances in relation to insurances held by Owner or Engineer without any right of contribution from any policies of insurance held by Owner or Engineer.

- .4 All policies of insurance shall provide that at least 30 days prior written notice be given to Owner in the event of cancellation or amendment restricting coverage.
- .5 Prior to commencing Work, Contractor shall provide Owner with Certificates of Insurance in a form acceptable to Owner, and with a letter from the insurer stating that the insurance provided complies with the requirements of the Contract.
- .6 Deductibles, if any, which are applicable to the insurance specified herein, shall be borne by Contractor.
- .7 The specified limits of insurance and coverages in no way define or limit the obligation of Contractor to indemnify Owner in the event of loss.
- .8 Owner makes no representation or warranty with respect to the extent or adequacy of the insurance protection afforded by the insurance policies that are specified in this section. Contractor shall be fully responsible to determine additional insurance coverages that may be necessary and advisable for protection of Contractor or to fulfil Contractor's obligations under this Contract

END OF SECTION

A-NMS009113++

District of Lakeland No. 521
Landfill Decommissioning
Project Specification

ADDENDA

Section 00 91 13
Page 1 of 1
2026-09-10

ADDENDUM NO.
to the
CONTRACT DOCUMENTS
for
DISTRICT OF LAKE LAND NO. 521
DISTRICT OF LAKE LAND NO. 521, SK LANDFILL DECOMMISSIONING

To All Bidders:

Any changes, additions and/or deletions made to the Contract Document for the District of Lakeland No. 521 Landfill Decommissioning Project will be placed in this section.

END OF SECTION

PART 1 – GENERAL1.1 SUMMARY OF WORK

.1

Requirements Included

- .1 Title and description of work: District of Lakeland No. 521 McPhee Lake Landfill Decommissioning.
- .2 Work included, but not limited to:
 - .a Hauling and installing clay liner, subsoil and topsoil as well as seeding the final cover for the landfill site in accordance with design specifications and regulatory requirements.
- .3 Contract method: Unit Price Contract

.2

Drawings and Specifications Furnished

- .1 Owner will provide electronic (PDF) copy plus 2 copies of 11 x 17 drawings and specifications to Contractor.
- .2 Additional copies of drawings and specifications are available upon request at an additional cost of \$300 per set.
- .3 Maintain at Site one complete set of drawings and specifications. Make available to Engineer at any time.

1.2 PROJECT COORDINATION

.1

Coordinate progress of the Work, progress schedules, submittals, use of site, temporary utilities, construction facilities and controls.

.2

Contractor to coordinate and pay for the relocation of utilities as required to complete the Work.

.3

Contractor to coordinate and pay for temporary utilities as required to complete the Work.

1.3 HOURS OF WORK

.1

Perform Work in conformity with all municipal bylaws with respect to noise control, hours of work, night work and holiday work.

.2

Obtain written permission of Engineer before undertaking holiday work or night work.

1.4 RELICS AND ANTIQUITIES

.1

Relics and antiquities and items of historical, cultural, or scientific interest such as cornerstones and contents, commemorative plaques, inscribed tablets, and similar objects found on site or in buildings to be demolished, remain property of Owner. Protect such articles and request directives from Engineer.

.2

Notify Engineer immediately if evidence of archaeological finds is encountered and await Engineer's written instructions before proceeding with work in area.

1.5 CUTTING AND PATCHING

.1

Approvals

- .1 Submit written request in advance of cutting or alteration which affects:
 - .a Structural integrity of any element of Project.

- .b Integrity of weather-exposed or moisture-resistant elements.
- .c Efficiency, maintenance, or safety of any operational element.
- .d Visual qualities of sight-exposed elements.
- .e Work of Owner or separate contractor.
- .2 Inspection
 - .a Inspect existing conditions, including elements subject to damage or movement during cutting and patching.
 - .b After uncovering, inspect conditions affecting performance of work.
 - .c Beginning of cutting or patching means acceptance of existing conditions.
- .3 Execution
 - .a Perform cutting, fitting, and patching including excavation and fill, to complete the Work.
 - .b Remove and replace defective and non-conforming work.
 - .c Perform Work to avoid damage to other work.
 - .d Prepare proper surfaces to receive patching and finishing.
 - .e Perform cutting and patching for weather-exposed and moisture-resistant elements and sight-exposed surfaces equivalent to original or better.
 - .f Cut rigid materials using power saw or core drill. Pneumatic or impact tools not allowed.
 - .g Restore work with new products in accordance with Contract Documents.
 - .h Fit work airtight to pipes, sleeves, ducts, conduit, and other penetrations through surfaces.
 - .i Refinish surfaces to match adjacent finishes; for continuous surfaces, refinish to nearest intersection; for an assembly, refinish entire unit.

1.6 FIELD ENGINEERING

- .1 Survey Requirements
 - .1 Contractor is responsible for completion of all construction layout survey, construction survey and protecting construction survey stakes.
 - .2 Contractor to confirm and protect control points prior to starting site work. Preserve permanent reference points during construction.
 - .3 Record locations, with horizontal and vertical data in Project Record Documents.
 - .4 Establish lines and levels, locate and lay out, by instrumentation.
 - .5 Contractor will complete periodic surveys at the site for the verification of quantities for payment.
- .2 Records
 - .1 Maintain a complete, accurate log of control and survey work as it progresses.
- .3 Subsurface Conditions:
 - .1 Promptly notify Engineer in writing if subsurface conditions at Place of the Work differ materially from those indicated in Contract

- Documents, or reasonable assumption of probable conditions based thereon.
- .2 After prompt investigation, should Engineer determine that conditions do differ materially, instructions will be issued for changes in the Work as provided in the contract procedures for Changes in the Work.

1.7 PROJECT MEETINGS

.1

Project progress will be called monthly throughout progress of work. The Contractor's Project Manager will administer.

1.8 SUBMITTALS

.1

Administrative

- .1 Submit to Engineer for review the submittals listed. Submit with reasonable promptness and in an orderly sequence so as to not cause delay in Work.
- .2 Work affected by submittal shall not proceed until review is complete.
- .3 Review submittals prior to submission to Engineer. This review represents that necessary requirements have been determined and verified, or will be, and that each submittal has been checked and coordinated with requirements of the Work and Contract Documents. Submittals not stamped, signed, dated and identified as to the specific project will be returned without being examined and will be considered rejected.
- .4 Verify that field measurements and affected adjacent Work are coordinated.
- .5 Adjustments made on submittals by Engineer are not intended to change the scope of work. If adjustments affect the value of Work, state such in writing to Engineer prior to proceeding with the work.

.2

Shop Drawings and Product Data

- .1 The term "Shop Drawings" means drawings, diagrams, illustrations, schedules, performance charts, brochures and other data which are to be provided by Contractor to illustrate details of a portion of Work.
- .2 Indicate materials, methods of construction and attachment or anchorage, erection diagrams, connection, explanatory notes and other information necessary for completion of Work.
- .3 Make changes in shop drawings as Engineer may require.
- .4 Contractor's responsibility for errors and omissions in submission is not relieved by Engineer's review of submittals.
- .5 Contractor's responsibility for deviations in submission from requirements of Contract Documents is not relieved by Engineer's review.
- .6 Keep one reviewed copy of each submission on Site.
- .7 Detail all shop drawings using the metric system. Prepare a drafting standard equivalent to that of Contract drawings.
- .8 Engineer will supply a Shop Drawing Review Stamp. Stamp all transparencies and copies of shop drawings submitted for review.

- .9 Fill in the following information on the Shop Drawing Review Stamp on each shop drawing prior to submitting the drawing to the Engineer:
 - .a PINTER & Associates Project. No. 2106
 - .b Drawing Number.
 - .c Date of submission.
- .10 Maintain a complete Shop Drawing Record showing the review status of all shop drawings on the work. Provide Engineer with a copy of this record on a monthly basis or as requested by Engineer.
- .11 Submit shop drawings to Engineer for review with a Transmittal Form as provided by Engineer or in a form acceptable to Engineer. Type or print the appropriate information on the form to fully describe the drawings being sent for review. Retain a photocopy of the form for filing and record purposes before drawings are sent to Engineer.
- .12 Transmittal form or shop drawing stamp to be signed by Contractor's authorized representative certifying approval of submission, verification of field measurements and compliance with Contract Documents
- .13 Submit electronic copies of product data sheets or brochures for requirements requested in specification Sections and as Engineer may reasonably request where shop drawings will not be prepared due to standardized manufacture of product.
- .14 Submit electronic files of shop drawings for each requirement requested in specification Sections and as Engineer may reasonably request.
- .15 During review, Engineer will mark drawings to indicate review status:
 - .a "REVIEWED" - Make and distribute additional copies as required for execution of the Work.
 - .b "REVISE & RESUBMIT" - Make the necessary revisions and resubmit revised drawings for review. Show the drawing number of the first such revised drawing and show the latest revision number applicable to the drawing by adding a suffix to the drawing number as - "REV. 1", "REV. 2", etc.
 - .c "NOT REVIEWED" - This notation indicates that Engineer has not reviewed the drawing. It may also be used in combination with the notation to revise and resubmit the drawing where Engineer lacks sufficient information to complete the review and requires resubmission of the drawing for review after revision.
 - .d Drawings will be marked "REVIEWED" together with the notation "REVISE & RESUBMIT" when Engineer requires resubmission of a revised drawing showing corrections made as a result of Engineer's notations on the shop drawings. This procedure will not relieve Contractor of responsibility for errors or omissions in the shop drawings or of responsibility for meeting all requirements of Contract.
- .16 Use only those shop drawings on the work that bear the "REVIEWED" notation.

- .17 Do not revise shop drawings marked "REVIEWED" unless resubmitted to Engineer for further review.
- .18 Determine which shop drawings have, in addition to those drawings specifically mentioned in Contract, design elements requiring the seal of a Professional Engineer registered in the Province or Territory where Work is located, in accordance with the applicable provincial or federal engineering acts or other governing legislation. Seal such drawings before submitting them for review. Submit for review engineering calculations signed by the registered Professional Engineer responsible for the shop drawing design elements.
- .19 Review by Engineer is for the sole purpose of ascertaining conformance with the general design concept. This review does not mean that Engineer approves the detail design inherent in the shop drawings, responsibility for which remains with Contractor, and such review does not relieve Contractor of responsibility for errors or omissions in the shop drawings or of responsibility for meeting all requirements of Contract Documents. Contractor is responsible for dimensions to be confirmed and correlated at the job-site, for information that pertains solely to fabrication processes or to techniques of construction and installation and for coordination of the work of all sub-trades.
- .3 Samples
 - .1 Submit for review, samples in duplicate as requested in respective specification Sections.
 - .2 Deliver samples prepaid to Engineer's business address.
- .4 Record Drawings
 - .1 After award of Contract, Engineer will provide a set of drawings for purpose of maintaining record drawings. During progress of the work, accurately and neatly record deviations from Contract Documents caused by site conditions and changes ordered by Engineer.
 - .2 Record locations of concealed components of mechanical and electrical services.
 - .3 Identify drawings as "Project Record Copy". Maintain in good condition, keep continuously updated and make available for inspection on site by Engineer.
 - .4 On completion of Work and prior to final inspection, submit record documents to Engineer.

1.9 SCHEDULE

- .1 Schedules Required
 - .1 Construction Progress Schedule.
 - .2 Submittal Schedule for Shop Drawings, Product Data and Samples.
 - .3 Cash Allowance Schedule for purchasing products.
- .2 Format
 - .1 Prepare schedule in form of horizontal bar chart.
 - .2 Provide separate bar for each trade or operation.

- .3 Provide horizontal time scale identifying first work day of each week.
- .4 Format for listings: Chronological order of start of each item of work.
- .3 Submission
 - .1 Submit initial schedules within 10 days after award of Contract.
 - .2 Engineer will review schedule and return reviewed copy within 10 days after receipt.
 - .3 Resubmit finalized schedule within 7 days after return of reviewed copy.

1.10 QUALITY CONTROL

- .1 Inspection
 - .1 Owner and Engineer shall have access to Work.
 - .2 Give timely notice requesting inspection if Work is designated for special tests, inspections or approvals by Engineer instructions, or law of Place of Work.
 - .3 If Contractor covers or permits to be covered Work that has been designated for special tests, inspections, or approvals before such is made, uncover such Work, have inspections or tests satisfactorily completed and make good such Work.
- .2 Independent Inspection Agencies
 - .1 Independent Inspection/Testing Agencies will be engaged by Engineer for purpose of inspecting and/or testing portions of Work. Cost of such services will be borne by Owner.
 - .2 Provide equipment required for executing inspection and testing by appointed agencies.
- .3 Reports
 - .1 Provide copies to Subcontractor of work being inspected/tested.

1.11 CONSTRUCTION FACILITIES AND TEMPORARY CONTROLS

- .1 Installation/Removal
 - .1 May provide construction facilities and temporary controls in order to execute Work expeditiously.
 - .2 Remove from site all such work after use.
- .2 Weather Enclosures
 - .1 Provide weathertight closures to unfinished door and window openings, tops of shafts, and other openings in floors and roofs.
 - .2 Close off floor areas where walls are not finished; seal off other openings; enclose building interior work area for temporary heat.
- .3 Dust Tight Screens
 - .1 Provide dust tight screens or partitions to localize dust generating activities, and for protection of workers, finished areas of Work and public.
 - .2 Maintain and relocate protection until such Work is complete.

- .4 Dewatering
 - .1 Provide temporary drainage and pumping facilities to keep excavations and site free from standing water/contributed from all sources including, but not limited to groundwater, precipitation, and seepage losses from adjacent lagoon cells. Dewater the site as required to allow for construction.
- .5 Site Storage/Loading
 - .1 Confine the Work and operations of employees to limits indicated by Contract Documents. Do not unreasonably encumber premises with Products.
 - .2 Do not load or permit to be loaded any part of the Work with a weight or force that will endanger the Work.
- .6 Sanitary Facilities
 - .1 Provide sufficient sanitary facilities for workers in accordance with local health authorities.
 - .2 Maintain in clean condition.
 - .3 Existing facilities as designated may be used during construction period.
- .7 Temporary Heating
 - .1 Provide temporary heating required during construction period, including attendance, maintenance and fuel.
 - .2 Construction heaters used inside building must be vented to outside or be non-flameless type. Solid fuel salamanders not permitted.
 - .3 Maintain temperatures of minimum 10°C in areas where construction is in progress, unless indicated otherwise in specifications.
 - .4 Ventilate heated areas and keep building free of exhaust or combustion gases.
 - .5 Permanent heating system of building, or portions thereof, may be used when available. Be responsible for damage thereto.
- .8 Temporary Power
 - .1 Provide and pay for temporary power required during construction for temporary lighting and operating of power tools, to maximum supply of 230 volts 30 amps.
 - .2 Arrange for connection with appropriate utility company. Pay costs for installation, maintenance, and removal.
- .9 Equipment/Tool/Materials Storage
 - .1 Provide and maintain, in clean and orderly condition, lockable weatherproof sheds for storage of tools, equipment and materials.
 - .2 Locate materials not required to be stored in weatherproof sheds on site in manner to cause least interference with work activities.
- .10 Project Cleanliness
 - .1 Maintain the Work in tidy condition, free from accumulation of waste products and debris.

1.12 BASIC PRODUCT
REQUIREMENTS

- .2 Remove waste material and debris from site and deposit in waste container at end of each working day.
- .3 Clean interior areas prior to start of finish work, maintain areas free of dust and other contaminants during finishing operations.
- .1 Product and Material Quality
 - .1 Products, materials, equipment, and articles (referred to as Products throughout specifications) incorporated in Work shall be new, not damaged or defective, and conforming with specifications for purpose intended. If requested, furnish evidence as to type, source and quality of Products provided.
 - .2 Defective Products will be rejected, regardless of previous inspections. Inspection does not relieve responsibility but is precaution against oversight or error. Remove and replace defective Products at own expense and be responsible for delays and expenses caused by rejection.
- .2 Manufacturer's Instructions
 - .1 Unless otherwise indicated in specifications, install or erect Products in accordance with manufacturer's instructions. Do not rely on labels or enclosures provided with Products. Obtain written instructions directly from manufacturers.
 - .2 Notify Engineer in writing, of conflicts between specifications and manufacturer's instructions, so that Engineer may establish course of action.
 - .3 Improper installation or erection of Products, due to failure in complying with these requirements, authorizes Engineer to require removal and reinstallation at no increase in Contract Amount.
- .3 Workmanship
 - .1 Execute Work by workers experienced and skilled in respective duties for which they are employed. Immediately notify Engineer if required Work is such as to make it impractical to produce required results.
 - .2 Do not employ any unfit person or anyone unskilled in their required duties. Engineer reserves the right to require the dismissal from site of workers deemed incompetent, careless, insubordinate, or otherwise objectionable.
- .4 Concealment
 - .1 In finished areas, conceal pipes, ducts, and wiring in floors, walls, and ceilings, except where indicated otherwise.
 - .2 Before installation, inform Engineer if there is a contradictory situation. Install as directed by Engineer.
- .1 Final Cleaning
 - .1 When the Work is Substantially Performed, remove surplus products, tools, construction machinery, and equipment not required for performance of remaining Work.

1.12 PROJECT CLOSEOUT

- .2 Remove waste materials and debris from site at regularly scheduled times or dispose of as directed by Engineer. Do not burn waste materials on site, unless approved by Engineer.
- .3 Leave work broom clean before inspection process commences.
- .4 Clean and polish glass, mirrors, hardware, wall tile, stainless steel, chrome, porcelain enamel, baked enamel, plastic laminate, mechanical and electrical fixtures. Replace broken, scratched or disfigured glass.
- .5 Remove stains, spots, marks and dirt from decorative work, electrical and mechanical fixtures, furniture fitments and walls.
- .6 Vacuum clean and dust building interiors, behind grilles, louvres and screens.
- .7 Wax, seal, shampoo or prepare floor finishes, as recommended by manufacturer.
- .8 Broom clean and wash exterior walks, steps, and surfaces.
- .9 Remove dirt and other disfigurements from exterior surfaces.
- .2 Systems Demonstration
 - .1 Prior to final inspection, demonstrate operation of each system to Engineer.
 - .2 Instruct personnel in operation, adjustment, and maintenance of equipment and systems, using provided operation and maintenance data as basis for instruction.
- .3 Documents
 - .1 Collect reviewed submittals and assemble documents executed by Subcontractors, suppliers, and manufacturers.
 - .2 Submit material prior to final Application for Payment.
 - .3 Submit operation and maintenance data, record drawings.
 - .4 Provide warranties and bonds fully executed and notarized.
 - .5 Execute transition of Performance and Labour and Materials Payment Bond(s) to warranty period requirements.
 - .6 Submit a final statement of accounting giving total adjusted Contract Amount, previous payments, and monies remaining due.
 - .7 Engineer will issue a final change order reflecting approved adjustments to Contract Amount not previously made.
- .4 Inspection/Takeover Procedures
 - .1 Prior to application for Certificate of Total Performance, carefully inspect the Work and ensure it is complete, that all construction deficiencies are complete, defects are corrected, and building is clean and in condition for occupancy. Notify Engineer, in writing, of completion of the Work and request an inspection.
 - .2 During Engineer inspection, a list of deficiencies and defects will be tabulated. Correct same.
 - .3 Make application for Certificate of Total Performance. Refer to CCDC 4 for specifics of application.

PART 2 – PRODUCTS

2.1 NOT USED

- .1 Not used.

A-NMS010000++		
District of Lakeland No. 521	GENERAL REQUIREMENTS	Section 01 00 00
Landfill Decommissioning		Page 10 of 10
Project Specification		2026-09-10

PART 3 – EXECUTION

3.1 NOT USED.1 Not used.

END OF SECTION

PART 1 – GENERAL1.1 RELATED
REQUIREMENTS

- .1 CCDC 4 Unit Price Contract.
- .2 Technical Drawings (Refer to Section 00 01 15 for list).

1.2 WORK COVERED BY
CONTRACT DOCUMENTS

- .1 Work of this Contract comprises general closure of a landfill site, located at SW-26-56-27-W2M, SK, and further identified as the Project location.

1.3 CONTRACT METHOD

- .1 Construct Work under unit price contract.
- .2 Submit Contract Bid on CCDC4-2011 Forms.
- .3 CCDC Authenticity Seals will be affixed to final contracts in advance of execution; these will be provided by the Engineer during document execution.
- .4 Contract with Owner will be signed and sealed in duplicate by Contractor and submitted to the District of Lakeland No. 521 for endorsement. One fully executed copy returned to Contractor.

1.4 WORK BY OTHERS

- .1 The existing transfer station located on the adjacent property will remain in operation throughout the construction process. Coordination with Operators and Users at the tie-in locations may be required.
- .2 Cooperate and coordinate with all Operators and Users to complete the Work of this Contract in a timely and efficient manner. The Contractor must schedule, and sequence all work to accommodate the work and schedule by other Contractors. No additional payment will be made for cooperating and coordinating with other Contractors as it is considered incidental to the Contract.

1.5 FUNDING PROGRAM
REQUIREMENTS

- .1 **THIS PROJECT IS PARTIALLY FUNDED BY THE GOVERNMENTS OF CANADA AND SASKATCHEWAN THROUGH THE CANADA-SASKATCHEWAN INVESTING IN CANADA INFRASTRUCTURE PROGRAM (ICIP).**
- .2 Funding program conditions of Participation:
 - .1 By participating in this contract, the Contractor hereby agrees that:
 - .a “The Third Party agrees to indemnify and save harmless Canada, Saskatchewan, the Recipient, their officers, servants, employees or agents from and against all claims, demands, loss, expenditures, damages, actions, suits, or other proceedings by

whomsoever brought or prosecuted in any manner based upon, or occasioned by any injury to persons, damage to or loss or destruction of property, economic loss or infringement of rights caused by or arising directly or indirectly from:

- .1 this Contract;
 - .2 the performance of a Contract or the breach of any term or condition of it by the Third Party, its officers, servants, employees or agents; or
 - .3 any omission or other willful or negligent act of the Third Party, their respective officers, servants, employees, or agents.”
- .b “The Third Party agrees that nothing in this Contract is to be construed as authorizing the Third Party to contract for or to incur any obligation on behalf of Canada, Saskatchewan or the Recipient or to act as agent for them.”

1.6 SURVEY RESPONSIBILITY

- .1 Contractor shall provide all required survey and layout services necessary to complete work, at no additional cost. Engineer will not be providing survey or layout services.
- .2 Complete a detailed topographic survey of the undisturbed site a minimum of 7 days prior to commencing work and submit results to Engineer electronically for review and comparison with design baseline.
- .3 Include detailed survey notes to substantiate all contract progress payment requests.
- .4 In the occurrence of any mathematical or spatial discrepancies or anomalies, work cooperatively and constructively with the Engineer to resolve in a positive and proactive manner.
- .5 Contractor shall use machinery with GPS grade-control systems to ensure efficiency and precision during the project.

1.7 WORK INCLUDED WITHIN THIS CONTRACT

This Contract Includes the following tasks:

- .1 The closure of existing landfill cell.
 - .1 Contour, prep surface, haul materials, and install cover material on site over existing cell as shown in design drawings.
 - .2 Proper clean-up of Site following construction.

1.8 QUALITY CONTROL RESPONSIBILITY

- .1 The Consultant is responsible for all quality control testing and measures necessary to ensure the work meets technical requirements and specifications.

- .2 Quality Control and Testing Services are to be provided at no additional cost.
- .3 Contractor is responsible for ensuring work is completed in a competent manner and is a finished kind that is fit for purpose.
- .4 Owner will conduct Quality Assurance as deemed necessary by the Engineer.
- .5 Submit prior to commencement of work Contractor's Quality Control Plan, outlining the proposed number and type of Quality Control Tests, for review and approval by Engineer.

1.9 PROJECT MEETINGS AND COMMUNICATION

- .1 Host Preconstruction Meeting following an award of project and prior to the commencement of work, at no additional cost.
- .2 Host bi-monthly (twice a month) Progress Meetings with Engineer and Owner at no additional cost.
- .3 Host Emergency or Topic Specific Meetings with the Engineer and Owner as deemed necessary by Engineer. Promptly notify Engineer if Contractor desires such meeting.
- .4 Engineer to prepare and provide meeting records.
- .5 Established lines of communication for this project are between Contractor and Engineer, and Owner and Engineer. Contractor is not to engage Owner directly, and/or without Engineer's knowledge. Tripartite communications will be facilitated whenever desired; the aim of this section is not to prevent communication between Contractor and Owner.
- .6 Advise Engineer promptly if Contractor feels that any direction or instruction is contrary to the specifications, drawings, or intent of the project agreement, for further study and direction.
- .7 Submit written Monthly Progress Reports to the Engineer and Owner describing incremental and cumulative expenditures on the project, schedule status, milestones reached, tasks completed, new issues encountered, and old business status update.

1.10 CHANGE ORDERS

- .1 Change Orders will occur as defined in CCDC 4.

1.11 OPTIONS AND SUBSTITUTIONS

- .1 The Engineer will consider requests for substitution from the contractor provided that the requests are submitted in time for review and are complete with full details of the type of materials and equipment to be substituted, and the reason for the request.

- .2 Contractor may not proceed with any substitution or option until authorized in writing by the Engineer.
- .3 Any substitution presented must provide tangible net value to the Owner, and may not add additional cost to the project, or contradict any specification or project requirement, unless authorized in advance by the Engineer.

1.12 DRAWING STATUS

- .1 The Issued-for-Construction version of the drawings will be stamped by the Engineer.
- .2 The Issued-for-Bid version of drawings included in this package will be discussed with the Contractor before final Issued-for-Construction drawings will be submitted.

1.13 SITE
SUPERINTENDENT

- .1 Maintain on the project at all times a competent superintendent to oversee all work and act as the Contractor's representative on site.
- .2 The superintendent shall not be changed by the Contractor except for good and sufficient reason and only then after consultation with the Engineer.
- .3 The Engineer or Owner may request a change in Site Superintendent at any time, and for any reason, at no additional cost to the work.

1.14 EXISTING SERVICES

- .1 Notify Engineer and utility companies of intended interruption of services and obtain required permits.
- .2 Where Work involves breaking into or connecting to existing services, give Engineer 48 hours notice for necessary interruption of mechanical or electrical service throughout course of work. Minimize duration of interruptions. Carry out work at times as directed by governing authorities with minimum disturbance to pedestrian, vehicular traffic and tenant operations.
- .3 Provide alternative routes for personnel, pedestrian, and vehicular traffic.
- .4 Establish location and extent of service lines in area of work before starting Work. Notify Engineer of findings.
- .5 Submit schedule to and obtain approval from Engineer for any shut-down or closure of active service or facility including power and communications services. Adhere to approved schedule and provide notice to affected parties.
- .6 Provide temporary services when directed by Engineer to maintain critical building and tenant systems.
- .7 Provide adequate bridging over trenches which cross sidewalks or roads to permit normal traffic.

- .8 Where unknown services are encountered, immediately advise Engineer, and confirm findings in writing.
- .9 Protect, relocate, or maintain existing active services. When inactive services are encountered, cap off in manner approved by authorities having jurisdiction.
- .10 Record locations of maintained, re-routed, and abandoned service lines.

**1.15 DOCUMENTS
REQUIRED**

- .1 Maintain at job site, one copy of each document as follows:
 - .1 Contract Drawings.
 - .2 Specifications.
 - .3 Addenda.
 - .4 Reviewed Shop Drawings.
 - .5 List of Outstanding Shop Drawings.
 - .6 Change Orders.
 - .7 Other Modifications to Contract.
 - .8 Field Test Reports.
 - .9 Copy of Approved Work Schedule.
 - .10 Health and Safety Plan and Other Safety Related Documents.
 - .11 Other documents as specified.

PART 2 – PRODUCTS**2.1 NOT USED**

- .1 Not used.

PART 3 – EXECUTION**3.1 NOT USED**

- .1 Not used.

END OF SECTION

PART 1 – GENERAL1.1 MEASUREMENT FOR
PAYMENT

- .1 For each unit price item, Engineer will calculate payment based on tendered unit price and Engineer's determination of units of work item completed.
- .2 For lump sum price item, Engineer will calculate payment based on tendered price and Engineer's estimate of percentage of work item completed.
- .3 Method of measurement to be used is detailed in the section of the specification covering each work item.
- .4 Where a method of measurement for payment for a work item is not specified, payment for that item will be deemed to be included in another pay item or other pay items.

1.2 PROGRESS CLAIMS

- .1 Contractor's Responsibilities:
 - .1 Submit progress claim to Engineer within 5 working days after each month end. Claim to cover preceding month.
 - .2 Progress claim to show estimate of percentage of work completed.
 - .3 Progress claim to include all labour and materials incorporated in Work and all materials stored at Site.
 - .4 Progress claim to include all agreed extras and deductions.
 - .5 Supply documentation to support claim for materials on site in the form of itemized lists or unpriced purchase orders showing quantities.
 - .6 Supply other evidence required by Engineer in support of progress claim.
- .2 Engineer's Responsibilities:
 - .1 Review Contractor's claim, prepare Progress Payment Certificate and issue to Owner within 10 working days following receipt of Contractor's claim.
 - .2 Engineer's estimate of percentage of work completed will govern calculation of payment on all Progress Payment Certificates.
 - .3 Inform Contractor of amendments to claim by copy of Progress Payment Certificate.

1.3 CHANGE ORDERS

- .1 Complete and promptly return all change price requests issued by Engineer, quoting unit and/or lump sum prices as requested. Include appropriate supporting documentation to verify prices.
- .2 Do not proceed with work affected by price request until authorized to do so by Change Order.
- .3 Make no change in Work unless Change Order issued. Change Order is only valid when signed by Engineer, Owner, and Contractor.

1.4 MEASUREMENT AND
PAYMENT ITEMS

- .1 Miscellaneous Items
 - .1 Mobilization:

- .1 Scope: Includes mobilization and all related work for all aspects of the Contract; and all requirements stipulated in Divisions 0/1. Mobilization consists of supplying, transporting to the site, assembling, erecting, and preparing such construction equipment, temporary work, and labour necessary to start the work.
- .2 Measurement: Shall not be measured for payment.
- .3 Payment: Lump sum payment as follows:
 - .1 When 5% of original contract amount is earned, 25% of lump sum bid for Mobilization and Demobilization will be paid.
 - .2 When 10% of original contract amount is earned, 25% of lump sum bid for Mobilization and Demobilization will be paid.
 - .3 When 25% of original contract amount is earned, 10% of lump sum bid for Mobilization and Demobilization will be paid.
 - .4 When 50% of original contract amount is earned, 10% of lump sum bid for Mobilization and Demobilization will be paid.
 - .5 Upon Substantial Performance the unpaid balance of the lump sum bid in the Schedule of Prices for Mobilization and Demobilization will be paid.
- .2 Bond and Insurance
 - .1 Scope: The lump sum bid for this item shall include all costs associated with insurance and bonding for this contract as described in the Instructions to Bidders of this document. The Contractor shall provide a Performance bond of 50% of the Total Bid Price and a Labour and Material Payment Bond of 50% of the Total Bid Price. Recommendation for payment will be made after satisfactory proof that the bonding and insurance is in place. Bonding and insurance shall remain in place until the expiration of the Warranty Period.
 - .2 Measurement: Shall not be measured for payment.
 - .3 Payment: Recommendation for payment will be made after satisfactory proof that the bonding and insurance is in place.
- .3 Supervision
 - .1 Scope: Provide the necessary supervision and qualified tradesmen to ensure the flow of materials and on-site construction compatible with the overall project schedule and progress.
 - .2 Measurement: Shall not be measured for payment.
 - .3 Payment: Recommendation for payment will be made after satisfactory proof of proper project supervision.
- .4 Live Out Allowance
 - .1 Scope: This cash allowance is intended to cover all live out expenses by the contractor.
 - .2 Measurement: Shall not be measured for payment.
 - .3 Payment: Recommendation for payment will be made after satisfactory proof of the contractor living outside their home base.

- .2 Site Work
 - .1 Site Grading
 - .1 Scope: Provision of all equipment, material, and labour required for leveling up the slope as needed and stripping material if needed. Refer to Section 31 14 13 – Soil Stripping and Stockpiling and as shown on the drawings.
 - .1 Rough grade to levels, profiles, and contours allowing for surface treatment as indicated.
 - .2 Moisture content of fill and existing surface to be approximately the same to facilitate bonding.
 - .3 Compact fill material and disturbed areas to acceptable levels as indicated by the Engineer.
 - .4 Compact all other areas disturbed by construction activities to acceptable levels as indicated by the Engineer.
 - .5 The Contractor shall be required to trim or build slopes at site boundaries to a grade not steeper than 3H:1V.
 - .2 Measurement: Shall not be measured but inspected for payment.
 - .3 Payment: Payment for meeting the requirements of this Section shall be on a lump sum basis for Site Grading as identified in the Schedule of Quantities and Prices. No separate payment will be made for unnecessary grading or work performed beyond established lines or grades unless otherwise authorized by the Owner's representative.
 - .2 Loading, Hauling and Installing Clay for Clay Liner in 150 mm Lifts:
 - .1 Scope: Provision of all equipment, material, and labour required to excavate and haul (within 100m) on site, as well as to place and compact the material. The volume provided represents the compacted volume, not the volume of loose material.
Compaction will be done in lifts of a maximum of 150 mm loose material using mechanical compaction equipment/device to a minimum of 98% of the standard Proctor density at optimum moisture content.
 - .2 Measurement: Shall be on a per cubic meter basis. Measurement is taken in the final position.
 - .3 Payment: Unit Price per cubic metre basis. No separate payment will be made for extra material beyond those established by the Engineer.
 - .3 Loading, Hauling and Installing Subsoil.
 - .1 Scope: Provision of all equipment, material, and labour required to excavate, haul, and transport to site, as well as to place the material.
 - .2 Measurement: Shall be on a per cubic meter basis. Measurement is taken in the final position.

- Payment: Unit Price per cubic metre basis. No separate payment will be made for extra material beyond those established by the Engineer.
- .4 Installing Topsoil
- .1 Scope: Provision of all equipment, material, and labour required to place the stockpiled material.
- .2 Measurement: Shall be on a per cubic meter basis. Measurement is taken in the final position.
Payment: Unit Price per cubic metre basis. No separate payment will be made for extra material beyond those established by the Engineer.
- .5 Seeding and Fertilizing
- .1 Scope: Provision of all equipment, material, and labour required for placement of grass seed and fertilizer in accordance with Section 312900 Grass Seeding. The work includes supply and placement of fertilizer, placement of grass seed (to be supplied by contractor), re-seeding as necessary until an adequate catch is achieved (as determined by the Owner), and all related work for which payment is not included elsewhere.
- .2 Measurement: Shall be on a per square metre basis, determined by survey.
- .3 Payment: Unit Price per square metre basis, as specified on the Bid Form.

PART 2 – PRODUCTS2.1 NOT USED

.1

Not Used.

A-NMS012200++

District of Lakeland No. 521
Landfill Decommissioning
Project Specification

MEASUREMENT AND PAYMENT

Section 01 22 00
Page 5 of 5
2026-09-10

PART 3 – EXECUTION

3.1 NOT USED

.1

Not Used.

END OF SECTION

PART 1 – GENERAL1.1 CO-ORDINATION

- .1 Co-ordinate all construction activities to provide efficient and orderly construction of each and every part of the Work.
- .2 Where construction of one part of the Work is dependent on construction of other parts, schedule and co-ordinate construction activities in the sequence needed to obtain the best results.
- .3 Where availability of space is limited, co-ordinate construction of different parts of the Work to provide maximum accessibility for maintenance, service, and repair.
- .4 Make adequate provisions to accommodate Work scheduled for later construction by Other Contractors or by the Owner's own forces.

1.2 COMMUNICATION
EQUIPMENT

- .1 Provide suitable computer equipment and software at the Contractor's office specified in this section for exchange of electronic data by e-mail of the following types of documents:
- | | | |
|----|-------------------|----------------------|
| .1 | Letters and Memos | Microsoft Word |
| .2 | Document Readers | Adobe Acrobat Reader |
| .3 | Schedules | Microsoft Project |
| .4 | Drawings | AutoCAD |
| .5 | Communication | Microsoft Outlook |

1.3 COMMUNICATION
METHODS

- .1 Communications will be sufficiently given by any one of the following methods:
- .1 Delivered personally to the Contractor, the Contractor's representative, or left at the Contractor's address as specified in this section.
- .2 Mailed at any post office to the Contractor's address as specified in this section.
- .3 Couriers to the Contractor's address as specified in this section.
- .4 Transmitted by Internet to the Contractor's e-mail address as specified in this Section.

1.4 CONTRACT
ADMINISTRATION

- .1 Co-ordinate scheduling and timing of administrative procedures with other construction activities to avoid delays and provide orderly progress of the Work. Administrative procedures include the following:
- .1 Preparation and monitoring of schedules.
- .2 Co-ordination of construction and removal of temporary facilities.
- .3 Co-ordination, review, and processing of submittals.
- .4 Participation in project meetings.
- .5 Following Contract acceptance procedures.
- .6 Preparation of change order proposals.

1.5 CONTRACTOR'S
ADDRESS FOR

- .1 Submit the name, address, telephone number, facsimile number, and e-mail address to be used for correspondence with the Contractor within 10 days of

CORRESPONDENCE

the date of commencement of the Contract. Update whenever information changes during the Contract.

1.6 OWNER'S ADDRESS FOR
CORRESPONDENCE .1

The Owner will provide to the Contractor the name, address, telephone number, facsimile number, and e-mail address to be used for correspondence with the Owner within 10 days of the date of commencement of the Contract. This information will be updated as required during the Contract.

1.7 CONTRACTOR'S
REPRESENTATIVES AND
SITE MANAGEMENT .1

Submit an organization chart showing the names, positions, telephone numbers, and responsibilities and levels of authority for the Contractor's representatives and site management organization, within 10 days of the date of commencement of the Contract, and update whenever information changes during the Contract.

1.8 OWNER'S
REPRESENTATIVES AND
ASSISTANTS .1

The Owner will provide to the Contractor an organization chart showing the names, positions, telephone numbers, and responsibilities and levels of authority for the Owner's Representative and assistants, within 10 days of the date of commencement of the Contract and will update whenever information changes during the Contract.

PART 2 – PRODUCTS2.1 NOT USED .1

Not Used.

PART 3 – EXECUTION3.1 NOT USED .1

Not Used.

END OF SECTION

PART 1 – GENERAL1.1 REFERENCES

- .1 Canadian Construction Documents Committee (CCDC)
- .1 CCDC 4-2011, Unit Price Contract.

1.2 APPLICATIONS
FOR PROGRESS

- .1 Refer to CCDC 4.

PAYMENT

- .2 Make applications for payment on account provided in Agreement monthly as Work progresses.
- .3 Date applications for payment on last day of agreed monthly payment period and ensure amount claimed is of value proportionate to amount of Contract, of Work performed, and Products delivered to Place of Work at that date.
- .4 Submit to Engineer, at least 14 days before first application for payment, Schedule of values for parts of Work, aggregating total amount of Contract Price, to facilitate evaluation of applications for payment.

1.3 SCHEDULE OF VALUES

- .1 Refer to CCDC 4.
- .2 Provide schedule of values supported by evidence as Engineer may reasonably direct and, when accepted by Engineer, be used as basis for applications for payment.
- .3 Include statement based on schedule of values with each application for payment.
- .4 Support claims for products delivered to Place of Work but not yet incorporated into Work by such evidence as Engineer may reasonably require to establish value and delivery of products.

1.4 PROGRESS
PAYMENT

- .1 Refer to CCDC 4.
- .2 Engineer will issue to Owner, no later than 10 days after receipt of an application for payment, certificate for payment in amount applied for or in such other amount as Engineer determines to be due. If Engineer amends application, Engineer will give notification in writing giving reasons for amendment.

1.5 SUBSTANTIAL
PERFORMANCE OF WORK

- .1 Refer to CCDC 4.
- .2 Prepare and submit to Engineer comprehensive list of items to be completed or corrected and apply for a review by Engineer to establish Substantial Performance of Work. Failure to include items on list does not alter responsibility to complete Contract.

- .3 No later than 10 days after receipt of list and application, Engineer will review Work to verify validity of application and, no later than 7 days after completing review, will notify Contractor if Work or designated portion of Work is substantially performed.
- .4 Engineer will state date of Substantial Performance of Work or designated portion of Work in certificate.
- .5 Immediately following issuance of certificate of Substantial Performance of Work, establish reasonable date for finishing Work in consultation with Engineer.

1.6 PAYMENT OF HOLDBACK UPON SUBSTANTIAL PERFORMANCE OF WORK

- .1 Refer to CCDC 4.
- .2 After issuance of certificate of Substantial Performance of Work:
 - .1 Submit application for payment of holdback amount.
 - .2 Submit sworn statement that accounts for labour, subcontracts, products, construction machinery and equipment, and other indebtedness which may have been incurred in Substantial Performance of Work and for which Owner might in be held responsible have been paid in full, except for amounts properly retained as holdback or as identified amount in dispute.
- .3 After receipt of application for payment and sworn statement, Engineer will issue certificate for payment of holdback amount.
- .4 Amount authorized by certificate for payment of holdback amount is due and payable on day following expiration of holdback period stipulated in lien legislation applicable to Place of Work. Where lien legislation does not exist or apply, holdback amount is due and payable in accordance with other legislation, industry practice, or provisions which may be agreed to between parties. Owner may retain out of holdback amount sums required by law to satisfy liens against Work or, if permitted by lien legislation applicable to Place of Work, other third-party monetary claims against Contractor which are enforceable against Owner.

1.7 FINAL PAYMENT

- .1 Refer to CCDC 4.
- .2 Submit application for final payment when Work is completed.
- .3 Engineer will, no later than 10 days after receipt of application for final payment, review Work to verify validity of application. Engineer will give notification that application is valid or give reasons why it is not valid, no later than 7 days after reviewing Work.
- .4 Engineer will issue final certificate for payment when application for final payment is found valid.

PART 2 – PRODUCTS

2.1 NOT USED .1 Not Used.

PART 3 – EXECUTION

3.1 NOT USED .2 Not Used.

END OF SECTION

PART 1 – GENERAL1.1 ADMINISTRATIVE
RESPONSIBILITIES

- .1 The Owner will be responsible for administrative requirements for the following Contract meetings:
 - .1 Preconstruction
 - .2 Construction Progress
 - .3 Environment
- .2 The Contractor shall be responsible for administrative requirements for the following Contract meetings:
 - .1 Workplace Orientation
 - .2 Safety
- .3 The Owner or the Contractor may request additional meetings related to installation of equipment, commissioning progress, warranty, dispute resolution, environmental issues. Unless otherwise specifically requested by the Contractor, the Owner will be responsible for administrative duties related to these meetings. The agenda for these meetings may be combined with that of the construction progress meetings.

1.2 ADMINISTRATIVE
REQUIREMENTS

- .1 The administrative requirements for Contract meetings include the following:
 - .1 Scheduling and administering the Contract meetings throughout the progress of the Work.
 - .2 Preparing the agenda for the meetings.
 - .3 Distributing to the relevant attendees written notice of each meeting and the proposed agenda at least 3 days in advance of the meeting date.
 - .4 Presiding at the meetings.
 - .5 Recording the minutes including attendance, significant proceedings and decisions, and action required by the parties.
 - .6 Reproducing and distributing copies of the minutes within 7 days after each meeting to the meeting participants and affected parties not in attendance.
- .2 Representatives of the Contractor, Subcontractors, and Suppliers shall attend meetings as necessary and be authorized to act on behalf of the party each represents.

1.3 PRE-CONSTRUCTION
MEETING

- .1 Frequency: Within 15 days after award of the Contract and prior to commencement of activities at the Site.
- .2 Purpose: To review personnel assignments, responsibilities, schedules, submissions, and administrative and procedural requirements.
- .3 Attendees:
 - .1 Contractor's representatives: senior management, site superintendent, major Subcontractors, and others as necessary.
 - .2 Owner's representatives: as determined by the Owner.

- .4 Agenda may include the following:
 - .1 Appointment of representatives of participants in the Work.
 - .2 Schedule of the Work and progress scheduling.
 - .3 Schedule of submittals.
 - .4 Requirements for temporary facilities, site signage, offices, storage sheds, utilities, and fences.
 - .5 Schedule of equipment delivery.
 - .6 Site safety and security.
 - .7 Contemplated changes, change orders, approvals required, costing and mark-up percentages permitted, time extensions, overtime, and administrative requirements.
 - .8 Products and materials provided by the Owner.
 - .9 Record documents.
 - .10 Maintenance manuals.
 - .11 Takeover procedures, acceptance, and warranties.
 - .12 Monthly progress claims, administrative procedures, and holdbacks.
 - .13 Inspection and testing.
 - .14 Insurance and transcripts of policies.
 - .15 Environmental management principles.
 - .16 Mobilization to the Site.

1.4 CONSTRUCTION PROGRESS MEETINGS

- .1 Frequency: Weekly during the course of the Work.
- .2 Purpose: To monitor construction progress, to identify problems and actions required for their solution, and to expedite the Work.
- .3 Attendees:
 - .1 Contractor's representatives: site superintendent and, when so requested by the Owner, Subcontractors, Suppliers, and other parties involved in the Work.
 - .2 Owner's representatives: as determined by the Owner.
- .4 Agenda may include the following:
 - .1 Review and approval of minutes of the previous meeting.
 - .2 Review of the Work progress since the previous meeting.
 - .3 Field observations, problems, and conflicts.
 - .4 Problems that impede the construction schedule.
 - .5 Off-site fabrication delivery schedules.
 - .6 Corrective measures and procedures to regain the Contract schedule.
 - .7 Revisions to the construction schedule.
 - .8 Progress and schedule for the succeeding work period.
 - .9 Submittal schedules.
 - .10 Adherence to quality standards.
 - .11 Contemplated changes effect on the construction schedule and Contract Time.
 - .12 Contentious items of the Work.
 - .13 Contract closeout issues.
 - .14 Safety and security issues.
 - .15 Environmental issues.

.16 Other business.

1.5 WORKPLACE ORIENTATION MEETINGS

- .1 As frequently as required for all new workers prior to commencement of Work on the Site.
- .2 Purpose is to familiarize new workers with site conditions, rules, regulations, safety, and security requirements.
- .3 Attendees included all new Contractor and Owner personnel scheduled to work on the Site.
- .4 Agenda may include the following:
 - .1 Project description including areas of work and other concurrent construction contracts.
 - .2 Hazardous areas including open excavations, construction equipment traffic, blasting, and chemical or explosive storage, etc.
 - .3 Safety equipment to be worn by workers, including areas with special requirements.
 - .4 Traffic routes on the Site.
 - .5 Evacuation procedures.
 - .6 First aid procedures.
 - .7 Excavation or work permit procedures.
 - .8 WHMIS (Workplace Hazardous Materials Information System) requirements for handling and storage of chemicals.
 - .9 Fire safety rules and regulations.
 - .10 Rules and regulations regarding wildlife, environmental concerns, drugs, alcohol, etc.

1.6 SAFETY MEETINGS

- .1 Frequency: Weekly, or more, during the course of the Work for each area of work.
- .2 Purpose: To review safety concerns and implement preventive safety measures.
- .3 Attendees: Contractor's and Owner's personnel for each area of work.
- .4 Agenda may include the following:
 - .1 Review and discussion of safety concerns, accidents, and "near misses."
 - .2 Remedial or preventive actions to be taken.

1.7 ENVIRONMENTAL MEETINGS

- .1 During the course of Work, schedule environment meetings weekly or as required by the Owner to deal with issues that may arise. Dependent on the issues, the Owner may combine the agenda for environmental meetings with that of the construction progress meetings.
- .2 Purpose: To review environment issues and implement mitigative measures.
- .3 Attendees:
 - .1 Contractor's representatives: Contractor's site superintendent and when so requested by Owner, subcontractors, suppliers, and other parties involved in the Work. Contractor's representatives shall be

qualified and authorized to act on behalf of the party each represents.

.2 Owner's representatives: as determined by Owner.

.4 Agenda to include the following:

.1 Review and discussion of environment concerns, accidents and "near misses".

.2 Identify environmental emergency notification procedures.

.3 Identify remedial or preventative action to be taken.

.4 All employees must attend environmental orientation.

PART 2 – PRODUCTS

2.1 NOT USED

.1 Not Used.

PART 3 – EXECUTION

3.1 NOT USED

.1 Not Used.

END OF SECTION

PART 1 – GENERAL1.1 MEASUREMENT AND
PAYMENT

.1

All work described in this section is considered incidental to work described elsewhere and is deemed included in the prices provided by the Contractor in the Unit Price Table. Therefore, no separate payment is to be made for work included in this section.

1.2 ADMINISTRATIVE

.1

Submit to Engineer submittals listed for review. Submit promptly and in orderly sequence to not cause delay in Work. Failure to submit in ample time is not considered sufficient reason for extension of Contract Time and no claim for extension by reason of such default will be allowed.

.2

Do not proceed with Work affected by submittal until review is complete.

.3

Present shop drawings, product data, samples, and mock-ups in SI Metric units.

.4

Where items or information is not produced in SI Metric units converted values are acceptable.

.5

Review submittals prior to submission to Engineer. This review represents that necessary requirements have been determined and verified, or will be, and that each submittal has been checked and co-ordinated with requirements of Work and Contract Documents. Submittals not stamped, signed, dated and identified as to specific project will be returned without being examined and considered rejected.

.6

Notify Engineer, in writing at time of submission, identifying deviations from requirements of Contract Documents stating reasons for deviations.

.7

Verify field measurements and affected adjacent Work are co-ordinated.

.8

Contractor's responsibility for errors and omissions in submission is not relieved by Engineer's review of submittals.

.9

Contractor's responsibility for deviations in submission from requirements of Contract Documents is not relieved by Engineer review.

.10

Keep one reviewed copy of each submission on site.

1.3 SHOP DRAWINGS AND
PRODUCT DATA

.1

The term "shop drawings" means drawings, diagrams, illustrations, schedules, performance charts, brochures and other data which are to be provided by Contractor to illustrate details of a portion of Work.

.2

Submit drawings stamped and signed by professional engineer registered or licensed in the Province of Saskatchewan.

- .3 Indicate materials, methods of construction and attachment or anchorage, erection diagrams, connections, explanatory notes, and other information necessary for completion of Work. Where articles or equipment attach or connect to other articles or equipment, indicate that such items have been coordinated, regardless of Section under which adjacent items will be supplied and installed. Indicate cross references to design drawings and specifications.
- .4 Allow 14 days for Engineer's review of each submission.
- .5 Adjustments made on shop drawings by Engineer are not intended to change Contract Price. If adjustments affect value of Work, state such in writing to Engineer prior to proceeding with Work.
- .6 Make changes in shop drawings as Engineer may require, consistent with Contract Documents. When resubmitting, notify Engineer in writing of revisions other than those requested.
- .7 Accompany submissions with transmittal letter, containing:
 - .1 Date.
 - .2 Project title and number.
 - .3 Contractor's name and address.
 - .a Identification and quantity of each shop drawing, product data and sample.
 - .4 Other pertinent data.
- .8 Submissions include:
 - .1 Date and revision dates.
 - .2 Project title and number.
 - .3 Name and address of:
 - .a Subcontractor.
 - .b Supplier.
 - .c Manufacturer.
 - .4 Contractor's stamp, signed by Contractor's authorized representative certifying approval of submissions, verification of field measurements and compliance with Contract Documents.
 - .5 Details of appropriate portions of Work as applicable:
 - .a Fabrication.
 - .b Layout, showing dimensions, including identified field dimensions, and clearances.
 - .c Setting or erection details.
 - .d Capacities.
 - .e Performance characteristics.
 - .f Standards.
 - .g Operating weight.
 - .h Wiring diagrams.
 - .i Single line and schematic diagrams.
 - .j Relationship to adjacent work.
- .9 After Engineer's review, distribute copies.

- .10 Submit one electronic copy of shop drawings for each requirement requested in specification Sections and as Engineer may reasonably request.
- .11 Submit electronic copies of product data sheets or brochures for requirements requested in specification Sections and as requested by Engineer where shop drawings will not be prepared due to standardized manufacture of product.
- .12 Submit electronic copies of test reports for requirements requested in specification Sections and as requested by Engineer.
 - .1 Report signed by authorized official of testing laboratory that material, product, or system identical to material, product, or system to be provided has been tested in accord with specified requirements.
 - .2 Testing must have been within 3 years of date of contract award for project.
- .13 Submit electronic copies of certificates for requirements requested in specification Sections and as requested by Engineer.
 - .1 Statements printed on manufacturer's letterhead and signed by responsible officials of manufacturer of product, system, or material attesting that product, system or material meets specification requirements.
 - .2 Certificates must be dated after award of project contract complete with project name.
- .14 Submit electronic copies of manufacturer's instructions for requirements requested in specification Sections and as requested by Engineer.
 - .1 Pre-printed material describing installation of product, system, or material, including special notices and Material Safety Data Sheets concerning impedances, hazards and safety precautions.
- .15 Submit electronic copies of Manufacturer's Field Reports for requirements requested in specification Sections and as requested by Engineer.
- .16 Documentation of the testing and verification actions taken by manufacturer's representative to confirm compliance with manufacturer's standards or instructions.
- .17 Submit electronic copies of Operation and Maintenance Data for requirements requested in specification Sections and as requested by Engineer.
- .18 Delete information not applicable to project.
- .19 Supplement standard information to provide details applicable to project.
- .20 If upon review by Engineer, no errors or omissions are discovered or if only minor corrections are made, copies will be returned, and fabrication and installation of Work may proceed. If shop drawings are rejected, noted copy will be returned and resubmission of corrected shop drawings, through same

procedure indicated above, must be performed before fabrication and installation of Work may proceed.

- .21 The review of shop drawings by Engineer is for sole purpose of ascertaining conformance with general concept.
- .1 This review shall not mean that Engineer approves detail design inherent in shop drawings, responsibility for which shall remain with Contractor submitting same, and such review shall not relieve Contractor of responsibility for errors or omissions in shop drawings or of responsibility for meeting requirements of construction and Contract Documents.
- .2 Without restricting generality of foregoing, Contractor is responsible for dimensions to be confirmed and correlated at job site, for information that pertains solely to fabrication processes or to techniques of construction and installation and for co-ordination of Work of sub-trades.

1.4 SAMPLES

- .1 Submit for review samples in duplicate as requested in respective specification Sections. Label samples with origin and intended use.
- .2 Deliver samples prepaid to Engineer's business address.
- .3 Notify Engineer in writing, at time of submission of deviations in samples from requirements of Contract Documents.
- .4 Where colour, pattern, or texture is criterion, submit full range of samples.
- .5 Adjustments made on samples by Engineer are not intended to change Contract Price. If adjustments affect value of Work, state such in writing to Engineer prior to proceeding with Work.
- .6 Make changes in samples which Engineer may require, consistent with Contract Documents.
- .7 Reviewed and accepted samples will become standard of workmanship and material against which installed Work will be verified.

1.5 PHOTOGRAPHIC DOCUMENTATION

- .1 Submit electronic and hard copy of colour digital photography in jpg format, standard resolution, monthly with progress statement and as directed by Engineer.
- .2 Project identification: name and number of project and date of exposure indicated.
- .3 Number of viewpoints: 4 locations.
- .1 Viewpoints and their location as determined by Engineer.

- .4 Frequency of photographic documentation: weekly and as directed by Engineer.

1.6 CERTIFICATES AND
TRANSCRIPTS

- .1 Immediately after award of Contract, submit Workers' Compensation Board status.
- .2 Submit transcription of insurance immediately after award of Contract.

PART 2 – PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 – EXECUTION

3.1 NOT USED

- .1 Not Used.

END OF SECTION

PART 1 – GENERAL1.1 INTENT

- .1 Submit for review shop drawings, product data, and samples called for by the Contract Documents and for such other items as the Engineer may reasonably request.
- .2 Until submittal is reviewed, do not proceed with work involving the relevant product.

1.2 SHOP DRAWINGS

- .1 Shop drawings means technical data specially prepared for work of this Contract, including drawings, diagrams, performance curves, data sheets, schedules, templates, patterns, reports, calculations, instructions, measurements, and similar information not in standard printed form.
- .2 Present shop drawings in a clear and thorough manner to appropriately illustrate the work.
- .3 Identify field dimensions on drawings.
- .4 Identify shop drawings by appropriate references to sheet, detail, schedule or room numbers.
- .5 Maximum drawing size: 860 x 1 120 mm.
- .6 Leave a clear space of 100 mm x 75 mm on each sheet of shop drawings for placement of Engineer's review stamp.
- .7 Submit one set of sepia for each required shop drawing.

1.3 PRODUCT DATA

- .1 Product data means standard printed information describing materials, products, equipment, and systems not specially prepared for work of this Contract, other than the designation of selections.
- .2 Clearly mark product data to identify products.
- .3 Manufacturer's standard schematic drawings, catalogue sheets, diagrams, schedules, performance charts, illustrations and descriptive data will be accepted in lieu of shop drawings provided that:
 - .1 information not applicable to work of this Contract is deleted, and
 - .2 standard information is supplemented with information specifically applicable to the work of this Contract.
- .4 Submit clear reproducible information as follows:
 - .1 One copy when product data is submitted as:
 - .a Data sheets larger than 216 mm x 355 mm. Submit mylars.
 - .b Unbound data sheets 216 mm x 355 mm or smaller. Submit printed or photocopied sheets.
 - .2 Four copies when product data is submitted as follows:
 - .a Information that can not be duplicated using a photocopier with an automatic document feeder, such as bound or multi-fold information.
 - .b Information containing photographs or other information that does not reproduce well on a commercial photocopier.

1.4 SAMPLES

- .1 Samples means cuts or containers of materials or partial sections of manufactured or fabricated components which are physically identical to products proposed for use and which establish minimum standards by which the work will be judged.
- .2 Label samples as to origin and intended use in the Work.

1.5 SUBMITTAL
PREPARATION

- .1 Review, date, and sign shop drawings, product data, and samples prior to submission.
- .2 Determine and verify:
 - .1 Field measurements.
 - .2 Field construction criteria.
 - .3 Catalogue numbers and similar data.
 - .4 Conformance with Contract Documents.
- .3 Coordinate each submittal with requirements of work and Contract documents. Individual drawings will not be reviewed until all related shop drawing and product data are available.
- .4 Notify Engineer, in writing, on the submittal and at the time of submission, of deviations from requirements of Contract Documents.

1.6 SUBMISSION
REQUIREMENTS

- .1 Make submittals sufficiently in advance of date that reviewed submittals will be required and, in such sequence, as to cause no delay in the Work.
- .2 Accompany submittals with transmittal letter, containing:
 - .1 Date.
 - .2 Project title and number.
 - .3 Contractor's name and address.
 - .4 Number of each shop drawing, product data and sample submitted.
 - .5 Other pertinent data.
- .3 Submittals shall include:
 - .1 Date and revision dates.
 - .2 Project title and number.
 - .3 Name of:
 - .a Contractor.
 - .b Subcontractor.
 - .c Supplier.
 - .d Manufacturer.
 - .e Name of detailer when details not prepared by Contractor, subcontractor, or supplier.
 - .4 Contractor's stamp, initialed or signed, certifying review of submittal, verification of field measurements, and compliance with Contract Documents.
- .4 Make corrections or changes to rejected submittals and resubmit, as specified for initial submission.

1.7 RESPONSIBILITY FOR
ERRORS, OMISSIONS AND
DEVIATIONS

.1

Engineer's review of submittals does not relieve Contractor from responsibility for errors and omissions, nor deviations from requirements of the Contract Documents.

1.8 REPRODUCTION OF
SUBMITTALS

.1

After final review, Engineer will reproduce at his expense the number of copies he requires, and return reviewed reproducible documents. Contractor shall reproduce at his expense the number of copies required for performance of the Work.

PART 2 – PRODUCTS2.1 NOT USED

.1

Not Used.

PART 3 – EXECUTION3.1 NOT USED

.1

Not Used.

END OF SECTION

PART 1 – GENERAL1.1 MEASUREMENT OF
PAYMENT

.1

All work described in this section is considered incidental to work described elsewhere and is deemed included in the prices provided by the Contractor in the Unit Price Table. Therefore, no separate payment to be made for work included in this section.

1.2 PROTECTION OF
PUBLIC TRAFFIC

.1

Comply with requirements of Acts, Regulations, and By Laws in force for regulation of traffic or use of roadways upon or over which it is necessary to carry out Work or haul materials or equipment.

.2

When working on travelled way:

- .1 Place equipment in position to minimize interference and hazard to travelling public.
- .2 Keep equipment units as close together as working conditions permit and preferably on same side of travelled way.
- .3 Do not leave equipment on travelled way overnight.

.3

Close lanes of road only after receipt of written approval from the Engineer.

- .1 Before re-routing traffic erect suitable signs and devices to Manual of Uniform Traffic Control Devices for Streets and Highways.

.4

Keep travelled way graded, free from pot holes, and of sufficient width for required number of lanes of traffic. Provide 7 m wide minimum temporary roadway for traffic in two-way sections through Work and on detours.

- .1 Provide 5 m wide minimum temporary roadway for traffic in one-way sections through Work and on detours.

.5

Provide gravelled detours or temporary roads as approved by the Engineer to facilitate passage of traffic around restricted construction area.

1.3 INFORMATION AND
WARNING DEVICES

.1

Provide and maintain signs, flashing warning lights, and other devices required to indicate construction activities or other temporary and unusual conditions resulting from Project Work which requires road user response.

.2

Supply and erect signs, barricades, and miscellaneous warning devices to Manual of Uniform Traffic Control Devices for Streets and Highways.

.3

Place signs and other devices in locations recommended in Manual of Uniform Traffic Control Devices for Streets and Highways.

.4

Meet with the Engineer prior to commencement of Work to prepare list of signs and other devices required for project. If situation on site changes, revise list to approval of the Engineer.

.5

Continually maintain traffic control devices in use:

- .1 Check signs daily for legibility, damage, suitability, and location. Clean, repair, or replace to ensure clarity and reflectance.
- .2 Remove or cover signs which do not apply to conditions existing from day to day.

1.4 CONTROL OF PUBLIC
TRAFFIC

.1

Provide competent flag personnel, trained in accordance with, and properly equipped to Manual of Uniform Traffic Control Devices for Streets and Highways for situations as follows:

- .1 When public traffic is required to pass working vehicles or equipment that block all or part of travelled roadway.
- .2 When it is necessary to institute one way traffic system through construction area or other blockage where traffic volumes are heavy, approach speeds are high and signal system is not in use.
- .3 When workmen or equipment are employed on travelled way over brow of hills, around sharp curves or at other locations where oncoming traffic would not otherwise have adequate warning.
- .4 Where temporary protection is required while other traffic control devices are being erected or taken down.
- .5 For emergency protection when other traffic control devices are not readily available.
- .6 In situations where complete protection for workers, working equipment and public traffic is not provided by other traffic control devices.
- .7 Delays to public traffic due to contractor's operators: 15 minutes maximum.

.2

Where roadway, carrying two way traffic, is restricted to one lane, for 24 hours each day, provide portable traffic signal system.

- .1 Adjust, as necessary, and regularly maintain system during period of restriction.
- .2 Ensure signal system meets requirements of Manual of Uniform Traffic Control Devices for Streets and Highways.

1.5 OPERATIONAL
REQUIREMENTS

.1

Maintain existing conditions for traffic throughout period of contract except that, when required for construction under contract and when measures have been taken as specified and approved by the Engineer to protect and control public traffic.

.2

Maintain existing conditions for traffic crossing right of way.

.3

Maintain existing conditions for traffic crossing right of way except when required for construction.

PART 2 – PRODUCTS2.1 NOT USED

.1

Not Used.

PART 3 – EXECUTION3.1 NOT USED

.1

Not Used.

END OF SECTION

PART 1 – GENERAL1.1 REFERENCES

- .1 Canada Labour Code, Part 2, Canada Occupational Safety and Health Regulations
- .2 Health Canada/Workplace Hazardous Materials Information System (WHMIS)
 - .1 Safety Data Sheets (SDS).
- .3 Province of Saskatchewan
 - .1 Occupational Health and Safety Act, 1993, S.S. 2005.

1.2 MEASUREMENT FOR PAYMENT

- .1 All work described in this section is considered incidental to work described elsewhere and is deemed included in the prices provided by the Contractor in the Unit Price Table. Therefore, no separate payment to be made for work included in this section.

1.3 SUBMITTALS

- .1 Make submittals in accordance with Section 01 33 00 – Submittal Procedures.
- .2 Submit site-specific Health and Safety Plan within 7 days after date of Notice to Proceed and prior to commencement of Work. Health and Safety Plan must include:
 - .1 Results of site specific safety hazard assessment.
 - .2 Results of safety and health risk or hazard analysis for site tasks and operation found in work plan.
- .3 Submit 2 copies of Contractor's authorized representative's work site health and safety inspection reports to Engineer weekly.
- .4 Submit copies of reports or directions issued by Federal, Provincial, and Territorial health and safety inspectors.
- .5 Submit copies of incident and accident reports.
- .6 Engineer will review Contractor's site-specific Health and Safety Plan and provide comments to Contractor within 7 days after receipt of plan. Revise plan as appropriate and resubmit plan to Engineer within 7 days after receipt of comments from Engineer.
- .7 Engineer's review of Contractor's final Health and Safety plan should not be construed as approval and does not reduce the Contractor's overall responsibility for construction Health and Safety.
- .8 Medical Surveillance: where prescribed by legislation, regulation, or safety program, submit certification of medical surveillance for site personnel prior

		to commencement of Work, and submit additional certifications for any new site personnel to Engineer.
	.9	On-site Contingency and Emergency Response Plan: address standard operating procedures to be implemented during emergency situations.
<u>1.4 FILING OF NOTICE</u>	.1	File Notice of Project with Provincial authorities prior to beginning of Work.
<u>1.5 SAFETY ASSESSMENT</u>	.1	Perform site specific safety hazard assessment related to project.
<u>1.6 MEETINGS</u>	.1	Schedule and administer Health and Safety meeting with Engineer prior to commencement of Work.
<u>1.7 REGULATORY REQUIREMENTS</u>	.1	Do Work in accordance with Section 01 41 00 – Regulatory Requirements.
<u>1.8 PROJECT/SITE CONDITIONS</u>	.1	Work at site will involve contact with: .1 Power, water, gas, and electrical utilities. .2 Motor vehicles.
<u>1.9 GENERAL REQUIREMENTS</u>	.1	Develop written site-specific Health and Safety Plan based on hazard assessment prior to beginning site Work and continue to implement, maintain, and enforce plan until final demobilization from site. Health and Safety Plan must address project specifications.
	.2	Engineer may respond in writing where deficiencies or concerns are noted and may request re-submission with correction of deficiencies or concerns.
<u>1.10 RESPONSIBILITY</u>	.1	Be responsible for health and safety of persons on site, safety of property on site, and for protection of persons adjacent to site and environment to extent that they may be affected by conduct of Work.
	.2	Comply with and enforce compliance by employees with safety requirements of Contract Documents, applicable federal, provincial, territorial, and local statutes, regulations, and ordinances, and with site-specific Health and Safety Plan.
<u>1.11 COMPLIANCE</u>	.1	Comply with Occupational Health and Safety Regulations, 1996.

REQUIREMENTS

.2

Comply with Canada Labour Code, Canada Occupational Safety and Health Regulations.

1.12 UNFORESEEN HAZARDS

.1

When unforeseen or peculiar safety-related factor, hazard, or condition occur during performance of Work, follow procedures in place for Employee's Right to Refuse Work in accordance with Acts and Regulations of Province having jurisdiction and advise Engineer verbally and in writing.

1.13 HEALTH AND SAFETY
CO-ORDINATOR

.1

Employ and assign to Work competent and authorized representative as Health and Safety Co-ordinator. Health and Safety Co-ordinator must:

- .1 Have working experience specific to activities associated with underground pipe installation.
- .2 Have working knowledge of occupational safety and health regulations.
- .3 Be responsible for completing Contractor's Health and Safety Training Sessions and ensuring that personnel not successfully completing required training are not permitted to enter site to perform Work.
- .4 Be responsible for implementing, enforcing daily, and monitoring site-specific Contractor's Health and Safety Plan.
- .5 Be on site during execution of Work.

1.14 POSTING OF
DOCUMENTS

.1

Ensure applicable items, articles, notices, and orders are posted in conspicuous location on site in accordance with Acts and Regulations of Province having jurisdiction, and in consultation with Engineer.

1.15 CORRECTION OF
NON-COMPLIANCE

.1

Immediately address health and safety non-compliance issues identified by authority having jurisdiction or by Engineer.

.2

Provide Engineer with written report of action taken to correct non-compliance of health and safety issues identified.

.3

Engineer may stop Work if non-compliance of health and safety regulations is not corrected.

1.16 BLASTING

.1

Blasting or other use of explosives is not permitted.

1.17 POWDER ACTUATED
DEVICES .1

Use powder actuated devices only after receipt of written permission from Engineer.

1.18 WORK STOPPAGE .1

Give precedence to safety and health of public and site personnel and protection of environment over cost and schedule considerations for Work.

PART 2 – PRODUCTS2.1 NOT USED .1

Not Used.

PART 3 – EXECUTION3.1 NOT USED .1

Not Used.

END OF SECTION

PART 1 – GENERAL1.1 RELATED
REQUIREMENTS

- .1 Section 31 23 33.01 – Excavating, Trenching, and Backfilling.

1.2 ACTION AND
INFORMATIONAL
SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 – Submittal Procedures.

- .2 Product Data:

- .1 Submit manufacturer's instructions, printed product literature, and data sheets for products supplied through contract and include product characteristics, performance criteria, physical size, finish, and limitations.
- .2 Submit 1 copy of WHMIS SDS in accordance with Section 01 35 29.06 - Health and Safety Requirements and 01 35 43 - Environmental Procedures.

1.3 FIRES

- .1 Fires and burning of rubbish on site is not permitted.

1.4 DRAINAGE

- .1 Develop and submit erosion and Sediment Control Plan (ESC) identifying type and location of erosion and sediment controls provided. Plan to include monitoring and reporting requirements.
- .2 Provide temporary drainage and pumping required to keep excavations and site free from water.
- .3 Ensure pumped water into waterways, sewer or drainage systems is free of suspended materials.
- .4 Control disposal or runoff of water containing suspended materials or other harmful substances in accordance with local authority requirements.

1.5 TERRESTRIAL
RESOURCES

- .1 Wildlife:
- .1 Do not allow pets on the Site.
- .2 Do not allow firearms, hunting, or shooting on the Site.
- .3 Prevent livestock from entering the Site by installing new fences specified in the Contract Documents; and installing temporary fences as necessary.
- .4 Do not harass wildlife.
- .5 Contractor shall install a snow fence (minimum) around all open excavations that are to be left open over night.
- .6 Contractor shall contact Alberta Sustainable Resources at (403)529-3680 if any wildlife is at risk as a result of the work.
- .2 Vegetation and Weed Control:
- .1 Remove or control existing and new adverse vegetation that affects adjacent landowners and their croplands, construction operations, or the function of the Permanent Work.

1.6 WORK ADJACENT
TO WATERWAYS

- .2 Do not import any materials to the Site that are contaminated with weed seeds. Clean dirty construction and reclamation equipment to prevent importing weed seeds.
- .3 Notify the Owner prior to commencing adverse vegetation control measures.
- .4 Be responsible for damage to crops, both on and off the Site, resulting from the Contractor's use of herbicides, or other adverse vegetation control measures.
- .5 Maintain records of the types and amounts of herbicides purchased, delivered, stored, mixed, and used, and the means of disposal of all excess. Maintain the records current and accurate and make them available for review by the Owner.
- .6 Monitor the site for early detection of weed growth during the growing season.
- .7 Control weeds once by mechanical equipment before they go to seed, but not before August 1 and at no extra cost to the Owner.
- .1 Unless otherwise provided for in the Contract Documents, do not divert, alter, or disrupt water flows in rivers, streams, and other surface bodies of water.
- .2 Prevent bark, slash, wood chips, sawdust, ashes, organic debris, topsoil, fuel and lubricants, or other substances harmful to aquatic life from entering a river, stream, or other surface bodies of water.
- .3 Do not perform construction operations within the wetted perimeter of a river, stream, and other surface bodies of water unless such work is part of the Permanent Work or Temporary Work.
- .4 Do not deepen by excavation or place fill material on the river or stream bed or other surface bodies of water unless such work is part of the Permanent Work or Temporary Work.
- .5 Manage construction operations to limit equipment crossings of rivers and streams and prevent turbidity and siltation during crossings. Install temporary culverts or bridge structures where frequent crossings are required.
- .6 Use clean granular fill with less than 5% fines passing the 80gm sieve size when exposed to a river or stream for Temporary Work such as cofferdams, causeways, and access ramps. Fine-grained soils may be used, provided only clean granular fill is exposed to the body of water at any time during construction and restoration operations.
- .7 Remove Temporary Work, including culverts and bridges, and reclaim river and stream banks and bed, and other disturbed areas, prior to attaining Substantial Performance of the Work unless specified otherwise.
- .8 Protect fish and fish habitat in rivers, streams, and other surface bodies of water located within the Site in accordance with the Contract Documents and Regulatory Requirements.

1.7 GROUNDWATER
RESOURCES

- .1 Do not change ground water levels in wells located on adjacent lands.
- .2 Do not change ground water quality in adjacent landowner wells.
- .3 Be responsible for and maintain silt fences until date of Warranty Performance of the Work.
- .4 Inspect silt fencing at intervals appropriate to weather events. Based on inspections maintain silt fencing in functional condition, remove silt accumulations and dispose on site at locations acceptable to the Owner.
- .5 Unless otherwise specified in the Contract Documents, or otherwise requested by the Owner, remove temporary silt fencing within 30 days after date of Warranty Performance of the Work.

1.7 POLLUTION
CONTROL

- .1 Waste Management:
 - .1 Separate waste materials for reuse and recycling. Remove construction waste, including demolition waste, from the Site unless otherwise specified. Dispose of such waste at the waste disposal facility identified in the Environmental Management Plan.
 - .2 Do not burn, bury, or otherwise discharge construction or demolition waste on the Site unless specified otherwise.
 - .3 When practical, minimize the amount of waste generated from construction operations and demolitions by salvaging materials for recycling. Salvage and segregate metal, plastic, paper, cardboard, and glass and transfer them to the nearest appropriate collection facility.
- .2 Hazardous Materials:
 - .1 Transport hazardous materials to and from the Site in accordance with Regulatory Requirements.
 - .2 Use and store hazardous materials in accordance with Regulatory Requirements.
 - .3 Remove spilled hazardous materials, including hazardous liquid wastes, in accordance with Regulatory Requirements, and reclaim land and other property. Report spills to the Engineer and the Owner.
 - .4 Dispose of hazardous waste materials, including hazardous liquid wastes, in accordance with Regulatory Requirements.
- .3 Handling of Construction Equipment Fuels and Lubricants:
 - .1 Employ persons qualified to handle Construction Equipment fuels and lubricants.
 - .2 Maintain a setback distance of 100 m between stored Construction Equipment fuels and lubricants and rivers, streams, and other surface bodies of water.
 - .3 Prevent handling and fuelling operations from contaminating the ground, surface water, and ground water. Use containment berms and an impermeable base course or other system to contain spilled fuel.

	.4	Clearly mark and barricade fuel storage areas and non-portable transfer lines. Use markers that are visible under all weather conditions.
	.5	Store waste Construction Equipment lubricants in a tank or closed container and dispose of off-Site in accordance with the Regulatory Requirements.
	.4	Air Pollution:
	.1	Prevent the discharge of atmospheric contaminants from construction operations in accordance with Regulatory Requirements.
	.2	Do not operate equipment, including Construction Equipment, that shows excessive emissions of exhaust gases until corrective repairs or adjustments are made.
	.3	Control dust on the Site, and prevent dust from the Site from damaging crops, orchards, cultivated fields, and dwellings, or causing a nuisance to persons. Be responsible for damages from dust caused by construction operations.
<u>1.8 HISTORICAL/ ARCHAEOLOGICAL CONTROL</u>	.1	Notify Engineer promptly and cease all work until directed otherwise if historical, archaeological, or cultural artifacts or resources are discovered during construction.
<u>1.9 NOTIFICATION</u>	.1	Engineer will notify Contractor in writing of observed noncompliance with Federal, Provincial or Municipal environmental laws or regulations, permits, and other elements of Contractor's Environmental Protection plan.
	.2	Contractor: after receipt of such notice, inform Engineer of proposed corrective action and take such action for approval by Engineer.
	.1	Take action only after receipt of written approval by Engineer.
	.3	Engineer will issue stop order of work until satisfactory corrective action has been taken.
	.4	No time extensions granted, or equitable adjustments allowed to Contractor for such suspensions.
<u>PART 2 – PRODUCTS</u>		
<u>2.1 NOT USED</u>	.1	Not Used.

PART 3 – EXECUTION

3.1 CLEANING

- .1 Progress Cleaning: clean in accordance with Section 01 74 11 – Cleaning.
 - .1 Leave Work area clean at end of each day.
- .2 Burying of rubbish and waste materials on site is not permitted.
- .3 Ensure waterways and wetlands remain free of waste and volatile materials disposal.
- .4 Final Cleaning: upon completion remove surplus materials, rubbish, tools, and equipment in accordance with Section 01 74 11 - Cleaning.

END OF SECTION

PART 1 – GENERAL1.1 REQUIREMENTS INCLUDED

- .1 Contractor responsible for following all required Regulations affecting the Work including but not limited to:

- .1 Water Security Agency
- .2 Saskatchewan Power Corporation
- .3 Saskatchewan Water Corporation
- .4 Saskatchewan Telecommunications
- .5 Saskatchewan Energy
- .6 Fisheries and Oceans Canada
- .7 Navigation Protection Act
- .8 Environment Canada
- .9 National Energy Board
- .10 Occupational Health and Safety
- .11 Municipal by-laws and servicing standards
- .12 Municipal utilities
- .13 Saskatchewan Environment

1.2 COMPLIANCE WITH REGULATIONS

- .1 Ascertain requirements and regulations of authorities listed above.
- .2 Comply with all such requirements and regulations as applicable to the Work.
- .3 Requirements set out in this Section are for guidance and information and are not necessarily complete.
- .4 If the Contract Documents are at variance with Regulatory Requirements, notify the Owner in writing, requesting direction, immediately after such variance becomes known.
- .5 If the Contractor fails to notify the Owner in writing and obtain the Owner's direction related to variations in Regulatory Requirements and performs work knowing it to be contrary to Regulatory Requirements, the Contractor accepts responsibility for correcting violations thereof, and bears the costs, expenses, and damages attributable to the Contractor's failure to comply with the provisions of such Regulatory Requirements.

1.3 PERMITS

- .1 Notwithstanding the provisions of CCDC 4, Owner will obtain construction permits required from:
- .1 Ministry of Environment.
- .2 Obtain all construction permits necessary for the Works other than those listed under the above item.

1.4 WORK IN VICINITY OF OVERHEAD POWER LINES

- .1 Request power company to relocate, de-energize or guard any energized conductor where construction equipment may operate within 3 m of conductor.
- .2 Obtain power company approval prior to operating any equipment within 3 m of energized conductor.

- .3 Where practical, avoid storage of metallic pipe sections under high voltage overhead power lines.
- .4 If pipe sections must be stored under power lines, protect personnel from effects of induced currents by grounding pipe sections at two (2) locations with AWG #2 copper ground conductors and grounding rods.
- .5 Complete and submit WCB Form 30M33 prior to commencement of work.

1.5 MIGRATORY BIRD ACT

- .1 The Migratory Bird Act prohibits disturbance to migratory birds, their eggs and habitat during nesting seasons. Vegetation clearing should be arranged to take place outside if the migratory bird nesting season.
- .2 Clearing and grubbing shall be targeted to occur outside the migratory bird nesting window for the region.
- .3 If clearing is to occur during the migratory nesting window, the Contractor shall employ a qualified biologist (at Contractor's cost) to conduct a bird survey of the target area and provide recommendations.
- .4 the Contractor shall mitigate any delays resulting from biologist recommendations.

PART 2 – PRODUCTS2.1 NOT USED

- .1 Not used.

PART 3 – EXECUTION3.1 NOT USED

- .1 Not used.

END OF SECTION

PART 1 – GENERAL1.1 LATEST EDITIONS

.1

All references to specifications, standards, or methods of technical associations refer to the latest adopted revision, including all amendments, in effect on the date of submission of bids, except where a date or issue is specifically noted.

1.2 ABBREVIATIONS

AANDC Aboriginal Affairs and Northern Development Canada

AASHTO American Association of State Highway and Transportation Officials

ACI American Concrete Institute

AFBMA Antifriction Bearing Manufacturers Association

AGA American Gas Association

AGMA American Gear Manufacturers Association

AISC American Institute of Steel Construction

AMCA Air Moving and Conditioning Association

ANSI American National Standards Institute

API American Petroleum Institute

ARI Air-Conditioning and Refrigeration Institute

ASCE American Society of Civil Engineers

ASHRAE American Society of Heating, Refrigerating and Air Conditioning Engineers

ASME American Society of Mechanical Engineers

ASTM American Society for Testing and Materials

AWMAC Architectural Woodworkers Manufacturers Association of Canada

AWPA American Wood Preservers Association

AWS American Welding Society

AWWA American Water Works Association

CAN Canadian National Standard

CBM Certified Ballast Manufacturers

CBTIC Clay Brick and Tile Institute of Canada

CEC Canadian Electrical Code

CEMA Canadian Electrical Manufacturers Association

CGA Canadian Gas Association

CGRA Canadian Good Roads Association

CGSB Canadian General Standards Board

CISC Canadian Institute of Steel Construction
CITC Canadian Institute of Timber Construction
CLA Canadian Lumbermen Association
CMAA Crane Manufacturers Association of America
CMHC Canada Mortgage and Housing Corporation
CPCA Canadian Painting Contractors Association
CPCI Canadian Prestressed Concrete Institute
CRCA Canadian Roofing Contractors Association
CRSI Concrete Reinforcing Steel Institute
CSA Canadian Standards Association
CSSBI Canadian Sheet Steel Building Institute
CUA Canadian Underwriters Association
CWB Canadian Welding Bureau
CWC Canadian Wood Council
CSPI Corrugated Steel Pipe Institute
EEI Edison Electric Institute
EEMAC Electrical and Electronic Manufacturers of Canada
FFPC Federal Fire Prevention Committee
FM Factory Mutual Engineering Corporation
IAO Insurers' Advisory Organization
IBRM Institute of Boiler and Radiator Manufacturers
IEC International Electrotechnical Commission
IEE Institution of Electrical Engineers (U.K.)
IEEE Institute of Electrical and Electronics Engineers
IES Illuminating Engineering Society
IGMAC Insulated Glass Manufacturers Association of Canada
IPCEA Insulated Power Cable Engineers Association
ISA Instrument Society of America
ISO International Standardization Organization
LEMA Lighting Equipment Manufacturers Association
LTIC Laminated Timber Institute of Canada
MMA Millwork Manufacturers Association
NAAMM National Association of Architectural Metal Manufacturers
NBC National Building Code of Canada

NEC National Electrical Code
 NESC National Electric Safety Code
 NFPA National Fire Protection Association
 NLGA National Lumber Grade Authority
 OECI Overhead Electrical Crane Institute
 PCA Portland Cement Association
 PCI Prestressed Concrete Institute
 RLM RLM Standards Institute
 RTAC Road and Transportation Association of Canada
 SAE Society of Automotive Engineers
 SBI Steel Boilers Institute
 SJI Steel Joist Institute
 SSPC Steel Structures Painting Council
 TTMAC Terrazzo, Tile and Marble Association of Canada
 ULC Underwriters' Laboratories of Canada
 USFG United States Federal Government
 WCB Workers' Compensation Board

1.3 CONFORMANCE

- .1 Conform to these standards, in whole or in part as specifically requested in Specifications.
- .2 If there is question as to whether any product or system is in conformance with applicable standards, Engineer reserves the right to have such products or systems tested to prove or disprove conformance.
- .3 The cost for such testing will be borne by Owner in the event of conformance with Contract Documents or by Contractor in the event of non-conformance.

PART 2 – PRODUCTS**2.1 NOT USED**

- .1 Not used.

PART 3 – EXECUTION**3.1 NOT USED**

- .1 Not used.

END OF SECTION

PART 1 – GENERAL1.1 MEASUREMENT OF
PAYMENT

.1

All work described in this section is considered incidental to work described elsewhere and is deemed included in the prices provided by the Contractor in the Unit Price Table. Therefore, no separate payment to be made for work included in this section.

1.2 INSPECTION

.1

Allow Engineer access to Work. If part of Work is in preparation at locations other than Place of Work, allow access to such Work whenever it is in progress.

.2

Give timely notice requesting inspection if Work is designated for special tests, inspections or approvals by Engineer instructions, or law of Place of Work.

.3

If Contractor covers or permits to be covered Work that has been designated for special tests, inspections or approvals before such is made, uncover such Work, have inspections or tests satisfactorily completed and make good such Work.

.4

Engineer will order part of Work to be examined if Work is suspected to be not in accordance with Contract Documents. If, upon examination such work is found not in accordance with Contract Documents, correct such Work and pay cost of examination and correction.

1.3 INDEPENDENT
INSPECTION AGENCIES

.1

Independent Inspection/Testing Agencies will be engaged by Engineer for purpose of inspecting and/or testing portions of Work.

.2

Provide equipment required for executing inspection and testing by appointed agencies.

.3

Employment of inspection/testing agencies does not relax Contractor's responsibility to perform Work in accordance with Contract Documents.

.4

If defects are revealed during inspection and/or testing, appointed agency will request additional inspection and/or testing to ascertain full degree of defect. Correct defects and irregularities as advised by Engineer at no cost to Engineer. Pay costs for retesting and re-inspection.

1.4 ACCESS TO WORK

.1

Allow inspection/testing agencies access to Work, off site manufacturing and fabrication plants.

.2

Co-operate to provide reasonable facilities for such access.

1.5 PROCEDURES

- .1 Notify appropriate agency and Engineer in advance of requirement for tests, in order that attendance arrangements can be made.
- .2 Submit samples and/or materials required for testing, as specifically requested in specifications. Submit with reasonable promptness and in orderly sequence to not cause delays in Work.
- .3 Provide labour and facilities to obtain and handle samples and materials on site. Provide sufficient space to store and cure test samples.
- .4 All testing required to meet specifications is Quality Control testing to be conducted by a certified material and testing agencies to be engaged and paid by Contractor.
- .5 Engineer may engage an independent testing laboratory to conduct random Quality assurance testing and will pay for that testing.

1.6 REJECTED WORK

- .1 Remove defective Work, whether result of poor workmanship, use of defective products or damage and whether incorporated in Work or not, which has been rejected by Engineer as failing to conform to Contract Documents. Replace or re-execute in accordance with Contract Documents.
- .2 Make good other Contractor's work damaged by such removals or replacements promptly.
- .3 If in opinion of Engineer it is not expedient to correct defective Work or Work not performed in accordance with Contract Documents, Engineer will deduct from Contract Price difference in value between Work performed and that called for by Contract Documents, amount of which will be determined by Engineer.

1.7 REPORTS

- .1 Submit 4 copies of inspection and test reports to Engineer.
- .2 Provide copies to subcontractor of work being inspected or tested and manufacturer or fabricator of material being inspected or tested.

1.8 TESTS AND MIX
DESIGNS

- .1 Not Used

PART 2 – PRODUCTS2.1 NOT USED

- .1 Not Used.

A-NMS014500++

District of Lakeland No. 521
Landfill Decommissioning
Project Specification

QUALITY CONTROL

Section 01 45 00
Page 3 of 3
2026-09-10

PART 3 – EXECUTION

3.1 NOT USED

.1

Not Used.

END OF SECTION

PART 1 – GENERAL1.1 CONTRACTOR'S
GENERAL RESPONSIBILITIES
FOR EXISTING UTILITIES

- .1 The approximate existence of service lines known to the Owner are indicated in the Contract Documents. Confirm the number, type, location and elevation of all existing service lines. Contact the appropriate Utility to locate all lines, conduits, and other such structures. Notify the Owner if any service lines have been omitted from or are incorrectly specified in the Contract Documents.
- .2 Identify, stake, and flag all existing service line locations and elevations. Maintain staking and flagging.
- .3 Notify the appropriate Utility prior to carrying out operations in the vicinity of the service lines. Comply with the requirements of, and co—operate fully with, each Utility for the location and protection of the service lines during the Work.
- .4 Be responsible to the Utility for any claims resulting from damage to the service lines as a result of the Contractor's construction operations.
- .5 Promptly notify the Utility and the Owner in the event of any damage or interruption to any services caused by the Contractor's construction operations. Co-operate with the Utility in the restoration of service as promptly as possible and bear all costs arising from the damage or interruption.

1.2 TEMPORARY UTILITIES

- .1 Provide the specified temporary utilities and as otherwise required in order to execute the Work expeditiously. Remove the temporary utilities from the Site upon completion of the Work unless specified otherwise.

1.3 TEMPORARY POWER
AND LIGHT

- .1 Provide power for the Owner's Site office if Site office is deemed necessary.
- .2 Arrange for connection with the appropriate Utility. Pay all costs for installation, maintenance, power consumption, and removal.
- .3 Provide and maintain sufficient temporary power for all construction equipment required to carry out the Work.
- .4 Provide and maintain adequate lighting to safely perform the Work. Provide white light for night construction. Avoid light pollution off the Site.
- .5 Where failure of the normal lighting system would endanger workers, provide an emergency lighting system capable of producing sufficient dependable illumination to enable the workers to:
- .1 leave the worksite;
 - .2 initiate emergency shut-down procedures; or
 - .3 restore normal lighting.

1.4 TEMPORARY HEATING
AND VENTILATION

- .1 Provide temporary heating for the Owner's Site office if site office is deemed necessary including maintenance and fuel consumption during the period of construction up to the date of Substantial Performance. Design the heating system for a temperature differential of 60°C and to be capable of maintaining a minimum temperature of 16° C.
- .2 Provide temporary heating for construction as specified in the Contract Documents.

1.5 TEMPORARY WATER
SUPPLY

- .1 Provide a continuous supply of potable water for the Owner's Site office if Owners Site office is deemed necessary.
- .2 Pay all costs for providing potable water.

1.6 TEMPORARY
SANITATION FACILITIES

- .1 Provide separate sanitation facilities for male and female workers on the Site in accordance with the requirements of the local health authorities.
- .2 Provide sanitation facilities for the Owner's site office, if site office is deemed necessary.
- .3 Provide toiletry consumables and maintain sanitation facilities in a clean condition.
- .4 Arrange and pay all costs for installation, maintenance, and removal.

1.7 TEMPORARY NATURAL
GAS OR PROPANE SUPPLY

- .1 Provide a continuous supply of natural gas or propane for the Owner's site office if site office is deemed necessary.
- .2 Arrange for connection with the appropriate Utility and pay all costs for installation, maintenance, and removal.
- .3 Pay for utility charges.

PART 2 – PRODUCTS2.1 NOT USED

- .1 Not Used.

PART 3 – EXECUTION3.1 NOT USED

- .1 Not Used.

END OF SECTION

PART 1 – GENERAL1.1 REFERENCES

- .1 Canadian Construction Documents Committee (CCDC)
 - .1 CCDC 4-2011, Unit Price Contract.
- .2 Canada Green Building Council (CaGBC)
 - .1 LEED Canada-NC Version 1.0-[2004], LEED (Leadership in Energy and Environmental Design): Green Building Rating System Reference Package For New Construction and Major Renovations (including Addendum [2007]).
 - .2 LEED Canada-CI Version 1.0-[2007], LEED (Leadership in Energy and Environmental Design): Green Building Rating System Reference Guide For Commercial Interiors.
- .3 Canadian General Standards Board (CGSB)
 - .1 CAN/CGSB 1.189-[00], Exterior Alkyd Primer for Wood.
 - .2 CGSB 1.59-[97], Alkyd Exterior Gloss Enamel.
- .4 Canadian Standards Association (CSA International)
 - .1 CSA-A23.1/A23.2-[04], Concrete Materials and Methods of Concrete Construction/Methods of Test and Standard Practices for Concrete.
 - .2 CSA-0121-[M1978(R2003)], Douglas Fir Plywood.
 - .3 CAN/CSA-S269.2-[M1987(R2003)], Access Scaffolding for Construction Purposes.
 - .4 CAN/CSA-Z321-[96(R2001)], Signs and Symbols for the Occupational Environment.
- .5 Public Works Government Services Canada (PWGSC) Standard Acquisition Clauses and Conditions (SACC)-ID: R0202D, Title: General Conditions 'C', In Effect as of: May 14, 2004.
- .6 U.S. Environmental Protection Agency (EPA) / Office of Water
 - .1 EPA 832R92005, Storm Water Management for Construction Activities: Developing Pollution Prevention Plans and Best Management Practices.

1.2 ACTION AND INFORMATIONAL SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00 – Submittal Procedures.

1.3 INSTALLATION AND REMOVAL

- .1 Prepare site plan indicating proposed location and dimensions of areas to be fenced, stockpile locations, materials storage areas, marshalling / parking areas, areas otherwise used by Contractor, location and number of trailers to be used, avenues of ingress/egress to work area and details of fence installation.
- .2 Identify areas which have to be graveled to prevent tracking of mud.

- .3 Indicate use of supplemental or other staging area.
- .4 Provide construction facilities in order to execute work expeditiously.
- .5 Remove from site all such work after use.

1.4 SITE STORAGE/
LOADING

- .1 Refer to CCDC 4.
- .2 Confine work and operations of employees by Contract Documents. Do not unreasonably encumber premises with products.
- .3 Do not load or permit to load any part of Work with weight or force that will endanger Work.

1.5 CONSTRUCTION
PARKING

- .1 Parking will be permitted on site provided it does not disrupt performance of Work.
- .2 Provide and maintain adequate access to project site.

1.6 SECURITY

- .1 Contractor shall implement any measures required to ensure the safety and integrity of the worksite, at no additional cost to the owner.

1.7 OFFICES

- .1 Contractor may provide office heated to 22 degrees C, lighted 750 lx and ventilated, of sufficient size to accommodate site meetings and furnished with drawing laydown table, as required. It is not anticipated to be required for this project.
- .2 Provide marked and fully stocked first-aid case in a readily available location.
- .3 Subcontractors may provide their own offices as deemed necessary. Direct location of these offices.
- .4 Maintain office in neat and tidy condition.
- .5 Engineer's Site office.
 - .1 A temporary office for Engineer is not required.

1.8 EQUIPMENT,
TOOL AND MATERIALS
STORAGE

- .1 Provide and maintain, in clean and orderly condition, lockable weatherproof sheds for storage of tools, equipment and materials.
- .2 Locate materials not required to be stored in weatherproof sheds on site in manner to cause least interference with work activities.

1.9 SANITARY
FACILITIES

- .1 Provide sanitary facilities for work force in accordance with governing regulations and ordinances.
- .2 Post notices and take precautions as required by local health authorities. Keep area and premises in sanitary condition.

1.10 CONSTRUCTION
SIGNAGE

- .1 Provide and erect Contractor construction sign, within three weeks of signing Contract, in a location approved by Engineer.
- .2 Contractor Construction sign dimensions and materials to be approved by Engineer.
- .3 Install owner provided project sign, provided by funding program, at no additional cost, at location designated by Engineer.
- .4 No other signs or advertisements, other than warning signs, are permitted on site.

1.11 PROTECTION AND
MAINTENANCE OF
TRAFFIC

- .1 Owner will provide and upkeep access roads as necessary to maintain traffic.
 - .2 Advise Engineer promptly if road maintenance is required to maintain site activities.
 - .3 Protect travelling public from damage to person and property.
 - .4 Contractor's traffic on roads selected for hauling material to and from site to interfere as little as possible with public traffic.
 - .5 Verify adequacy of existing roads and allowable load limit on these roads. Contractor: responsible for repair of damage to public roads caused by construction operations.
 - .6 Provide necessary lighting, signs, barricades, and distinctive markings for safe movement of traffic.
 - .7 Dust control: adequate to ensure safe operation at all times.
 - .8 Provide snow removal during period of Work, if applicable.
- OR
- .9 Provide access and temporary relocated roads as necessary to maintain traffic.
 - .10 Maintain and protect traffic on affected roads during construction period except as otherwise specifically directed by the Engineer.
 - .11 Provide measures for protection and diversion of traffic, including provision of watch-persons and flag-persons, erection of barricades, placing of lights

around and in front of equipment and work, and erection and maintenance of adequate warning, danger, and direction signs

- .12 Protect travelling public from damage to person and property.
- .13 Contractor's traffic on roads selected for hauling material to and from site to interfere as little as possible with public traffic.
- .14 Verify adequacy of existing roads and allowable load limit on these roads. Contractor: responsible for repair of damage to roads caused by construction operations.
- .15 Construct access and haul roads necessary.
- .16 Haul roads: constructed with suitable grades and widths; sharp curves, blind corners, and dangerous cross traffic shall be avoided.
- .17 Provide necessary lighting, signs, barricades, and distinctive markings for safe movement of traffic.
- .18 Dust control: adequate to ensure safe operation at all times.
- .19 Location, grade, width, and alignment of construction and hauling roads: subject to approval by the Engineer.
- .20 Lighting: to assure full and clear visibility for full width of haul road and work areas during night work operations.
- .21 Provide snow removal during period of Work.
- .22 Remove, upon completion of work, haul roads designated by the Engineer.

1.12 CLEAN-UP

- .1 Remove construction debris, waste materials, packaging material from work site daily.
- .2 Clean dirt or mud tracked onto paved or surfaced roadways.
- .3 Store materials resulting from demolition activities that are salvageable.
- .4 Stack stored new or salvaged material not in construction facilities.

PART 2 – PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 – EXECUTION

3.1 NOT USED

.1 Not Used.

END OF SECTION

PART 1 – GENERAL1.1 REFERENCES

- .1 Provide traffic accommodation in accordance with the following standards (latest revision) except where specified otherwise.
- .2 Saskatchewan Highways and Transportation
 - .1 8400 — Specification for Traffic Accommodation and Safety

1.2 PUBLIC HIGHWAYS
AND ROADS

- .1 Comply with all requirements of the road authority having jurisdiction over public roads used by the Contractor in the execution of the Work.
- .2 Determine the condition and availability of public highways and roads, clearances, restrictions, bridge load limits, bond requirements, and other limitations that may affect ingress to and egress from the Site.
- .3 Comply with applicable load regulations during hauling of materials and equipment over public highways, roads, or bridges. Minimize interference with local traffic.
- .4 Keep public highways and roads impacted by the Work open to traffic and passable at all times.
- .5 Retain qualified personnel or organizations specializing in such work to develop a Traffic Accommodation Strategy in accordance with Saskatchewan Highways and Transportation and the requirements of other road authorities having jurisdiction.
- .6 Supply, install, and maintain all necessary barricades, temporary signs, red lights, flashers, danger signals and signs, and all other precautions for the protection of the Work and the safety of the public.
- .7 In addition to the requirements of the road authority having jurisdiction, provide flagmen to control traffic at all locations where the Contractor's operations interfere with public highways, roads, and detours.
- .8 Promptly control dust and repair damage to public highways, roads, and bridges caused by Contract generated traffic in order to maintain public access and use.
- .9 Do not permit scrapers, rock trucks or tracked equipment to travel on existing bridges or asphalt paved roadways.
- .10 Do not block or impede access roads or driveways to local landowner residences located near the Site.

1.3 TEMPORARY ACCESS
AND HAUL ROADS AND
DETOURS

- .1 Design and construct all temporary roads required for construction operations.
- .2 Provide detours required for the execution of the Work.

- .3 Confine construction traffic to the limits of temporary roads and avoid disturbances to adjacent lands.
- .4 Contain hauled material in vehicles, and keep routes clear of mud, fallen rock, and debris resulting from construction operations.
- .5 Control dust, remove snow, and maintain road surfaces daily or at frequent intervals depending upon weather or traffic and as required by the Owner.
- .6 Reclaim all haul roads when they are no longer required. Scarify, grade to original contours, cultivate, replace topsoil, and seed to grass.

1.4 SUBMITTALS

- .1 Provide the following submittals:
- .2 The Traffic Accommodation Strategy at least 7 days prior to commencement of the Work at the Site.
- .3 Plans showing the location of temporary access and haul roads and detours, drainage structures, and bridges required for execution of the Work, at least 10 days prior to commencement of the Work at the Site.

PART 2 – PRODUCTS2.1 NOT USED

- .1 Not Used.

PART 3 – EXECUTION3.1 NOT USED

- .1 Not Used.

END OF SECTION

PART 1 – GENERAL1.1 RELATED
REQUIREMENTS

- .1 Not Used.

1.2 REFERENCES

- .1 Canadian Construction Documents Committee (CCDC)
.1 CCDC 4 – 2011, Unit Price Contract.
- .2 Within text of each specifications section, reference may be made to reference standards.
- .3 Conform to these reference standards in whole or in part as specifically requested in specifications.
- .4 If there is question as to whether products or systems are in conformance with applicable standards, Engineer reserves right to have such products or systems tested to prove or disprove conformance.
- .5 Cost for such testing will be borne by Owner in event of conformance with Contract Documents or by Contractor in event of non-conformance.

1.3 QUALITY

- .1 Refer to CCDC 4.
- .2 Products, materials, equipment and articles incorporated in Work shall be new, not damaged or defective, and of best quality for purpose intended. If requested, furnish evidence as to type, source, and quality of products provided.
- .3 Procurement policy is to acquire, in a cost-effective manner, items containing highest percentage of recycled and recovered materials practicable consistent with maintaining satisfactory levels of competition. Make reasonable efforts to use recycled and recovered materials and in otherwise utilizing recycled and recovered materials in execution of work.
- .4 Defective products, whenever identified prior to completion of Work, will be rejected regardless of previous inspections. Inspection does not relieve responsibility but is precaution against oversight or error. Remove and replace defective products at own expense and be responsible for delays and expenses caused by rejection.
- .5 Should disputes arise as to quality or fitness of products, decision rests strictly with Engineer based upon requirements of Contract Documents.
- .6 Unless otherwise indicated in specifications, maintain uniformity of manufacture for any particular or like item throughout building.
- .7 Permanent labels, trademarks and nameplates on products are not acceptable in prominent locations, except where required for operating instructions, or when located in mechanical or electrical rooms.

1.4 AVAILABILITY

- .1 Immediately upon signing Contract, review product delivery requirements and anticipate foreseeable supply delays for items. If delays in supply of products are foreseeable, notify Engineer of such in order that substitutions or other remedial action may be authorized in ample time to prevent delay in performance of Work.
- .2 In event of failure to notify Engineer at commencement of Work and should it subsequently appear that Work may be delayed for such reason, Engineer reserves right to substitute more readily available products of similar character, at no increase in Contract Price or Contract Time.

1.5 STORAGE, HANDLING AND PROTECTION

- .1 Handle and store products in manner to prevent damage, adulteration, deterioration and soiling and in accordance with manufacturer's instructions when applicable.
- .2 Store packaged or bundled products in original and undamaged condition with manufacturer's seal and labels intact. Do not remove from packaging or bundling until required in Work.
- .3 Store products subject to damage from weather in weatherproof enclosures.
- .4 Store cementitious products clear of earth or concrete floors, and away from walls.
- .5 Keep sand, when used for grout or mortar materials, clean and dry. Store sand on wooden platforms and cover with waterproof tarpaulins during inclement weather.
- .6 Store pipes, appurtenances, and fence materials on flat, solid supports and keep clear of ground. Slope to shed moisture.
- .7 Remove and replace damaged products at own expense and to satisfaction of Engineer.
- .8 Touch-up damaged factory finished surfaces to Engineer's satisfaction. Use touch-up materials to match original. Do not paint over name plates.

1.6 TRANSPORTATION

- .1 Pay costs of transportation of products required in performance of Work.

1.7 MANUFACTURER'S INSTRUCTIONS

- .1 Unless otherwise indicated in specifications, install or erect products in accordance with manufacturer's instructions. Do not rely on labels or enclosures provided with products. Obtain written instructions directly from manufacturers.
- .2 Notify Engineer in writing, of conflicts between specifications and manufacturer's instructions, so that Engineer will establish course of action.

- .3 Improper installation or erection of products, due to failure in complying with these requirements, authorizes Engineer to require removal and re-installation at no increase in Contract Price or Contract Time.

1.8 QUALITY OF WORK

- .1 Ensure Quality of Work is of highest standard, executed by workers experienced and skilled in respective duties for which they are employed. Immediately notify Engineer if required Work is such as to make it impractical to produce required results.
- .2 Do not employ anyone unskilled in their required duties. Engineer reserves right to require dismissal from site, workers deemed incompetent or careless.
- .3 Decisions as to standard or fitness of Quality of Work in cases of dispute rest solely with Engineer, whose decision is final.

1.9 CO-ORDINATION

- .1 Ensure co-operation of workers in laying out Work. Maintain efficient and continuous supervision.
- .2 Be responsible for coordination and placement of openings, sleeves and accessories.

1.10 REMEDIAL WORK

- .1 Refer to CCDC 4.
- .2 Perform remedial work required to repair or replace parts or portions of Work identified as defective or unacceptable. Co-ordinate adjacent affected Work as required.
- .3 Perform remedial work by specialists familiar with materials affected. Perform in a manner to neither damage nor put at risk any portion of Work.

1.11 FASTENINGS

- .1 Provide metal fastenings and accessories in same texture, colour and finish as adjacent materials, unless indicated otherwise.
- .2 Prevent electrolytic action between dissimilar metals and materials.
- .3 Use non-corrosive hot dip galvanized steel fasteners and anchors for securing exterior work, unless stainless steel or other material is specifically requested in affected specification Section.
- .4 Space anchors within individual load limit or shear capacity and ensure they provide positive permanent anchorage. Wood, or any other organic material plugs are not acceptable.
- .5 Keep exposed fastenings to a minimum, space evenly and install neatly.

- .6 Fastenings which cause spalling or cracking of material to which anchorage is made are not acceptable.

1.12 FASTENINGS - EQUIPMENT

- .1 Use fastenings of standard commercial sizes and patterns with material and finish suitable for service.
- .2 Use heavy hexagon heads, semi-finished unless otherwise specified. Use No. 304 stainless steel for exterior areas.
- .3 Bolts may not project more than one diameter beyond nuts.
- .4 Use plain type washers on equipment, sheet metal and soft gasket lock type washers where vibrations occur. Use resilient washers with stainless steel.

1.13 EXISTING UTILITIES

- .1 When breaking into or connecting to existing services or utilities, execute Work at times directed by local governing authorities, with minimum of disturbance to Work and others.
- .2 Protect, relocate, or maintain existing active services. When services are encountered, cap off in manner approved by authority having jurisdiction. Stake and record location of capped service.

PART 2 – PRODUCTS

2.1 NOT USED

- .1 Not Used.

PART 3 – EXECUTION

3.1 NOT USED

- .1 Not Used.

END OF SECTION

PART 1 – GENERAL1.1 FIELD ENGINEER ROLE & RESPONSIBILITIES

- .1 Engineer will provide within 15 days after Contract award and update as required during the Contract, a contact list showing names, position and telephone numbers for the Engineer's Site Management personnel.
- .2 Engineer will carry out site engineering duties as follows:
 - .1 Record, transcribe and distribute minutes of formal progress and other meetings held during the course of the Contract.
 - .2 Issue clarification of the Drawings and technical Specifications.
 - .3 Receive from Contractor, for review purposes, the following:
 - .4 Copy of proposed construction schedules and updates
 - .5 Payment submissions.
 - .6 Prepare Progress Payment submissions for Contractor.
 - .7 Carry out inspection of the Work at the Site and other locations as deemed necessary by the Engineer, and issue instructions to correct observed deficiencies.
 - .8 Receive Contractor submittals required with respect to the Work and deal with Contractor in matters arising from submittal review.
 - .9 With respect to contemplated changes in the Work, issue the necessary documentation, receive the related quotations and information and authorize changes in the Work.

1.2 CONTRACTOR SITE SUPERVISION

- .1 Provide site representative for superintendence of Work.
- .2 Site representative shall be authorized to attend meetings, submit construction schedules and cash flow forecasts, supervise layout of Work, advise on changes to the Work, prepare payment submissions and receive instruction from the Engineer.

1.3 SURVEY REFERENCE POINTS AND LEGAL SURVEY MARKERS

- .1 Existing base horizontal and vertical control points are designated on drawings.
- .2 Locate, confirm, and protect control points and legal survey markers prior to starting site work. Preserve permanent reference points during construction.
- .3 Make no changes or relocations without prior written approval from the Engineer.
- .4 Report to Engineer when a reference point or legal survey marker is lost, destroyed, or requires relocation because of necessary changes in grades or locations.
- .5 Employ a competent surveyor to replace control points in accordance with original survey control.
- .6 Require surveyor to replace legal survey markers lost or destroyed as a result of construction activities.
- .7 Maintain a complete, accurate log of control points and survey work as it progresses.

1.4 EXISTING SURVEY
MARKERS

.1

Replace legal survey markers, disturbed or removed by the construction operation. If it is necessary to remove or disturb existing legal survey markers that are within 1.5 m of the Work, notify Engineer before such removal or disturbance and replacement will be at Owner's expense.

1.5 SUBSURFACE
CONDITIONS

.1

Promptly notify Engineer in writing if subsurface conditions at Site differ materially from those indicated in Contract Documents, or a reasonable assumption of probable conditions based thereon.

.2

After prompt investigation, should Engineer determine that the conditions do differ materially, instructions will be issued for changes in Work as provided in CCDC 4.

PART 2 – PRODUCTS2.1 NOT USED

.1

Not used.

PART 3 – EXECUTION3.1 NOT USED

.1

Not used.

END OF SECTION

PART 1 – GENERAL1.1 RELATED
REQUIREMENTS

- .1 Canadian Construction Documents Committee (CCDC)
.1 CCDC 4 - 2011, Unit Price Contract

1.2 REFERENCES

- .1 Canadian Construction Documents Committee (CCDC)
.1 CCDC 4 - 2011, Unit Price Contract.

1.3 PROJECT
CLEANLINESS

- .1 Maintain Work in tidy condition, free from accumulation of waste products and debris.
- .2 Remove waste materials from site at daily regularly scheduled times or dispose of as directed by Engineer. Do not burn waste materials on site.
- .3 Clear snow and ice from access to Site, and from all work areas.
- .4 Make arrangements with and obtain permits from authorities having jurisdiction for disposal of waste and debris.
- .5 Provide on-site containers for collection of waste materials and debris.
- .6 Provide and use marked separate bins for recycling.
- .7 Dispose of waste materials and debris off site.
- .8 Store volatile waste in covered metal containers and remove from premises at end of each working day.
- .9 Use only cleaning materials recommended by manufacturer of surface to be cleaned, and as recommended by cleaning material manufacturer.

1.4 FINAL CLEANING

- .1 Refer to CCDC 4.
- .2 When Work is Substantially Performed remove surplus products, tools, construction machinery and equipment not required for performance of remaining Work.
- .3 Remove waste products and debris and leave Work clean and suitable for occupancy.
- .4 Prior to final review remove surplus products, tools, construction machinery and equipment.
- .5 Remove dirt and other disfiguration from exterior surfaces.
- .6 Clean roofs, downspouts, and drainage systems.

1.5 WASTE .1 Separate waste materials for reuse and recycling.

MANAGEMENT AND
DISPOSAL

PART 2 – PRODUCTS

2.1 NOT USED .1 Not Used.

PART 3 – EXECUTION

3.1 NOT USED .1 Not Used.

END OF SECTION

PART 1 – GENERAL1.1 RELATED
REQUIREMENTS

.1

Not Used.

1.2 REFERENCES

.1

Canadian Construction Documents Committee (CCDC)

.1 CCDC 4 - 2011, Unit Price Contract.

1.3 ADMINISTRATIVE
REQUIREMENTS

.2

Acceptance of Work Procedures:

- .1 Contractor's Inspection: Contractor: conduct inspection of Work, identify deficiencies and defects, and repair as required to conform to Contract Documents.
 - .1 Notify Engineer in writing of satisfactory completion of Contractor's inspection and submit verification that corrections have been made.
 - .2 Request Engineer's inspection.
- .2 Engineer's Inspection:
 - .1 Engineer and Contractor to inspect Work and identify defects and deficiencies.
 - .2 Contractor to correct Work as directed.
- .3 Completion Tasks: submit written certificates in English that tasks have been performed as follows:
 - .1 Work: completed and inspected for compliance with Contract Documents.
 - .2 Defects: corrected and deficiencies completed.
 - .3 Equipment and systems: tested, adjusted and fully operational.
- .4 Declaration of Substantial Performance: when Engineer considers deficiencies and defects corrected and requirements of Contract substantially performed, make application for Certificate of Substantial Performance.
- 5 Commencement of Lien and Warranty Periods: date of Owner's acceptance of submitted declaration of Substantial Performance to be date for commencement for warranty period and commencement of lien period unless required otherwise by lien statute of Place of Work.
- .6 Final Payment:
 - .1 When Engineer considers final deficiencies and defects corrected and requirements of Contract met, make application for final payment.
 - .2 Refer to CCDC 4: when Work deemed incomplete by Engineer, complete outstanding items and request re-inspection.
- .7 Payment of Holdback: after issuance of Certificate of Substantial Performance of Work, submit application for payment of holdback amount in accordance with contractual agreement.

1.4 FINAL CLEANING

.1

Clean in accordance with Section 01 74 11 – Cleaning.

- .1 Remove surplus materials, excess materials, rubbish, tools, and equipment.

PART 2 – PRODUCTS

2.1 NOT USED .1 Not Used.

PART 3 – EXECUTION

3.1 NOT USED .1 Not Used.

END OF SECTION

PART 1 – GENERAL1.1 SITE CONDITIONS

.1

Be aware that the project area is located in an area where strong winds and intense heat are prevalent.

PART 2 – PRODUCTS2.1 EQUIPMENT AND MATERIALS

.1

Provide all pumps, hoses, and related equipment and power sources required for care of water.

.2

Maintain pumps in good operating condition at all times. Have at the Site at all times at least one standby pump for each category of pump required for care of water.

.3

Install a replacement pump or pumps of equal capacity before removing a pump or pumps for maintenance.

PART 3 – EXECUTION3.1 GENERAL

.1

Design, construct and maintain Temporary Work, construct related Permanent Work, as required for care of water, including all necessary cofferdams, channels, flumes, drains, sandpoints, wells and sumps and other temporary diversion and protective works and furnish all materials required therefor. Furnish, install, maintain and operate all necessary pumping and other equipment, for dewatering the various parts of the work and for maintaining the foundation and other parts of the work free of water, ice and snow from whatever source.

.2

Maintain all sumps, trenches, and discharge lines to ensure proper containment and free flow of water to and from the pumps and other diversion and protective works at all times.

.3

Obtain any permits required.

.4

Ensure that care of water procedures do not interfere with the operation of the landfill.

.5

Repair damage to any part of the work caused by water or failure of protective works at no extra cost to the Owner.

.6

Be responsible for additional excavation and subsequent backfill made necessary by water, snow, or ice.

.7

Ensure procedures for "Care of Water" do not cause pollution in the area. Locate and control discharges of water to avoid causing damage to property, pollution of water courses, nuisance on roads, or injury to the public or wildlife.

- .8 Make provisions for handling residual water, storm runoff and snowmelt that may enter the landfill or excavations from time to time.
- .9 Make arrangements with landowners and agencies that may be affected by disposal of water, snow, and ice.
- .10 Remove and dispose of all water, snow and ice from the landfill work areas.

3.2 CONSTRUCTION ACCESS CROSSING

- .1 Provide construction access crossings.
- .2 Design crossings to accommodate the drainage of runoff water during the non-irrigation season.
- .3 Design crossings to accommodate the full canal flow without increasing the backwater in the canal if the crossing is to be used during the irrigation season.
- .4 Design crossings for the maximum load of the construction equipment to be used.
- .5 Do not use existing on Site, public and private, bridges and culvert crossings for construction equipment.

END OF SECTION

PART 1 – GENERAL1.1 RELATED
REQUIREMENTS

- .1 Section 01 33 00 - Submittal Procedures.
- .2 Section 01 35 29.06 - Health and Safety Requirements.
- .3 Section 01 74 11 - Cleaning.

1.2 MEASUREMENT
FOR PAYMENT

- .1 All work described in this section is considered incidental to work described elsewhere and is deemed included in the prices provided by the Contractor in the Unit Price Table. Therefore no separate payment to be made for work included in this section.

1.3 REFERENCES

- .1 U.S. Environmental Protection Agency (EPA)/Office of Water
 - .1 EPA 832R92005, Storm Water Management for Construction Activities: Developing Pollution Prevention Plans and Best Management Practices.

1.4 DEFINITIONS

- .1 Clearing consists of cutting off trees and brush vegetative growth to not more than specified height above ground and disposing of felled trees, previously uprooted trees and stumps, and surface debris.
- .2 Close-cut clearing consists of cutting off standing trees, brush, scrub, roots, stumps and embedded logs, removing at, or close to, existing grade and disposing of fallen timber and surface debris.
- .3 Clearing isolated trees consists of cutting off to not more than specified height above ground of designated trees, and disposing of felled trees and debris.
- .4 Underbrush clearing consists of removal from treed areas of undergrowth, deadwood, and trees smaller than 50 mm trunk diameter and disposing of fallen timber and surface debris.
- .5 Grubbing consists of excavation and disposal of stumps and roots [boulders and rock fragments of specified size] to not less than specified depth below existing ground surface.

1.5 ACTION AND
INFORMATIONAL
SUBMITTALS

- .1 Provide submittals in accordance with Section 01 33 00 - Submittal Procedures.
- .2 Samples:
 - .1 Tree wound paint: one liter can with manufacturer's label.
 - .2 Herbicide: one liter can with manufacturer's label.

	.3	Submit certificates signed by manufacturer certifying that materials comply with specified performance characteristics and physical properties.
	.4	Submit manufacturer's installation instructions.
<u>1.6 QUALITY ASSURANCE</u>	.1	Do construction occupational health and safety in accordance with Section 01 35 29.06 - Health and Safety Requirements.
	.2	Safety Requirements: worker protection.
	.1	Workers must wear gloves, respirators, long sleeved clothing, eye protection, and protective clothing when applying herbicide materials.
	.2	Workers must not eat, drink or smoke while applying herbicide material.
	.3	Clean up spills of preservative materials immediately with absorbent material and safely discard to landfill.
<u>1.7 STORAGE AND PROTECTION</u>	.1	Prevent damage to fencing, trees, landscaping, natural features, bench marks, existing buildings, existing pavement, utility lines, site appurtenances, water courses, root systems of trees which are to remain.
	.1	Repair damaged items to approval of Engineer.
	.2	Replace trees designated to remain, if damaged, as directed by Engineer.
<u>1.8 WASTE MANAGEMENT AND DISPOSAL</u>	.1	Separate waste materials for reuse and recycling as directed by Engineer.
<u>PART 2 – PRODUCTS</u>		
<u>2.1 MATERIALS</u>	.1	Bituminous based paint of standard manufacture specially formulated for tree wounds.
	.2	Herbicide: effective for killing annual and perennial weeds, and bamboo grass, by being absorbed through roots and foliage.
	.1	Spray applied on non-crop land areas.
	.3	Soil Material for Fill:
	.1	Excavated soil material: free of debris, roots, wood, scrap material, vegetable matter, refuse, soft unsound particles, deleterious, or objectionable materials.
	.2	Remove and store soil material for reused.
<u>PART 3 – EXECUTION</u>		

3.1 TEMPORARY EROSION
AND SEDIMENTATION
CONTROL

- .1 Provide temporary erosion and sedimentation control measures to prevent soil erosion and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways, according to requirements of authorities having jurisdiction.
- .2 Inspect, repair, and maintain erosion and sedimentation control measures during construction until permanent vegetation has been established.
- .3 Remove erosion and sedimentation controls and restore and stabilize areas disturbed during removal.

3.2 PREPARATION

- .1 Inspect site and verify with Engineer, items designated to remain.
- .2 Locate and protect utility lines: preserve in operating condition active utilities traversing site.
 - .1 Notify Engineer immediately of damage to or when unknown existing utility lines are encountered.
 - .2 When utility lines which are to be removed are encountered within area of operations, notify Engineer in ample time to minimize interruption of service.
- .3 Notify utility authorities before starting clearing and grubbing.
- .4 Keep roads and walks free of dirt and debris.

3.3 APPLICATION

- .1 Manufacturer's instructions: comply with manufacturer's written recommendations or specifications, including product technical bulletins, handling, storage and installation instructions, and datasheet.

3.4 CLEARING

- .1 Clearing includes felling, trimming, and cutting of trees into sections and satisfactory disposal of trees and other vegetation designated for removal, including downed timber, and rubbish occurring within cleared areas.
- .2 Clear as directed by Engineer, by cutting at height of not more than 300 mm above ground. In areas to be subsequently grubbed, height of stumps left from clearing operations to be not more than 1000 mm above ground surface.
- .3 Cut off branches and cut down trees overhanging area cleared as directed by Engineer.
- .4 Cut off unsound branches on trees designated to remain as directed by Engineer.
- .5 Apply herbicide in accordance with manufacturer's label to top surface of stumps designated not to be removed.

3.5 CLOSE CUT CLEARING

- .1 Close cut clearing to within 100 mm of ground surface.
- .2 Cut off branches down trees overhanging area cleared as directed by the Engineer.
- .3 Cut off unsound branches on trees designated to remain as directed by Engineer.

3.6 ISOLATED TREES

- .1 Cut off isolated trees as directed by Engineer at height of not more than 300 mm above ground surface.
- .2 Grub out isolated tree stumps.
- .3 Prune individual trees as indicated.
- .4 Trim trees designated to be left standing within cleared areas of dead branches [4] cm or more in diameter; and trim branches to heights as indicated.
- .5 Cut limbs and branches to be trimmed close to bole of tree or main branches.
- .6 Paint cuts more than 3 cm in diameter with approved tree wound paint.

3.7 UNDERBRUSH
CLEARING

- .1 Clear underbrush from areas as indicated.

3.8 GRUBBING

- .1 Remove and dispose of roots larger than 7.5 cm in diameter, matted roots, and designated stumps from indicated grubbing areas.
- .2 Grub out stumps and roots to not less than 200 mm below ground surface.
- .3 Grub out visible rock fragments and boulders, greater than 300 mm in greatest dimension, but less than 0.25 m³.
- .4 Fill depressions made by grubbing with suitable material and to make new surface conform with existing adjacent surface of ground.

3.9 REMOVAL AND
DISPOSAL

- .1 Remove cleared and grubbed materials to disposal area as indicated by Engineer.
- .2 Cut timber greater than 125 mm diameter to 300 mm lengths and stockpile as indicated. Stockpiled timber becomes property of Owner.
- .3 Burning of cleared and grubbed material is not allowed.
- .4 Bury to approval of Engineer by:
 - .1 Consolidating.

- .2 Covering with minimum 500 mm of mineral soil.
- .3 Finishing surface.
- .5 Chip or mulch and stockpile spread cleared and grubbed vegetative material on site as directed by Engineer.
- .6 Remove diseased trees identified by Engineer and dispose of this material to approval of Engineer.

3.10 FINISHED SURFACE

- .1 Leave ground surface in condition suitable for stripping of topsoil to approval of Engineer.

3.11 CLEANING

- .1 Proceed in accordance with Section 01 74 11 - Cleaning.
- .2 On completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.

END OF SECTION

PART 1 – GENERAL1.1 RELATED
REQUIREMENTS

.1 Section 01 74 11 – Cleaning.

1.2 REFERENCES.1 U.S. Environmental Protection Agency (EPA)/Office of Water
.1 EPA 832R92005, Storm Water Management for Construction
Activities: Developing Pollution Prevention Plans and Best
Management Practices.1.3 MEASUREMENT FOR
PAYMENT.1 All work described in this section is considered incidental to work described
elsewhere and is deemed included in the prices provided by the Contractor in
the Unit Price Table. Therefore, no separate payment to be made for work
included in this section.PART 2 – PRODUCTS2.1 NOT USED

.1 Not Used.

PART 3 – EXECUTION3.1 TEMPORARY EROSION
AND SEDIMENTATION
CONTROL.1 Provide temporary erosion and sedimentation control measures to prevent
soil erosion and discharge of soil-bearing water runoff or airborne dust to
adjacent properties and walkways, according to requirements of authorities
having jurisdiction.
.2 Inspect, repair, and maintain erosion and sedimentation control measures
during construction until permanent vegetation has been established.
.3 Remove erosion and sedimentation controls and restore and stabilize areas
disturbed during removal.3.2 STRIPPING OF
TOPSOIL.1 Ensure that procedures are conducted in accordance with applicable
Provincial and Municipal requirements.
.2 Remove topsoil before construction procedures commence to avoid
compaction of topsoil.
.3 Handle topsoil only when it is dry and warm.
.4 Remove vegetation from targeted areas by non-chemical means and dispose
of stripped vegetation by composting.
.5 Remove brush from targeted area by non-chemical means and dispose of
mulching.

- .6 Strip topsoil to depths as directed by Engineer.
- .7 Avoid mixing topsoil with subsoil.
- .8 Pile topsoil in berms in locations as directed by Engineer.
- .9 Stockpile height not to exceed 3 m.
- .10 Dispose of unused topsoil in location as indicated by Engineer.
- .11 Protect stockpiles from contamination and compaction.
- .12 Cover topsoil that has been piled for long term storage, with trefoil or grass to maintain agricultural potential of soil.

3.3 STOCKPILES

- .1 Unless otherwise designated in the Contract Documents, stockpile stripped material adjacent to borrow areas, waste areas or along the road right of way. Choose stockpile locations such that they will not interfere with construction.
- .2 Stockpile topsoil separately from other materials.
- .3 Maintain a minimum separation of 1 m between stockpiles.
- .4 Stockpile frozen material stripped from borrow areas separately from other materials.
- .5 Adopt measures to prevent drifting of topsoil.
- .6 Keep drainage courses clear of stockpiled material.
- .7 Stockpile material at slopes lower than 2H: 1 V.

3.4 PREPARATION OF
GRADE

- .1 Verify that grades are correct and notify Engineer if discrepancies occur, do not begin work until instructed by Engineer.
 - .1 Grade area only when soil is dry to lessen soil compaction.
 - .2 Grade soil establishing natural contours and eliminating uneven areas and low spots, ensuring positive drainage.

3.5 PLACING OF
TOPSOIL

- .1 Place topsoil only after Engineer has accepted subgrade.
- .2 Excavate, load and haul topsoil from stockpiles and place in waste areas, drainage ditches and road embankments.
- .3 Spread topsoil during dry conditions in uniform layers not exceeding 150 mm, over unfrozen subgrade free of standing water.

- .4 Distribute material to uniform thickness over the entire area. Disc material and remove debris, roots, branches, foreign material, undesirable plants, stones in excess of 50 mm diameter, contaminated soil and other deleterious materials.
- .5 Manually spread Topsoil around structures, fences, or other obstructions.
- .6 Grade to ensure positive drainage on slopes and away from structures.
- .7 Use water trucks and sprinklers as necessary to control all airborne dust caused by topsoil placement and grading operations when necessary.
- .8 Clean up, immediately, any soil or debris spilled onto roadways or driveways.
- .9 Leave surface smooth, uniform and compact to 90% Standard Proctor Density to prevent settlement when watered. Obtain minimum depth of topsoil after compaction of 200 mm.
- .10 Establish traffic patterns for equipment to prevent driving on topsoil after it has been spread to avoid compaction.
- .11 Cultivate soil following spreading procedures.

3.6 SUB-SOILING

- .1 Not Used.

3.7 CLEANING

- .1 Proceed in accordance with Section 01 74 11 – Cleaning.
- .2 On completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools, and equipment.

END OF SECTION

PART 1 – GENERAL1.1 INTENT

- .1 Read this section in conjunction with other sections for location of excavation specified herein.

1.2 DETAILED DRAWINGS

- .1 Not Used.

1.3 DEFINITIONS

- .1 "Common Excavation" is defined as all excavation within the project work area.
- .2 "Borrow Excavation" is defined as all imported excavation from designated borrow areas excluding stripping and excavation of frozen material.
- .3 "Waste Excavation" is defined as all exported excavation from the project area to the designated waste areas that is not required for the completion of the project work excluding stripping.

PART 2 – PRODUCTS

- .1 Not used.

PART 3 – EXECUTION3.1 PREPARATION

- .1 Notify Owners Representative at least 2 days prior to beginning excavating operations.
- .2 The pit location for the clay liner material has been identified and is located at the Emma Lake transfer station (53.560119, -105.887333).
- .3 A pit location for subgrade fill material has been identified and is located at the Emma Lake transfer station (53.560119, -105.887333).
- .4 A location for topsoil has no been identified.
- .5 Prior to commencing excavation:
- .1 Contact all appropriate utility companies and establish exact location and current status of all utilities, voltage of underground and overhead power lines and pressure of natural gas lines.

- .2 Notify Owner if any utility lines have been omitted from or incorrectly indicated in the Contract Documents.

3.2 PROTECTION OF EXISTING FACILITIES

- .1 Locate utility lines, fencing, survey reference points, instrumentation, culverts, and all other existing facilities before commencement of Work. Protect these items from damage.

3.3 UNAUTHORIZED EXCAVATION

- .1 Unauthorized excavation is any excavation beyond lines, elevations and dimensions indicated in specifications and in the Contract Documents without specific authorization by the Owner.
- .2 Fill unauthorized excavation to lines, elevations and dimensions indicated, as directed by the Owner.
- .3 Unauthorized excavation and remedial work will be at Contractor's expense.

3.4 EXCAVATION LINES

- .1 Excavate to the lines and grades indicated in the Contract Documents or as determined by the Owner.

3.5 SHORING AND BRACING

- .1 If required to provide safe working conditions and to prevent cave-ins and loose soil from falling into excavations, protect excavations by temporary shoring, bracing, or other suitable methods.
- .2 Where the excavation is made to accommodate structures, sufficient material shall be removed to allow for the proper placing and bracing of forms.
- .3 No extra payment will be made for supplying, placing, maintaining and removing sheeting, bracing, shoring, or other means of temporary support.

3.6 EXCAVATION

- .1 Strip Topsoil (and Subsoil where required) in accordance with Section 31 14 13 – Soil Stripping and Stockpiling and stockpile in the designated area.

- .2 Dispose of unsuitable organic soils and other unsuitable, native or uncontaminated material in the waste area designated by the Owner.
- .3 Remove and dispose of all water, snow and surface ice prior to excavation.
- .4 Schedule and coordinate the work such that excavations are trimmed to grade prior to becoming frozen.
- .5 Excavate to the required lines, grades and elevations.
- .6 Prevent loss of soil and sloughing of slopes if springs or seepage are encountered within excavation.
- .7 Remove boulders, loose bedrock, soil blocks and other fragments that may slide or roll into excavated areas, which, in the opinion of the Owner or the Contractor, are unsafe or appear to endanger persons, work or property. The fact that such removal may enlarge an excavation beyond the required excavation lines shall not relieve the Contractor from the necessity of doing such scaling and removal.
- .8 All excavation within roadways shall be performed by a hydraulic tracked excavator. Earthmovers (buggies) shall not be used.

3.7 COBBLES AND BOULDERS

- .1 The Contractor is advised that cobbles and boulders too large to be left in fill materials may be encountered in materials excavated from all areas of the site including Borrow Areas. These cobbles and boulders must be removed from the fill prior to compaction. In some cases, the cobbles and boulders can be too large to be reasonably moved by hand and must be removed by machinery. When cobbles and boulders are removed by machinery, reasonable care, satisfactory to the Owner, must be taken to limit the quantity of suitable fill removed with the cobble or boulder.
- .2 The Contractor is encouraged to make appropriate use of cobbles and boulders materials where suitable and acceptable to the Owner. Stockpile excess cobbles and boulders at locations within the Site limits designated by the Owner.
- .3 No separate payment will be made for removal, handling, transporting and/or disposing of cobbles and boulders.

3.8 DISPOSAL OF EXCAVATED
MATERIAL

.1 General

- .1 Obtain prior approval by Owner for stockpile areas. Strip topsoil from stockpile areas except do not strip topsoil stockpile areas.
- .2 If stockpiling is required, stockpile materials meeting the classifications of different zones in separate stockpiles.
- .3 Prepare stockpile sites and construct stockpiles taking every precaution necessary to prevent segregation of particle sizes and contamination with other materials.
- .4 Finish the surfaces in stockpiles to safe, stable lines and slopes 3H:1V or flatter or as directed by the Owner and leave the surfaces in a neat and workmanlike manner.
- .5 Maintain stockpiles in a condition acceptable to Owner.
- .6 Do not block drainage courses with stockpiled material.
- .7 Space all stockpiles at least three metres from adjacent material stockpiles with a different classification.
- .8 Remove all stockpiled materials from stockpiles and incorporate into the Work of the Contract.

.2 Suitable Materials

- .1 See Section 31 22 50 – Compacted Earth Fill for definitions of suitable materials.
- .2 Load, haul and place, suitable materials from common and borrow excavations where placement of compacted and tamped fills are designated.
- .3 Spread and compact materials as specified in Section 31 22 50 – Compacted Earth Fill.

.3 Unsuitable Materials

- .1 See Sections 31 22 50 – Compacted Earth Fill for definitions of unsuitable materials.

- .2 Load, haul and place unsuitable materials from excavations in waste fills and designate waste areas.
- .3 Load, haul and place unsuitable materials from borrow excavations in borrow areas, after the removal of all suitable materials.
- .4 Spread and compact as specified in Section 31 22 50 – Compacted Earth Fill.

3.9 TOLERANCE

- .1 Excavate all surfaces to within ± 20 mm of the lines, grades and elevations shown in the Contract Documents or as directed by engineer.

END OF SECTION

PART 1 – GENERAL1.1 RELATED
REQUIREMENTS

- .1 Section 01 33 00 – Submittal Procedures.
- .2 Section 31 23 33.01 – Excavating, Trenching and Backfilling.
- .3 Section 01 45 00 – Quality Control
- .4 Section 01 74 11 – Cleaning.

1.2 REFERENCES

- .1 ASTM International
 - .1 ASTM D 698-[07e1], Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort (600 kN-m/m;).
- .2 Canada Green Building Council (CaGBC)
 - .1 LEED Canada-NC Version 1.0-[2004], LEED (Leadership in Energy and Environmental Design): Green Building Rating System for New Construction and Major Renovations (including Addendum [2007]).
 - .2 LEED Canada-NC-[2009], LEED (Leadership in Energy and Environmental Design): Green Building Rating System for New Construction and Major Renovations 2009.
 - .3 LEED Canada-CI Version 1.0-[2007], LEED (Leadership in Energy and Environmental Design): Green Building Rating System for Commercial Interiors.
 - .4 LEED Canada-EB: O&M-[2009], LEED (Leadership in Energy and Environmental Design): Green Building Rating System for Existing Buildings: Operations and Maintenance 2009.
- .3 Underwriters' Laboratories of Canada (ULC)

1.3 ACTION AND
INFORMATIONAL
SUBMITTALS

- .1 Submit in accordance with Section 01 33 00 - Submittal Procedures.

1.4 EXISTING
CONDITIONS

- .2 Known underground and surface utility lines and buried objects are as indicated on site plan.
- .3 Refer to dewatering in Section 31 23 33.01 – Excavating, Trenching and Backfilling.

1.5 PROTECTION

- .1 Protect and/or transplant existing fencing, trees, landscaping, natural features, bench marks, buildings, pavement, surface or underground utility lines which are to remain as directed by Engineer. If damaged, restore to original or better condition unless directed otherwise.
- .2 Maintain access roads to prevent accumulation of construction related debris on roads.

PART 2 – PRODUCTS2.1 MATERIALS

- .1 Fill material: Type in accordance with of Section 31 23 33.01 – Excavating, Trenching and Backfilling.
- .2 Excavated or graded material existing on site suitable to use as fill for grading work if approved by Engineer.

PART 3 – EXECUTION3.1 STRIPPING OF TOPSOIL

- .1 Do not handle topsoil while in wet or frozen condition or in any manner in which soil structure is adversely affected as determined by Engineer.
- .2 Commence topsoil stripping of areas as directed by Engineer after area has been cleared of brush, weeds and grasses and removed from site.
- .3 Strip topsoil to depths as directed by Engineer. Avoid mixing topsoil with subsoil.
- .4 Stockpile in locations as directed by Engineer. Stockpile height not to exceed 2 m.
- .5 Dispose of unused topsoil as directed by Engineer.

3.2 GRADING

- .1 Rough grade to levels, profiles, and contours allowing for surface treatment as indicated.
- .2 Slope rough grade away from buildings as directed (offers more choice).
- .3 Grade ditches to depth as directed.
- .4 Prior to placing fill over existing ground, scarify surface to depth of 150 mm minimum before placing fill over existing ground. Maintain fill and existing surface at approximately same moisture content to facilitate bonding.
- .5 Compact filled and disturbed areas to maximum dry density to ASTM D 698, as follows:
 - .1 [85]% under landscaped areas.
 - .2 [95]% under paved and walk areas.
- .6 Do not disturb soil within branch spread of trees or shrubs to remain.

3.3 TESTING

- .1 Inspection and testing of soil compaction will be carried out by testing laboratory designated by Engineer. Costs of tests will be paid by Owner. Refer to Section 01 45 00 – Quality Control.
- .2 Submit testing procedure, frequency of tests to Engineer for review.

3.4 SURPLUS MATERIAL.....1

Remove surplus material and material unsuitable for fill, grading or landscaping as directed by Engineer.

3.5 CLEANING.....1

Progress Cleaning: clean in accordance with Section 01 74 11 – Cleaning.

.1 Leave Work area clean at end of each day.

.2 Final Cleaning: upon completion remove surplus materials, rubbish, tools, and equipment in accordance with Section 01 74 11 – Cleaning.

.3 Waste Management: separate waste materials for reuse and recycling when appropriate.

.1 Remove recycling containers and bins from site and dispose of materials at appropriate facility.

END OF SECTION

PART 1 – GENERAL1.1 INTENT

- .1 Read this section in conjunction with other sections for location, use, and placement of compacted earth fill specified herein.

1.2 DETAILED DRAWINGS

- .1 Not Used.

1.3 TYPES OF FILL

- .1 Compacted Clay.
- .2 Subsoil.

1.4 DEFINITIONS

- .1 "Suitable Material" is defined as material obtained from common or borrow excavations, free of organic or frozen materials, that is suitable for compacted landfill cover material.
- .2 "Unsuitable Material" is defined as organic or frozen material from common or borrow excavations that is not suitable for compacted cover material.
- .3 "Compacted Fill" or "Tamped Fill" is defined as suitable material obtained from common or borrow excavations, free of organic, wet, or frozen materials, and placed on site, road, or cover material.
- .4 "Waste Fill" is defined as organic or frozen material from common or borrow excavation that is not suitable for site or landfill cover.
- .5 "Subsoil" is defined as material that lies immediately beneath the Topsoil and extending to root depth. Subsoil may be up to 1.5 m in depth. Subsoil will consist of native material at the site.

PART 2 – PRODUCTS2.1 FILL MATERIALS

- .1 Compacted and tamped fill material is fine grained material having a minimum of 50% passing the 0.075 mm sieve size and classified as a low to medium plastic clay based on the unified classification system as modified by PFRA.
- .2 Remove tree roots, sod, or other organic material from borrow excavation.
- .3 Do not use frozen material in the fill.

- .4 Remove cobbles and rock fragments having maximum dimensions greater than 75 mm.

PART 3 – EXECUTION

3.1 GENERAL

- .1 Drain, clean, and maintain fill foundations free from debris, snow, ice, water, frozen ground, topsoil, or any loose objectionable material. Do not proceed with fill placement until the Owner has inspected and approved foundation areas designated for fill placement.
- .2 Scarify the foundation to obtain a suitable bond with the earthfill immediately prior to placing the first layer of earthfill.
- .3 Construct earthfills to the lines, grades and elevations shown in the Contract Documents.
- .4 Suspend all earthwork operations at any time when satisfactory work cannot be conducted on account of rain, floods, cold weather, or other unsatisfactory conditions.

3.2 DENSITY CONTROL

- .1 Compact all fill material, except waste fill, to a dry density equal to or greater than 95% of the maximum dry density obtained in the Standard Proctor Compaction Test performed in accordance with ASTM D698.
- .2 Tamp fill material to a minimum 95% of the maximum dry density obtained in the Standard Proctor Compaction Test performed in accordance with ASTM D698.

3.3 MOISTURE CONTROL

- .1 Maintain moisture content for compacted fill materials within $\pm 2\%$ of optimum moisture content as determined by ASTM D698 test procedures.
- .2 Maintain moisture content for tamped fill materials within $\pm 2\%$ of optimum moisture content as determined by ASTM D698 test procedures.
- .3 When the moisture content in the fill material is lower than that specified for placement, water shall be added and mixed with the material to achieve uniform moisture content in the material to conform to the requirements.
- .4 When the moisture content in the fill material is higher than that specified for placement, the material shall be dried by scarifying, disking, and harrowing to achieve uniform moisture content in the material that conforms to the requirements.

3.4 PLACEMENT AND
COMPACTION

- .1 Drain and clean all earth foundations of loose, thawed, frozen, soft, or other deleterious material including ice, snow, and organic materials and Topsoil.
- .2 Work the surface to obtain a suitable bond with the earth fill immediately prior to placing the first layer.
- .3 When the surface of the prepared foundations or the compacted fill material is too dry or too smooth to bond properly with the layer of fill material to be placed thereon, moisten the surface and work with a disc, scarifier, or other equipment, to provide a satisfactory bonding surface before the succeeding layer of fill material is placed.
- .4 When the surface of the prepared foundations or the compacted fill material is too wet for proper compaction, remove it and allow it to dry, or work it with a harrow, disc, or other equipment to reduce the moisture content to the required amount; then compact the fill material before the succeeding layer of fill material is placed thereon.
- .5 Maintain slopes at less than 3H:1V for earth foundations on which fill is to be placed.
- .6 Place compacted fill material in continuous horizontal layers. Spread, blend, smooth, and compact each lift to provide a homogeneous fill without stratification. Commence placement of fill at the lowest elevation of foundation. Use sheepsfoot type compaction equipment.
- .7 For the subsoil layer, place subsoil material in continuous horizontal layers not exceeding 150 mm when compacted. Commence placement of subsoil at the lowest elevation. Use sheepsfoot type compaction equipment.
- .8 Join new fill to existing slopes by terracing or excavating into slopes to remove all dried and loose material.
- .9 Schedule fill placement operations such that the foundation areas or previously compacted earthfill does not freeze and that compacted earthfill is not placed on frozen subgrade. Remove and replace any such frozen layers of compacted earthfill at no cost to the Owner.
- .10 Reroute construction traffic or increase fill thickness over soft foundations in areas where fill surface starts rutting. If rutting has occurred, scarify, regrade, and moisture condition the fill surface prior to placement of overlying fill.
- .11 Re-compact or remove any portion of the fill which has suffered a reduction in density due to frost, rain or any other reason before placing succeeding layers. Protect compacted fill material and foundations prepared for the fill from freezing.

- .12 Remove any non-conforming materials, which accumulate on the surface of any layer or prepared foundation before any material is placed for the succeeding layer.

3.5 COMPACTION EQUIPMENT

- .1 Supply necessary compaction equipment capable of meeting the specified compaction requirements.
- .2 Hauling equipment is not acceptable for compaction.
- .3 The Owner's Representative reserves the right to order the discontinuation of any compaction equipment that does not produce the specified compaction requirements or causes excessive breakage around structures.

3.6 TOLERANCES

- .1 Make changes in grade to blend slopes into naturally level areas.
- .2 Compact all surfaces to within ± 25 mm from the lines, grades, and elevations shown in the Contract Documents.

END OF SECTION

PART 1 – GENERAL**1.1 DESCRIPTION**

- .1 Read this Section in conjunction with other sections for testing requirements for Earthwork and Granular Material Testing specified herein.
- .2 Read this Section in conjunction with requirements for testing specified in CCDC 4.

**1.2 DETAILED
DRAWINGS**

- .1 Not Used.

1.3 TESTING

- .1 Contractor is responsible for performance testing in performance of the Work.
- .2 The Owner's representative will perform quality assurance testing and related functions.
- .3 The Owner's representative will perform quality assurance testing according to the testing standards listed in Reference Documents as selected by the Owner.
- .4 Provide samples requested by Owner's representative for testing.

PART 2 – PRODUCTS**2.1 NOT USED**

- .1 Not Used.

PART 3 – EXECUTION**3.1 FILL MATERIAL TESTING**

- .1 Fill materials may be tested, before and after placement, for conformance with specified requirements and to confirm suitability for intended uses.
- .2 Acceptance of fill material will be made only after the material has been dumped, spread, and compacted in place. Owner may reject fill material in the borrow areas, in the stockpiles, in the transporting vehicle or in place. Cooperate with the Owner to ensure only acceptance fill material will be placed in the Work.

**3.2 COMPACTION AND
MOISTURE CONTENT
TESTING**

- .1 Compaction and moisture content testing will be performed during fill material placement operations to ensure that specified requirements are met.
- .2 The frequency of compaction and moisture content testing will be determined by the Owner.

END OF SECTION

PART1 – GENERAL1.1 DESCRIPTION

.1

This Section specifies requirement for excavating trenches and backfilling for installation of appurtenances, or excavation for fill material.

1.2 RELATED REQUIREMENTS

.1

Section 01 35 29:06 - Health and Safety Requirements.

1.3 DEFINITIONS

.1

Common excavation is defined as the excavation of all materials other than rock, and shall include over-burden over rock, hard pan, quicksand and frozen earth and boulders up to a size of 1.0 cubic metres.

.2

“Borrow Excavation” is defined as all imported excavation from designated borrow areas excluding stripping and excavation of frozen material.

.3

Boulder excavation is defined as boulders, pieces of concrete or masonry excluding previously blasted rock in excess of 1.0 cubic metres which can be removed with a power operated excavator.

1.4 SAFETY REQUIREMENTS

.1

Adhere to municipal and provincial requirements relating to safety of trenching work.

.2

Adhere to municipal, provincial and national codes when blasting is required.

.3

Traffic accommodation will be the responsibility of the contractor during construction. The contractor shall submit, for approval by the Engineer, a traffic management plan prior to starting any work on site.

1.5 PROTECTION

.1

Existing Buried Utilities:

.1

Prior to commencing any excavation work, notify applicable utility authorities, establish location and state of use of buried services. Clearly mark such locations to prevent disturbance during work.

.2

Maintain and protect from damage, water, sewer, electric and other utilities encountered.

.3

Obtain direction of owner of utility and Engineer before moving or otherwise disturbing utility.

.2

Existing Surface Features:

.1

Protect existing buildings, culverts, trees and other plants, lawns, fencing, service poles, wires located within right-of-way or adjoining properties from damage while work is in progress and repair damage.

- .3 Shoring and Bracing:
- .1 Whenever shoring, sheeting, timbering and bracing of excavations is required engage services of a professional engineer to design and assume responsibility for adequacy of shoring and bracing. Professional engineer to be registered in province or territory in which work is to be carried out.
 - .2 When requested by Engineer, submit for review drawings and calculations signed and stamped by professional engineer responsible for their preparation.
 - .3 Close sheeting, when required, to be designed and constructed to prevent adjacent soil or water from entering excavation.
 - .4 Maintain unobstructed access to fire and police appurtenances, telephone, electric, water, sewer, gas or other public utilities and private properties.
 - .5 Protect open excavation against flooding and damage from surface water run-off.

1.6 SITE CONDITIONS

- .1 The Tenderer may examine the site of the Work before submitting his Tender, either personally or through a representative and satisfy himself as to the nature and location of the Work, local conditions, soils structure and topography at the site of the Work, the nature and quality of the materials to be used, the equipment and facilities needed preliminary to, and during, the prosecution of the Work, the means of access to the site, on-site accommodation, all necessary information as to risks, contingencies and circumstances as may affect his Tender, and all other matters which can, in any way, affect the Work under the Contract. The Tenderer is fully responsible for obtaining all information required for the preparation of his Tender and for the execution of the Work.
- .2 The Tenderer is not entitled to rely on any data or information included in the Tender Documents as to site or sub-surface conditions or test results indicating the suitability or quantity or otherwise off-site or subsurface materials for backfilling or other uses in carrying out the construction of the Work. If the Tenderer requires additional time to conduct his own investigations or is of the opinion either that the site or subsurface conditions or that site or subsurface materials differ materially from that indicated by data or information included in the Tender Documents, he shall promptly request such additional time or notify the Engineer in writing of this opinion before the time of Tender submission. The Engineer will either request the Owner to extend the time for submission of Tenders or enable Tenderers to carry out further investigation or issue an addendum modifying the Tender Documents or both as the circumstances may permit.

1.7 MEASUREMENT AND
PAYMENT

- .1 Work performed to this section will be in conjunction with work involved in other sections with the exception of the following:
- .1 Common Excavation: Payment for common excavation will be included in the unit price tendered per cubic metre of material. The cost shall include excavation, hauling, stockpiling, dewatering,

backfilling, placing and compaction of bedding material, disposal of excess excavation material, re-gravelling of roadways and driveways disturbed by construction, disposal of all rocks not allowed as backfill and replacement with suitable backfill, and all other work required for which separate payment is not indicated in the tender form.

PART 2 – PRODUCTS

2.1 MATERIALS

- .2 Common Backfill:
 - .1 Approved material selected from trench excavation or other source, unfrozen and free cinders, ashes, sods, refuse, or other deleterious materials
 - .2 The maximum size of boulders permitted in backfill will be 0.2 m³ or of 300 mm average diameter.
- .3 Clay
 - .1 Clay is required to meet the proper hydraulic properties as required by the “Standards for Landfills in Alberta”. The maximum Hydraulic Conductivity for clay should be 1×10^{-7} m/s.
- .4 Pit Locations:
 - .1 The pit location for the clay liner material has been identified and is located on-site.
 - .2 The pit location for subgrade fill has been identified and is located on-site.
 - .3 A location for topsoil has not been identified.
 - .4 Contractor shall be responsible for locating, organizing approvals for haul roads, screening or crushing to meet specified gradations, loading, hauling and all other associated work for the specific trenching, backfilling and compaction material requirements.

PART 3 – EXECUTION

3.1 SITE PREPARATION

- .1 Remove trees, shrubs, vegetation, fences and other obstructions, ice and snow, from surfaces to be excavated within limits indicated.
- .2 Strip topsoil from within limits of excavation and stockpile as directed.
- .3 If required to provide safe working conditions and to prevent cave-ins and loose soil from falling into excavations, protect excavations by temporary shoring, bracing, or other suitable methods.
- .4 No extra payment will be made for supplying, placing, maintaining, and removing sheeting, bracing, shoring, or other means of temporary support.

3.2 DEWATERING

- .1 Excavations must be maintained in a dry condition for soil placement. Methods of dewatering are the responsibility of the Contractor.

- .2 Dispose of water in a manner not detrimental to public health, environment, public and private property, or any portion of work completed or under construction.

3.3 EXCAVATION

- .1 Strip Topsoil (and Subsoil where required) in accordance with Section 31 14 13 and stockpile in the designated area.
- .2 Dispose of unsuitable organic soils and other unsuitable, native, or uncontaminated material in the waste area designated by the owner.
- .3 Remove and dispose of all water, snow, and surface ice prior to excavation.
- .4 Prevent loss of soil and sloughing of slopes if springs or seepage are encountered within excavation.
- .5 Remove boulders, loose bedrock, soil blocks, and other fragments that may slide or roll into excavated areas, which, in the opinion of the Owner or the Contractor, are unsafe or appear to endanger persons, work, or property.
- .6 Stockpile excavated material in an area approved by the Engineer. Separate the stockpiles (topsoil, subgrade, clay) in separate areas to avoid mixing.

3.6 BACKFILLING

- .1 Do not proceed with backfilling operations until Engineer has inspected installations.
- .1 Use common or granular backfill material as indicated or as required by the Engineer.
- .2 Do not place backfill in freezing weather without written permission of Engineer.
- .3 Shoring, sheeting, and bracing:
- .1 Unless otherwise shown on drawings, or directed by Engineer, remove sheeting and shoring from trench during backfilling operations.
- .2 Do not remove bracing until backfilling has reached level of bracing.

3.7 ACCESS TO PROPERTIES
AND STREET MAINTENANCE

- .1 Until the date of substantial completion, the Contractor, at his costs, shall be responsible for street maintenance and access to properties.
- .2 Such maintenance and access to properties shall include providing proper drainage, temporary gravel streets, street levelling with use of motor patrol, providing towing services

3.9 CLEANUP

- .1 The Contractor shall be required to restore all roadways and areas affected by his operation to conditions prior to construction start and to satisfaction of Engineer.
- .2 The Contractor shall provide a schedule to the Engineer which details how the construction program will be undertaken. This shall meet the approval of the Engineer and the Owner so they are assured that access to properties is maintained.

END OF SECTION

PART 1 – GENERAL1.1 INTENT .1

Read this Section in conjunction with other Sections for location and requirement of Subgrade Preparation specified herein.

1.2 DETAILED DRAWINGS .1

Not Used.

1.3 MEASUREMENT AND PAYMENT .1

Payment for Subgrade Preparation will be at the unit price per cubic metre as shown in the Bid Form based upon measurements taken by the Engineer.

.2

This price will include all cost in connection with labour, materials, placement, and all work incidental thereto.

PART 2 – PRODUCTS2.1 NOT USED .1

Not Used.

PART 3 – EXECUTION3.1 SUBGRADE PERPARATION .1

Where subgrade is existing waste located in cell within landfill, subgrade will be spread to be uniformly distributed. See Section 31 22 50 “Compacted Earth Fill” for specifications. Fill will be used to fill cell to capacity. Subgrade will be tampered to remove air voids. Shape and roll alternatively to obtain a smooth, even, and uniform compacted sub-grade.

.2

When the moisture content in the subgrade material is lower than that specified, water shall be added and mixed with the material to achieve uniform moisture content in the material to conform to the requirements.

.3

When the moisture content in the subgrade material is higher than that specified, the material shall dry by scarifying, disking and harrowing to achieve uniform moisture content in the material that conforms to the requirements.

.4

Remove and dispose of unsuitable materials as authorized by the Owners representative. Replace with an approved suitable material and compact as specified herein.

.5

The Contractor shall maintain the subgrade to the specified section, grades and condition required for filter fabric and/or granular material placement. The Contractor shall be responsible for providing interim drainage to prevent damage to the work or the causing of unstable conditions due to high moisture contents. No separate payment will be made for these items.

District of Lakeland No. 521	SUBGRADE PREPARATION	Section 31 27 00
Landfill Decommissioning		Page 2 of 2
Project Specification		2026-09-10

- .6 The subgrade shall pass density and proof rolling requirements prior to the placement of filter fabric and/or granular materials.

3.2 TOLERANCES .1

Shape and compact subgrade to the required cross-section and grade to within ± 10 mm of design elevations but not uniformly high or low and maintain surface drainage as required to protect the work.

END OF SECTION

PART 1 – GENERAL1.1 RELATED
REQUIREMENTS

- .1 Section 311413 – Soil Stripping and Stockpiling
- .2 Section 312320 – Earthwork and Granular Material Testing
- .3 Section 312700 – Subgrade Preparation

1.2 MEASUREMENT AND
PAYMENT

- .1 Payment for Compacted Clay Liner (CCL) will be at the unit price per cubic metre as shown in the Bid Form based upon measurements taken by the Engineer of the horizontal surface area covered after installation of the CCL.
- .2 This price will include all cost in connection with labour, materials, placement, and all work incidental thereto.

1.3 STORAGE AND
HANDLING REQUIREMENTS

- .1 Store materials in accordance with manufacturer's recommendations.
- .2 Store and protect from damage.
- .3 Replace defective or damaged materials with new.

PART 2 – PRODUCTS2.1 PRODUCTS

- .1 Clay will be sourced from Emma Lake transfer station (53.560119, - 105.887333).
- .2 The Clay will be tested to ensure proper hydraulic properties, as required by the "Standards for Landfills in Alberta".
- .3 Requirements for the CCL include:
 - .1 Minimum of 0.6 m compacted clay thickness,
 - .2 Maximum Hydraulic Conductivity of finished CCL should be 1×10^{-7} m/s.

PART 3 – EXECUTION3.1 EXAMINATION

- .1 Verification of Conditions: verify that conditions of substrate previously installed under other Sections or Contracts are acceptable for CCL installation, as approved by the Engineer.
- .1 Visually inspect substrate.
- .2 Inform Engineer of unacceptable conditions immediately upon discovery.
- .3 Proceed with installation only after unacceptable conditions have been remedied and after receipt of written approval to proceed from Engineer.

3.2 PREPARATION

.1

Temporary Erosion and Sedimentation Control:

- .1 Provide temporary erosion and sedimentation control measures to prevent soil erosion and discharge of soil-bearing water runoff or airborne dust to adjacent properties and walkways, according to sediment and erosion control plan, specific to site.
- .2 Inspect, repair, and maintain erosion and sedimentation control measures during construction until permanent vegetation has been established.
- .3 Remove erosion and sedimentation controls and restore and stabilize areas disturbed during removal.

3.3 PLACEMENT

.1

Place clay liner material in unfrozen condition.

.2

Place compacted clay liner on prepared compacted subsurface as indicated. Compact clay to 95% maximum density to ASTM D698. Clay lift to be compacted at a moisture content of +/- 2.0% of optimum moisture content as defined by ASTM D698. Scarify surface of each lift before placing additional clay. Compacted thickness of each lift not to exceed 150 mm.

3.3 BEDDING

.1

Dewater excavation, as necessary, to allow placement of liner in dry, unfrozen condition.

3.5 CLEANING

.1

Progress Cleaning: clean in accordance with relevant Sections.

- .1 Leave Work area clean at end of each day.
- .2 Final Cleaning: upon completion remove surplus materials, rubbish, tools, and equipment in accordance with Section 01 74 11 – Cleaning.
- .3 Waste Management: separate waste materials for reuse and recycling.

END OF SECTION

PART 1 – GENERAL1.1 DELIVERY STORAGE
AND HANDLING

- .1 Provide seed in standard containers clearly labeled with the following information:
- .1 Supplier's name and address
 - .2 Lot Number
 - .3 Net Mass
 - .4 Names and percentages of individual seed species
- .2 Protect seed from moisture, mould and damage while in transit and storage.
- .3 Provide fertilizer in standard containers clearly labeled with the following information:
- .1 Supplier's name and address
 - .2 Specified Composition
 - .3 Net Mass

PART 2 – PRODUCTS2.1 MATERIALS

- .1 For all manicured turf areas, a grass mixture of:
- .1 Kentucky Bluegrass — any two of the following:
 - Touchdown, Nugget, America or Midnight 35% by weight
 - .2 Creeping Red Fescue — either Boreal or Jasper 25% by weight
 - .3 Chewings Fescue — either Victory or Banner 30% by weight
 - .4 Redtop or turf type perennial ryegrass 10% by weight
- This seed mixture shall be applied at a rate of not less than 2.93 kg per 100 sq. metre (6.0 lb Per 1,000 ft²)
- .2 For all-natural areas that have been previously disturbed, a grass mixture of:
- .1 Western Wheatgrass (Walsh) 45% by weight
 - .2 Northern Wheatgrass (Elbee) 45% by weight
 - .3 Fall Rye 10% by weight
 - .4 This seed mixture shall be applied at a rate of not less than 70 kg/ha.
- .3 Provide seed and seed mixture that are free of all prohibited noxious weed seeds.
- .4 Provide Canada No. 1 Grade seed in accordance with the Government of Canada Seeds Act and Seeds Regulations. Do not provide seeds which are wet, mouldy, or otherwise damaged.
- .5 Provide fertilizer in accordance with Government of Canada Fertilizer Act and Fertilizers Regulations. Fertilizer is to be compatible with the seed mixture and the soil conditions.

PART 3 – EXECUTION**3.1 GENERAL**

- .1 Prepare topsoil surface for seeding as required by Engineer.
- .2 Apply materials during calm weather and on ground free of frost and standing water.
- .3 Measure the quantities of materials by weight.

3.2 APPLICATION OF SEEDS

- .1 Perform seeding operations at such a time of the year when climatic conditions are suitable for establishing grass stands.
- .2 Fine grade and loosen the surface to plow depth to obtain a proper seed bed without undue loss from high winds or ordinary rainfall.
- .3 Where the work adjoins existing vegetation, blend the application at least 300 mm into adjacent vegetated areas.
- .4 Protect seeded areas against damage.
- .5 Sow seed mixture by drilling with disk or shoe-type grass drill.
- .6 Apply seed uniformly at the rate specified.
- .7 Regulate the drill so that the seed is properly placed in the soil to a depth of 20 to 32 mm.
- .8 Apply fertilizer uniformly at the rate of 78.5 Kg per hectare using a fertilizer attachment.

3.3 MAINTENANCE

- .1 Re-apply seed to all areas that do not show a uniform stand of grass. Perform such reapplication to allow for establishment prior to Substantial Performance of the Work. A uniform stand of grass will be considered growth that shows no bare spots greater than 0.25 square meters in size and provides a minimum of eighty percent ground cover.
- .2 Areas seeded in the fall will be inspected in the following spring, one month after the staff of the growing season.

END OF SECTION

PART 1 – GENERAL

1.1 INTENT .1 Read this section in conjunction with other sections for location, use and placement of restoration of sitework specified herein.

1.2 DETAILED DRAWINGS .1 Not Applicable.

PART 2 – PRODUCTS

2.1 NOT USED .1 Not Used.

PART 3 – EXECUTION

3.1 RESTORATION – GENERAL .1 Restore all existing areas and sitework damaged or disturbed due to earthwork or other work of this Contract, back to their original condition.

3.2 RESTORATION OF LANDSCAPED AREAS .1 Replace topsoil in accordance with Section 31 14 13 – Soil Stripping and Stockpiling.

.2 Restore grassed areas by seeding in accordance with Section 31 29 00 – Grass Seeding.

3.3 RESTORATION OF CONCRETE STRUCTURES .1 Restore any damage to concrete curb & gutter, swales, sidewalks, and driveways back to their original condition (or better) that is damaged or disturbed by the installation of pipeline and associated work.

.2 The restoration of concrete monolithic sidewalks, curb & gutters, and swales will require reinforcing dowel between existing concrete structures and replacement concrete structures.

3.4 RESTORATION OF GRAVEL SURFACING .1 Push and windrow existing granular material prior to start of construction activities.

.2 Replace damaged gravel surface resulting from construction activities with base granular materials material to equal or greater thickness of existing gravel structure prior to construction.

.3 Grade gravel to match existing lines, grades, and elevations.

.4 Granular materials shall be in accordance with Section 31 23 20 – Earthwork and Granular Material Testing.

**3.5 RESTORATION OF HOT
MIX ASPHALT**

- .1 Restore any damage to asphalt pavement due to construction activities.
- .2 Where edges of existing paving have become ragged, cut paving to form a straight line prior to placing new paving.
- .3 Thoroughly clean edges of existing paving and coat with bituminous bonding agent prior to placing asphalt.
- .4 Place asphalt in maximum 75 mm lifts.
- .5 Compact new asphalt paving using a steel wheel roller with a minimum weight of 8 tonnes.
- .6 Ensure finished grade of asphalt paving conforms to existing surface with no rises, depressions, or ridges.

END OF SECTION